

## 2020 Zinc dust spray 400 ml

**Description** Zinc dust spray with excellent corrosion protection for all ferrous metals such as gates,

metal housings, machines, fittings, fences, etc. The contained zinc with a purity of 97% serves as a sacrificial material and thus protects with cathodic corrosion protection effect even when exposed to weathering by salt and water. Ideal for application on welded joints,

pipelines and tanks for chemical plants, pumps, trelliswork and carpentry.

**Advantages** 97% pure zinc - very good corrosion protection - metal-like appearance

**Application fields** Metalworking, industry, offshore

Application 1. The surface must be dry and free of grease and dust. Sand problem surfaces and old

paintwork.

2. Shake for at least 2 minutes before use

3. Spray on in 2-3 spray coats, spraying distance 15-25 cm.

4. After use, spray overhead to prevent clogging

## **Technical data**

Chemical base	Zinc, alkyd resin
Colour	Silver
Density	0,73 g/ml
Curing	24 h at room temperature
Recommended layer	ca. 40 µm
thickness	
-	-
Propellant	Dimethylether
Application temperature	15°C - 25°C
Storage temperature	10°C - 30°C
Shelf life	24 months
Packaging	400 ml aerosol
Product variants	A202040001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.