

2030 Zinc paste 500 ml

Description	Highly effective zinc repair paint with high application strength and long-term corrosion protection. Ideal for quick mending and repair of injured or damaged galvanized surfaces. Meets requirements for the repair of zinc coatings according to DIN 1461 and ASTM A780. The product contains 90% metallic zinc in the dry film and is temperature resistant up to approx. 300°C.
Advantages	Excellent weather protection - for zinc repairs according to DIN 1461 - extremely strong adhesion - easy application of 100 microns
Application fields	Metalworking, industry
Application	1. The surface must be dry, grease- and dust-free. Sand problematic substrates and old paintwork. 2. Stir well before use. 3. Apply with a brush or a spray gun (if necessary adjust viscosity with paint thinner). Overcoatable with PVC-and acrylate-based paints. Do not use alkyd resin paints (synthetic resins).

Technical data

Chemical base	Zinc, alkyd resin
Colour	Silver
Density	2,14 g/ml
Curing	2-3 d at room temperature
Recommended layer thickness	>100 µm (DIN EN ISO 1461)
Consumption	ca. 250 ml/m ² at 100 µm (VdL-RL 08)
Propellant	-
Application temperature	15°C - 25°C
Storage temperature	10°C - 30°C
Shelf life	12 months
Packaging	500 ml tin can
Product variants	A203050001 500 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.