

4615 Adhesive lubricant spray 400 ml

Description	Adhesive lubricant spray is a highly viscous, tough elastic lubricant, particularly effective against wear, oxidation and corrosion. After spraying the active ingredient can creep deeply. A well-adhering, non-embrittling lubricating film remains on the surface after the solvent has evaporated. Has a noise-absorbing effect, prevents jerky starting, protects against corrosion and wear. The layer does not become brittle in the cold, is salt water resistant, has a low dust binding capacity and gums, does not coke and does not burn.
Advantages	Protects against corrosion and wear - no staining - temperature resistant (-30°C to +200°C)
Application fields	Auto repair shops, metalworking
Application	1. The substrate should be dry, dust, grease and rust free. 2. Bring the can to room temperature and shake vigorously. 3. Spray the surface to be treated several times and allow to dry briefly. The optimal spray distance is between 25 and 30 cm.

Technical data

Chemical base	Mineral oil
Colour	Yellow
Density	0,77 g/ml (20°C)
Temperature resistance	-30°C - 200°C
Solvent (%)	32
-	-
Propellant	Propane/butane
Application temperature	10°C - 25°C
Storage temperature	-5°C - 30°C
Shelf life	36 months
Packaging	400 ml aerosol
Product variants	A461540001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.