

TECHNICAL DATA SHEET

4615

Adhesive lubricant spray 400 ml

Adhesive lubricant spray is a highly viscous, tough elastic lubricant, particularly effective against wear, oxidation and corrosion. After spraying the active ingredient can creep deeply. A well-adhering, non-embrittling lubricating film remains on the surface after the solvent has evaporated. Has a noise-absorbing effect, prevents jerky starting, protects against corrosion and wear. The layer does not become brittle in the cold, is salt water resistant, has a low dust binding capacity and gums, does not coke and does not burn.

Protects against corrosion and wear
Low soiling
temperature resistant (-30 °C to +200 °C)

Application fields

Auto repair shops, metalworking

Application

1. The substrate should be dry, dust, grease and rust free. 2. Bring the can to room temperature and shake vigorously. 3. Spray the surface to be treated several times and allow to dry briefly. The optimal spray distance is between 25 and 30 cm.

Overview

Property	Value	Unit	Norm / Condition
Chemical Base	Mineral oil		
Color	Yellow		
Density	0,77	g/cm ³	22°C
Temperature resistance	-30 - 200	°C	
Solvent	32	%	
Propellant	Propane/butane		
Application Temperature	10 - 25	°C	

Packaging

Packaging	400 ml aerosol		
Product variants	A461540001 400 ml		
Recommended storage	5 - 25	°C	
Shelf life *	36	months	

* in the sealed container

**TECHNICAL DATA SHEET
4615**

Disclaimer

We provide technical application advice to the best of our knowledge. However, all information and recommendations regarding the suitability and application of the products do not exempt the purchaser from performing their own tests and trials to determine the suitability of the products for the intended processes and purposes. Our advisory services related to our products, their processing, and properties are provided without obligation. The application, use, and processing of the products are beyond our control and are therefore the sole responsibility of the user. Naturally, we guarantee the impeccable quality of our products in accordance with our General Terms and Conditions of Sale and Delivery.

Please also refer to our safety data sheet.

Approved: 26.11.2024
MatNo: 93887