

4625 PTFE Spray 400 ml

| | |
|---------------------------|--|
| Description | Silicone-free lubricating, sliding and separating agent for metal, rubber, plastics and other materials based on PTFE. As a grease-free dry lubricant with a simultaneous non-stick effect, it is particularly well suited for applications where mineral oils or MoS2 cannot be used due to the risk of dirt. It is often used for gear parts, bushings, hinges, lock cylinders, sunroof mechanisms, snap locks, pedal linkages or V-belts. It fills in microscopic imperfections and protects against moisture and corrosion. The dry lubricant adheres to all metal, plastic and wood surfaces. |
| Advantages | Fat-free - water-repellent - non-stick - temperature resistant from - 190°C to + 260°C |
| Application fields | Auto repair shops, industry, metalworking |
| Application | 1. Shake the container well before use. 2. Spray the lubrication point. 3. Repeat if necessary. |

Technical data

| | |
|--------------------------------|-------------------|
| Chemical base | PTFE / binder |
| Colour | Transparent |
| Density | 0,64 g/ml |
| Temperature resistance | -190°C - 260°C |
| VOC (%) | 97,5 |
| - | - |
| Propellant | Propane/butane |
| Application temperature | 5°C - 35°C |
| Storage temperature | 5°C - 25°C |
| Shelf life | 24 months |
| Packaging | 400 ml aerosol |
| Product variants | A462540002 400 ml |

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.