

TECHNICAL DATA SHEET 4715

Power rust dissolver Spray 250 ml

Power Rust Remover mineral oil free is ideal for loosening and cleaning rusted connections and surfaces. The KENA®-technology penetrates deeply, encrustations are fractured and released. The concentrate formula allows for long penetrating action over several hours. Very economical and free of mineral oil.

Unique active ingredient formula
Economical in use
removes rust and encrustations

Application fields

Auto repair shops, metalworking, household

Application

1. Spray onto rusted connections / surfaces. 2. Depending on the degree of rust, allow to act up for 24 h. Work in with a brush or a towel. 3. Rinse with water or wipe off. 4. If necessary, repeat.

Note: May cause discoloration on surfaces or dissolve plastics. Check the suitability prior to use.

Overview

Property	Value	Unit	Norm / Condition
Chemical Base	Solvent-based surfactant solution		
Color	Light yellow		
Density	0,75	g/cm ³	22°C
pH-value	5,0 - 7,0		
Free from	Mineral oil, silicone oil		
Special features	biologically degradable		
Propellant	Propane/butane		
Application Temperature	5 - 35	°C	

Packaging

Packaging	250 ml aerosol		
Product variants	A471525001 250 ml		
Recommended storage	5 - 25	°C	
Shelf life *	24	months	

* in the sealed container

**TECHNICAL DATA SHEET
4715**

Disclaimer

We provide technical application advice to the best of our knowledge. However, all information and recommendations regarding the suitability and application of the products do not exempt the purchaser from performing their own tests and trials to determine the suitability of the products for the intended processes and purposes. Our advisory services related to our products, their processing, and properties are provided without obligation. The application, use, and processing of the products are beyond our control and are therefore the sole responsibility of the user. Naturally, we guarantee the impeccable quality of our products in accordance with our General Terms and Conditions of Sale and Delivery.

Please also refer to our safety data sheet.

Approved: 26.11.2024
MatNo: 91616