

## 4740 Rust dissolver MoS2 Spray 400 ml

<b>Description</b>	Rust dissolver with MoS2-based high-pressure lubrication for loosening stuck connections and screw connections. Due to the excellent creeping effect, the rust dissolver penetrates deep-seated spaces. Provides additional protection against corrosion and displaces water and moisture. Due to the molybdenum disulphide (MoS2), the product can be used primarily at high temperatures and under extreme pressure loads. Molybdenum disulfide has the lowest coefficient of friction of any known lubricant.
<b>Advantages</b>	Lubrication even under high pressure loads - eliminates squeaking and creaking - very temperature-resistant - loosens stuck parts
<b>Application fields</b>	Auto repair shops, industry, metalworking
<b>Application</b>	1. Shake the container well before use. 2. Spray onto respective area. 3. Repeat if necessary. Note: Check material compatibility before use.

### Technical data

<b>Chemical base</b>	Mineral oil / MoS2
<b>Colour</b>	Grey
<b>Density</b>	0,68 g/ml (20°C)
<b>VOC (%)</b>	100
-	-
-	-
<b>Propellant</b>	Propane/butane
<b>Application temperature</b>	5°C - 35°C
<b>Storage temperature</b>	5°C - 25°C
<b>Shelf life</b>	24 months
<b>Packaging</b>	400 ml aerosol
<b>Product variants</b>	A474040001 400 ml

Find comprehensive advice on health, safety, and environmental protection in the corresponding safety data sheets.

This technical information leaflet is the result of careful testing and used to advise our customers. The information contained herein corresponds to our best knowledge. Since proper use does not lie within our influence, however, we can assume liability only for the perfect quality of the products we provided up to the point in time of delivery. We reserve the right to make any changes in this product information due to new knowledge.