05.11.2020	Kit Components
Product code	Description
0735-191118	ergo 0735
Components:	
0733-200407	ergo 0733 - Component A ergo 0735
0734-200407	ergo 0734 - Component B ergo 0735



Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2020 Version number 2 Revision: 05.11.2020 SECTION 1: Identification of the substance/mixture and of the company/undertaking - 1.1 Product identifier - Trade name: ergo 0733 - Component A ergo 0735 - 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. - Application of the substance / the mixture Epoxy resin adhesive - 1.3 Details of the supplier of the safety data sheet - Manufacturer/Supplier: Kisling AG Motorenstrasse 102 CH-8620 Wetzikon Tel: +41- 58-272 0 272 - Only representative (REACH) and importer (CLP): Kisling Deutschland GmbH Salzstraße 15 D-74676 Niedernhall Tel +49 8171 99982 30 - Further information obtainable from: ergo@kisling.com - Department issuing MSDS: ergo@kisling.com - 1.4 Emergency telephone number: +49-700-24 112 112 (KAR) **SECTION 2: Hazards identification** - 2.1 Classification of the substance or mixture - Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. - 2.2 Label elements - Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. - Hazard pictograms GHS07 GHS09 - Signal word Warning - Hazard-determining components of labelling: Phenol polymer with formaldehyde, glycidyl ether bisphenol-F-(epichlorhydrin) reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) - Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. - Precautionary statements P261 Avoid breathing vapours. (Contd. on page 2) DEGEN

DEGEN

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0733 - Component A ergo 0735

	(Contd. of page 1)
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
 Additional inf 	
EUH205 Conta	ains epoxy constituents. May produce an allergic reaction.
- Labelling of p	ackages where the contents do not exceed 125 ml
- Hazard pictog	
GHS07 GH	IS09
- Signal word V	Varning
- Hazard-deter	mining components of labelling:
	r with formaldehyde, glycidyl ether
bisphenol-F-(e	
	ct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
- Hazard staten	
H317 May cau	se an allergic skin reaction.
- Precautionary	
P261	Avoid breathing vapours.
P280	Wear protective gloves / eye protection.
P305+P351+P2	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
- 2.3 Other haz	
	Γ and vPvB assessment
- PBT: Not appl	
- vPvB : Not app	

SECTION 3: Composition/information on ingredients

*

- **3.2 Mixtures** - **Description:** Adhesive

- Dangerous components:		
CAS: 28064-14-4	Phenol polymer with formaldehyde, glycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 30 - ≤ 50%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-xxxx	bisphenol-F-(epichlorhydrin) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - < 25%
CAS: 51728-26-8 NLP: 500-111-9	pentaerythritol, ethoxylated, esters with acrylic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	> 5 - < 10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-xxxx	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 5 - ≤ 15%
CAS: 2530-83-8 EINECS: 219-784-2 Reg.nr.: 01-2119513212-58-xxxx	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	> 1 - < 3%
		(Contd. on page 2

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0733 - Component A ergo 0735

- Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
- After contact with skin, wash immediately with plenty of soap and water.
- If skin irritation continues, consult a doctor.
- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

- Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 - 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow product to reach sewage system or any water course.
 - 6.3 Methods and material for containment and cleaning up: Pick up mechanically. Dispose contaminated material as waste according to item 13.
 - 6.4 Reference to other sections See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 10 for information on "stability and reactivity".
 - See Section 13 for disposal information.

(Contd. on page 4)

Version number 2

Revision: 05.11.2020

Trade name: ergo 0733 - Component A ergo 0735

(Contd. of page 3)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire - and explosion protection: No special measures required.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

- Information about storage in one common storage facility: Store away from foodstuffs.

- Further information about storage conditions: Keep receptacle tightly sealed.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

MAK (Germany) vgl. Abschn. IVe

- DNELs	L.	
2530-83-8	[3-(2,3-epoxypro]	poxy)propyl]trimethoxysilane
Dermal	Acute, System	21 mg/kg bw (Worker)
	Longterm System	21 mg/kg bw/day (Worker)
Inhalative	Acute, System	147 mg/m ³ (Worker)
	Longterm System	147 mg/m ³ (Worker)
- PNECs		

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

PNEC Freshwater 1 mg/l

PNEC Marinewater 0.1 mg/l

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Clean skin thoroughly immediately after handling the product.
- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

(Contd. of page 4)

Trade name: ergo 0733 - Component A ergo 0735

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

0.1 Information on having hereical and chemin	
- 9.1 Information on basic physical and c - General Information	hemical properties
- Appearance:	
Form:	Pasty
	ADR 2.3.4: solid
Colour:	White
- Odour:	Characteristic
- Odour threshold:	Not determined.
- pH-value:	Not applicable.
- Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: > 200 °C
- Flash point:	>100 °C
- Flammability (solid, gas):	Not determined.
- Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Oxidising properties	Not determined.
- Vapour pressure:	Not applicable.
- Density:	Not determined.
- Relative density	Not determined.
- Vapour density	Not applicable.
- Evaporation rate	Not applicable.
- Solubility in / Miscibility with	
water:	Insoluble.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

(Contd. on page 6)

Version number 2

Revision: 05.11.2020

(Contd. of page 5)

Trade name: ergo 0733 - Component A ergo 0735

- 10.3 Possibility of hazardous reactions

Reacts with strong alkali. Reacts with strong acids.

Reacts with strong oxidising agents.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral LD50 11,400 mg/kg (Rat, male/female)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral LD50 8,025 mg/kg (Rat, male/female) (OECD TG 401)

Dermal LD50 4,250 mg/kg (Rabbit) (OECD TG 402)

- Primary irritant effect:

- Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

(Contd. on page 7)

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

(Contd. of page 6)

Trade name: ergo 0733 - Component A ergo 0735

- 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- Recommendation Disposal must be made according to official regulations.

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

|--|

- 14.1 UN-Number - ADR, IMDG, IATA	UN3077
- 14.2 UN proper shipping name - ADR	3077 ENVIRONMENTALLY HAZARDOUS
- IMDG	SUBSTANCE, SOLID, N.O.S. (Phenol polymer with formaldehyde, glycidyl ether, Bisphenol F epoxy resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE SOLID, N.O.S. (Phenol polymer with formaldehyde glycidyl ether, Bisphenol F epoxy resin), MARINE
- IATA	POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE SOLID, N.O.S. (Phenol polymer with formaldehyde glycidyl ether, Bisphenol F epoxy resin)
- 14.3 Transport hazard class(es)	
- ADR	
- Class - Label	9 (M7) Miscellaneous dangerous substances and articles. 9
- IMDG, IATA	
- Class - Label	9 Miscellaneous dangerous substances and articles. 9
- 14.4 Packing group - ADR, IMDG, IATA	III
	Product contains environmentally hazardous substances
- 14.5 Environmental hazards:	Phenol polymer with formaldehyde, glycidyl ether Bisphenol F epoxy resin Symbol (fish and tree)

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0733 - Component A ergo 0735

Special marking (IATA):	(Contd. of page
- Special marking (IATA):	Symbol (fish and tree)
 - 14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category - Stowage Code 	Warning: Miscellaneous dangerous substances ar articles. 90 F-A,S-F A SW23 When transported in BK3 bulk container, se 7.6.2.12 and 7.7.3.9.
- 14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
- Transport/Additional information:	ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
- ADR	
- Limited quantities (LQ) - Excepted quantities (EQ)	5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
- Transport category - Tunnel restriction code - Remarks:	3 - SV375: These substances are not subject to the other provisions
	ADR / RID if they are transported in individual composite packaging with a net quantity of no more than 1 of liquid substances or a net mass of no more than 5 I of solids per individual or inner packaging, provided th the packaging is used correspond to the general provisio of subsections 4.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG	
- Limited quantities (LQ) - Excepted quantities (EQ)	5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
- Remarks:	2.10.2.7: Marine pollutants in individual packaging or composi packaging with a net quantity per individual or inne packaging of no more than 5 L for liquids or a net ma per individual or inner packaging of no more than 5 kg for solids are not subject to any other provisions of this Coc applicable to marine pollutants, provided that the packaging complies with the general Meet the requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The the case of marine pollutants that also meet the criteria for inclusion in another class, all provisions of this Code the apply to any further hazards continue to apply.

Contd. on page 9) _____ DEGEN -

Version number 2

Revision: 05.11.2020

Trade name: ergo 0733 - Component A ergo 0735

	(Contd. of page 8)
- Remarks:	A 197 (375): These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (PHENOL POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER, BISPHENOL F EPOXY RESIN), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- National regulations:

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- ;

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- * Data compared to the previous version altered.



Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2020 Version number 2 Revision: 05.11.2020 SECTION 1: Identification of the substance/mixture and of the company/undertaking - 1.1 Product identifier - Trade name: ergo 0734 - Component B ergo 0735 - 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. - Application of the substance / the mixture Epoxy resin adhesive - 1.3 Details of the supplier of the safety data sheet - Manufacturer/Supplier: Kisling AG Motorenstrasse 102 CH-8620 Wetzikon Tel: +41- 58-272 0 272 - Only representative (REACH) and importer (CLP): Kisling Deutschland GmbH Salzstraße 15 D-74676 Niedernhall Tel +49 8171 99982 30 - Further information obtainable from: ergo@kisling.com - Department issuing MSDS: ergo@kisling.com - 1.4 Emergency telephone number: +49-700-24 112 112 (KAR) **SECTION 2: Hazards identification** - 2.1 Classification of the substance or mixture - Classification according to Regulation (EC) No 1272/2008 Skin Corr. 1B H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction. - 2.2 Label elements - Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. - Hazard pictograms GHS05 GHS07 - Signal word Danger - Hazard-determining components of labelling: N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine Butadiene-acrylonitrile copolymer trimethylhexane-1,6-diamine Fatty acids, C18 unsaturated dimers, polymers with tall oil fatty acids and triethylenetetramine m-phenylenebis(methylamine) 3,6-diazaoctanethylenediamin - Hazard statements H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. - Precautionary statements P261 Avoid breathing vapours. (Contd. on page 2) - DEGEN

DEGEN

Safety data sheet according to 1907/2006/EC, Article 31 Revision: 05.11.2020 Printing date 05.11.2020 Version number 2 Trade name: ergo 0734 - Component B ergo 0735 (Contd. of page 1) P280 Wear protective gloves / eye protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. - Labelling of packages where the contents do not exceed 125 ml - Hazard pictograms GHS07 GHS05 - Signal word Danger - Hazard-determining components of labelling: N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine Butadiene-acrylonitrile copolymer trimethylhexane-1,6-diamine Fatty acids, C18 unsaturated dimers, polymers with tall oil fatty acids and triethylenetetramine m-phenylenebis(methylamine) 3.6-diazaoctanethylenediamin - Hazard statements H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. - Precautionary statements P261 Avoid breathing vapours. P280 Wear protective gloves / eye protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P310 - 2.3 Other hazards - Results of PBT and vPvB assessment - PBT: Not applicable. - vPvB: Not applicable. **SECTION 3: Composition/information on ingredients** - 3.2 Mixtures - Description: Adhesive

- Dangerous components:		
CAS: 68683-29-4	Butadiene-acrylonitrile copolymer	> 15 - ≤ 30%
	Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 10563-29-8 EINECS: 234-148-4 Reg.nr.: 01-2119970376-29-xxxx	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	> 5 - ≤ 15%
CAS: 68082-29-1 NLP: 500-191-5	Fatty acids, C18 unsaturated dimers, polymers with tall oil fatty acids and triethylenetetramine Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 5 - < 10%
	•	(Contd. on page 3)

*

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

		(Contd. of page 2)
CAS: 104-15-4 EINECS: 203-180-0	p-toluenesulphonic acid (containing a maximum of 5 % H2SO4)	> 1 - ≤ 5%
Index number: 016-030-00-2	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 25620-58-0	trimethylhexane-1,6-diamine	≥ 2.5 - < 3%
EINECS: 247-134-8	Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	> 1 - < 2.5%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	> 1 - < 2.5%
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4,	≥ 0.1 - < 1%
Index number: 612-059-00-5	H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
- Additional information: For the	e wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
- After contact with skin, wash immediately with plenty of soap and water.
- If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- Rinse cautiously with water for several minutes.
- Remove contact lenses, if present and easy to do. Continue rinsing.
- After swallowing:
- Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

- Do not inhale explosion gases or combustion gases.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

(Contd. of page 3)

- 6.1 Personal preca	utions, protective equipment and emergency procedures	
Wear protective eq	upment. Keep unprotected persons away.	
- 6.2 Environmental	precautions:	
Inform respective a	uthorities in case of seepage into water course or sewage system.	
	ct to reach sewage system or any water course.	
- 6.3 Methods and n	naterial for containment and cleaning up:	
Pick up mechanical	ly.	
Flush away residue	s with plenty of water.	
Dispose contaminat	ed material as waste according to item 13.	
Use neutralising ag	ent.	
- 6.4 Reference to of	ther sections	
See Section 7 for in	formation on safe handling.	
See Section 8 for in	formation on personal protection equipment.	
See Section 10 for i	nformation on "stability and reactivity".	
See Section 13 for	disposal information.	

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire - and explosion protection:

No special precautions are necessary if used and stored according to specifications.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

*

- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.

- Further information about storage conditions: Keep receptacle tightly sealed.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 8 A

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- 8.1 Control parameters

- Ingre	dients	with	limit	values	that	require	monitoring	at the	workplace:
mgre	uluius		mmu	ruiuco	unu	require	monitoring	at the	"or aprace.

1477-55-0 m-phenylenebis(methylamine)

MAK (Germany) als Dampf und Aerosol;vgl.Abschn.IV

112-24-3 3,6-diazaoctanethylenediamin

MAK (Germany) als Dampf und Aerosol;vgl.Abschn.IV

- DNELs

Oral	Acute, System	20 mg/kg (General population)				
	Longterm System	0.41 mg/kg bw/day (General population)				
Dermal	Acute, Local	1 mg/kg (General population)				
	Acute, System	8 mg/kg bw (General population)				
	Longterm Local	0.028 mg/kg bw/day (Worker)				
	Longterm System	0.57 mg/kg bw/day (Worker)				
Inhalative	Acute, System	1,600 mg/m ³ (General population)				
		5,380 mg/m ³ (Worker)				
	Longterm System	0.29 mg/m ³ (General population)				

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

112-24-3 3,6-diazaoctarethylenediamin PNEC Freshwater 0.19 mg/l PNEC Freshwater sed 95.9 mg/kg PNEC Marinewater 0.038 mg/l PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg PNEC Marinewater sed 19.2 mg/kg PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2		(Contd. of page 4)					
112-24-3 3,6-diazaoctanethylenediamin PNEC Freshwater 0.19 mg/l PNEC Freshwater sed 95.9 mg/kg PNEC Marinewater 0.038 mg/l PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls Personal protective equipment: - General protective equipment: - General protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Kcep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. - Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves more one-meadation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and		1 mg/m ³ (Worker)					
PNEC Freshwater 0.19 mg/l PNEC Freshwater sed 95.9 mg/kg PNEC Marinewater 0.038 mg/l PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. -8.2 Exposure controls -Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. - Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. - Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves more to each use for their proper condition	- PNECs						
PNEC Freshwater sed 95.9 mg/kg PNEC Marinewater 0.038 mg/l PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - General protective and hygienic measures: The usual protective and hygienic measures: The usual protective and hygienic measures: The usual protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manu	112-24-3 3,6-diazaoctanethylenediamin						
PNEC Marinewater 0.038 mg/l PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - Prersonal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ Check protection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to b	PNEC Freshwater	0.19 mg/l					
PNEC Soil 19.1 mg/kg PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calcu	PNEC Freshwater sed	95.9 mg/kg					
PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. -8.2 Exposure controls - Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material - Potertation time of glove material The seact break tro	PNEC Marinewater	0.038 mg/l					
PNEC STP 4.25 mg/l PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the 	PNEC Soil	19.1 mg/kg					
PNEC Marinewater sed 19.2 mg/kg - Additional information: The lists valid during the making were used as basis. - 8.2 Exposure controls - Personal protective equipment: - General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation/ Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ Check protective gloves material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves General of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Pretration time of glove material Check protection: Tightly se	PNEC STP						
 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The seak trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 	PNEC Marinewater sed	0					
 Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation. Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 	- Additional information: The lists valid during the making were used as basis.						
 Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation. Paterial of gloves The solution of the gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Pertertion fine of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 	- 8.2 Exposure controls						
The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Pretertion fine of glove material The selection. Pretertion fine of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles		uipment:					
 Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. - Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles							
 Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
 Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the gloves material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
 Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 - Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles							
 Filter A/P2 Protection of hands: Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection: Tightly sealed goggles							
 Protective gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles	- Protection of hands:						
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles	Protective gloves (EN 3	74)					
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles	Check protective gloves	prior to each use for their proper condition.					
 the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 		recommendation to the glove material can be given for the product/ the preparation/					
 Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles							
 and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
 resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles							
 application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 							
 - Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles 		naterial can not be calculated in advance and has distribute to be checked prior to the					
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. - Eye protection: Tightly sealed goggles		ove material					
- Eye protection: Tightly sealed goggles							
- Body protection: Use protective suit.							
	- Body protection: Use p	protective suit.					
	SECTION 9: Phys	ical and chemical properties					
SECTION 9: Physical and chemical properties	- 9.1 Information on bas	sic physical and chemical properties					
SECTION 9: Physical and chemical properties - 9.1 Information on basic physical and chemical properties	- General Information						
- 9.1 Information on basic physical and chemical properties	- Appearance:						
- 9.1 Information on basic physical and chemical properties - General Information	Form:	Pasty					
 - 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty 							
- 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty ADR 2.3.4: solid		Black					
- 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty ADR 2.3.4: solid Colour: Black							
- 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty ADR 2.3.4: solid Colour: Black - Odour: Characteristic							
- 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty ADR 2.3.4: solid Colour: Black - Odour: Characteristic - Odour threshold: Not determined.	- pH-value:	Not applicable.					
- 9.1 Information on basic physical and chemical properties - General Information - Appearance: Form: Pasty ADR 2.3.4: solid Colour: Black - Odour: Characteristic - Odour threshold: Not determined.							

(Contd. on page 6)

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

		(Contd. of page 5)
- Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Undetermined.	
- Flash point:	Not applicable.	
- Flammability (solid, gas):	Not determined.	
- Decomposition temperature:	Not determined.	
- Auto-ignition temperature:	Product is not self-igniting.	
- Explosive properties:	Product does not present an explosion hazard.	
- Explosion limits: Lower: Upper: - Oxidising properties	Not determined. Not determined. Not determined.	
- Vapour pressure:	Not applicable.	
- Density: - Relative density - Vapour density - Evaporation rate	Not determined. Not determined. Not applicable. Not applicable.	
- Solubility in / Miscibility with water:	Insoluble.	
- Partition coefficient: n-octanol/water:	Not determined.	
- Viscosity: Dynamic: Kinematic: - 9.2 Other information	Not applicable. Not applicable. No further relevant information available.	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability

*

- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Strong exothermic reaction with acids.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:				
25620-58-0 trimethylhexane-1,6-diamine				
Oral	LD50	910 mg/kg (Rat, male/female)		
1477-55-	0 m-phen	nylenebis(methylamine)		
Oral	LD50	930 mg/kg (Rat, male/female)		
Dermal	LD50	3,100 mg/kg (Rat, male/female)		
	•	(Contd. on	page 7)	

- DEGEN

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

		(Contd. of page 6)				
Inhalative	LC50/4 h	1.34 mg/l (Rat, male/female)				
90-72-2 2,	90-72-2 2,4,6-tris(dimethylaminomethyl)phenol					
Oral	LD50	1,200 mg/kg (Rat, male/female)				
Dermal	LD50	1,280 mg/kg (Rat, male/female)				
112-24-3	3,6-diazao	ctanethylenediamin				
Oral	LD50	1,716 mg/kg (Rabbit)				
Dermal	LD50	1,465 mg/kg (Rabbit)				

- Primary irritant effect:

- Skin corrosion/irritation

Causes severe skin burns and eye damage.

- Serious eye damage/irritation
- Causes serious eye damage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

25620-58-0 trimethylhexane-1,6-diamine

EC50/24 h 31.5 mg/l (DA)

- 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

(Contd. of page 7)

Trade name: ergo 0734 - Component B ergo 0735

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN3259
14.2 UN proper shipping name ADR	3259 AMINES, SOLID, CORROSIVE, N.O.S. (N'-(: aminopropyl)-N,N-dimethylpropane-1,3-diamine)
IMDG, IATA	AMINES, SOLID, CORROSIVE, N.O.S. (N'-(3 aminopropyl)-N,N-dimethylpropane-1,3-diamine)
14.3 Transport hazard class(es)	
ADR	
at the second se	
Class Label	8 (C8) Corrosive substances. 8
IMDG, IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group	0
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code): EMS Number:	80 EASP
Segregation groups	F-A,S-B Alkalis
Stowage Category	A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	
•	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LO)	1 kg
Limited quantities (LQ) Excepted quantities (EQ)	1 kg Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 500 g
Transport category	2
Tunnel restriction code	E
IMDG	1 kg
Limited quantities (LQ)	1 kg Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per unter packaging: 50 g
	(Contd. on page

Printing date 05.11.2020

Version number 2

Revision: 05.11.2020

Trade name: ergo 0734 - Component B ergo 0735

- UN "Model Regulation": UN 3259 AMINES, SOLID, CORRO (3-AMINOPROPYL)-N,N-DIMETH DIAMINE), 8, II	/

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- National regulations:

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H302 Harmful if swallowed.

- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity oral Category 4
- Skin Corr. 1B: Skin corrosion/irritation Category 1B
- Skin Corr. 1C: Skin corrosion/irritation Category 1C
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3
- * Data compared to the previous version altered.