

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- -1.1 Product identifier
- Trade name: 1305 Component A 1307
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Adhesives

Resin

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- -1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- -2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms









GHS05

GHS07

GHS08 GHS09

- Signal word Danger
- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

 α,α -dimethylbenzyl hydroperoxide

2-hydroxyethyl methacrylate

methacrylic acid, monoester with propane-1,2-diol

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

(Contd. on page 2)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER/doctor. P310

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- -2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable. - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	> 30 - ≤ 50%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	> 5 - ≤ 15%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α , α -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 %	≥ 3 - ≤ 5%
CAS: 150-76-5 EINECS: 205-769-8 Index number: 604-044-00-7	mequinol Repr. 2, H361d; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5	methacrylic acid Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C≥1 %	< 1%
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4	1,4-dihydroxybenzene Muta. 2, H341; Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302; Skin Sens. 1, H317	≥ 0.025 - < 0.1% (Contd. on page

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 2)

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

-4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

-5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

-5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

-5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

-6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

CH EN.

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 3)

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

	rol parameter		s that require monitoring at the workplace:
0	nethacrylic ac		, time require monetoring at the workplace.
			m value: 360 mg/m³, 100 ppm
`			m value: 180 mg/m ³ , 50 ppm
		Sc;	
	1,4-dihydrox	•	
MAK (Sv			m value: 2 e mg/m³
		ong-ter	m value: 2 e mg/m³ M2·
- DNELs			
	-1 methacryli	ic acid	, monoester with propane-1,2-diol
Dermal			4.2 mg/kg bw/day (General population)
123-31-9	1,4-dihydrox	ybenz	ene
Dermal	Longterm Sy	ystem	64 mg/kg bw/day (General population)
			128 mg/kg bw/day (Worker)
Inhalative	Longterm Lo	ocal	0.5 mg/m³ (General population)
			1 mg/m³ (Worker)
	Longterm Sy	ystem	1.74 mg/m³ (General population)
			7 mg/m³ (Worker)
- PNECs			
	•	ic acid	, monoester with propane-1,2-diol
Oral PNI	EC oral		mg/kg Food (General population)
PNI	EC Freshwater	r	0.904 mg/l (General population)
PNI	EC Freshwater	r sed	6.28 mg/kg (General population)
PNI	EC Marinewat	ter	0.904 mg/l (General population)
	EC Soil		0.727 mg/kg (General population)
	EC STP		10 mg/l (General population)
			6.28 mg/kg (General population)
	1,4-dihydrox	•	
PNI	EC Freshwater	r	0.114 mg/l (Contd. on pag

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

- CAS No. Designation of material % Type Value Unit

- Additional Occupational Exposure Limit Values for possible hazards during processing: 144-62-7 oxalic acid MAK (Switzerland) | Long-term value: 1 e mg/m³

- Additional information: The lists valid during the making were used as basis.
- -8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

-9.1 Information on basic physical and chemical properties

- General Information

Colour: Transparent
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

(Contd. on page 6)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 5) - Lower and upper explosion limit Not determined. - Lower: - Upper: Not determined. > 100 °C - Flash point: - Decomposition temperature: Not determined. Not determined. -pH - Viscosity: Not determined. - Kinematic viscosity - Kinematic viscosity 6,000 mPas (Brookfield (4/20)) - Dynamic at 20 °C: - Solubility Not miscible or difficult to mix. - water: Not determined. - Partition coefficient n-octanol/water (log value) Not determined. - Vapour pressure: - Vapour pressure: - Density and/or relative density 1.06 g/cm³ - Density at 20 °C: Not determined. - Relative density Not determined. - Vapour density -9.2 Other information - Appearance: - Form: Fluid - Important information on protection of health and environment, and on safety. Product is not self-igniting. - Ignition temperature: - Explosive properties: Product does not present an explosion hazard. - Change in condition - Softening point/range Not determined. - Oxidising properties Not determined. - Evaporation rate - Information with regard to physical hazard classes Void - Explosives Void - Flammable gases - Aerosols Void - Oxidising gases Void - Gases under pressure Void - Flammable liquids Void - Flammable solids Void - Self-reactive substances and mixtures Void - Pyrophoric liquids Void - Pyrophoric solids Void - Self-heating substances and mixtures Void - Substances and mixtures, which emit flammable gases in contact with water Void Void - Oxidising liquids Void - Oxidising solids - Organic peroxides Void - Corrosive to metals Void Void - Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

(Contd. on page 7)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 6)

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- -10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:					
10595-06-9 2-phenoxyethyl methacrylate					
Oral LD50 5,050 mg/kg (Rat, n		5,050 mg/kg (Rat, male/female)			
868-77-9 2	868-77-9 2-hydroxyethyl methacrylate				
Oral LD50 5,050 mg/kg (Rat, male/female)		5,050 mg/kg (Rat, male/female)			
Dermal	LD50	3,000 mg/kg (Rabbit)			
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide				
Oral	LD50	382 mg/kg (Rat, male/female)			
Dermal	LD50	500 mg/kg (Rat, male/female)			
Inhalative	Inhalative LC50/4 h 1.37 mg/l (Rat, male/female)				
79-41-4 m	79-41-4 methacrylic acid				
Oral	LD50	1,320 - 2,260 mg/kg (Rat, male/female)			
Dermal	LD50	500 - 1,000 mg/kg (Rabbit)			
Inhalative	Inhalative LC50/4 h 7,100 mg/l (Rat, male/female)				
123-31-9 1	123-31-9 1,4-dihydroxybenzene				
Oral	LD50	375 mg/kg (Rat, male/female) (OECD 401)			
Dermal	LD50	> 2,000 mg/kg (Rabbit) (OECD 402)			

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2
- -11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

CH-EN

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 7)

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.

	- Toxicity to fish:		
	868-77-9 2	-hydroxyethyl methacrylate	
	LC50/96 h	213 - 242 mg/l (Pimephales promelas)	
ſ	123-31-9 1	,4-dihydroxybenzene	

- 12.2 Persistence and degradability No further relevant information available.
- -12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

LC50/96 h 0.638 mg/l (Oncorhynchus mykiss)

- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects No further relevant information available.
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

- 14.1 UN number or ID number - ADR, IMDG, IATA	UN3082
- 14.2 UN proper shipping name	
-ADR	3082 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy methacrylate)
- IMDG	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate, cumene hydroperoxide), MARINI
	POLLUTANT
- IATA	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy methacrylate)

CH-EN -

Version number 6 (replaces version 5) Printing date 10.04.2023 Revision: 10.04.2023

Trade name: 1305 - Component A 1307

	(Contd. of page
- 14.3 Transport hazard class(es)	
- ADR	
- Class	9 (M6) Miscellaneous dangerous substances and articles.
- IMDG, IATA - Class	0 Missellaneous dangerous substances and enticles
- Class - Label	9 Miscellaneous dangerous substances and articles.9
- 14.4 Packing group - ADR, IMDG, IATA	III
- 14.5 Environmental hazards:- Marine pollutant:- Special marking (ADR):- Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
 - 14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category 	Warning: Miscellaneous dangerous substances an articles. 90 F-A,S-F A
- 14.7 Maritime transport in bulk according to IM instruments	Not applicable.
- Transport/Additional information:	ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code - Remarks:	Maximum net quantity per outer packaging: 1000 ml 3 (-) SV375: These substances are not subject to the other provision of ADR / RID if they are transported in individual o composite packaging with a net quantity of no mor than 5 l of liquid substances or a net mass of no mor than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to th general provisions of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. (Contd. on page 1)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

	(Contd. of page
- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
- Remarks:	2.10.2.7:
	Marine pollutants in individual packaging or composit
	packaging with a net quantity per individual or inne packaging of no more than 5 L for liquids or a net mas
	per individual or inner packaging of no more than 5 k
	for solids are not subject to any other provisions of this
	Code applicable to marine pollutants, provided that th
	packaging complies with the general Meet th
	requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8
	In the case of marine pollutants that also meet th
	criteria for inclusion in another class, all provisions of
	this Code that apply to any further hazards continue t apply.
	аррту.
- IATA - Remarks:	A 197 (375):
- Kemarks.	These substances when transported in single o
	combination packagings containing a net quantity pe
	single or inner packaging of 5 L or less for liquids of
	having a net mass of 5 kg or less for solids, are no
	subject to any other provisions of these Regulation
	provided the packagings meet the general provisions of
	5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (2
	PHENOXYETHYL METHACRYLATE), 9, III

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- -15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.

(Contd. on page 11)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1305 - Component A 1307

(Contd. of page 10) H332 Harmful if inhaled. H335 May cause respiratory irritation. H341 Suspected of causing genetic defects. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. - Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. E: Organic peroxides - Type E/F Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Muta. 2: Germ cell mutagenicity – Category 2 Carc. 2: Carcinogenicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4 -* Data compared to the previous version altered.

CH-EN