



Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

-1.1 Product identifier

- Trade name: 1306 Component B 1307
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Adhesives

Hardening agent / Curing agent

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- -1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms









GHS05

GHS07

GHS08 GHS09

- Signal word Danger

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide

2-hydroxyethyl methacrylate

methacrylic acid, monoester with propane-1,2-diol

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

(Contd. on page 2)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- -2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	> 30 - ≤ 50%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	> 5 - ≤ 15%
CAS: 1187441-10-6 EC number: 810-703-1	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide Eye Dam. 1, H318; Skin Sens. 1B, H317	≥ 3 - ≤ 5%
CAS: 150-76-5 EINECS: 205-769-8 Index number: 604-044-00-7	mequinol Repr. 2, H361d; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 92-84-2 EINECS: 202-196-5	phenothiazine STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	≥ 0.1 - < 0.25%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5	methacrylic acid Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	< 1%

⁻ Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- -4.1 Description of first aid measures
- General information: Remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

(Contd. of page 2)

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

-5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

-5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

-5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

-6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

(Contd. on page 4)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

(Contd. of page 3)

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

-8.1 Control parameters

T 11 4 141	The second secon		
- Ingredients with limit values that require monitoring at the workplace:			
92-84-2 phenothiazine			
MAK (Switzerlan	K (Switzerland) Long-term value: 5 e mg/m ³		
	H;		
79-41-4 methacr	ylic acid		
MAK (Switzerlan	MAK (Switzerland) Short-term value: 360 mg/m³, 100 ppm		
		m value: 180 mg/m ³ , 50 ppm	
	SSc;		
- DNELs			
27813-02-1 meth	27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Dermal Longtern	Dermal Longterm System 4.2 mg/kg bw/day (General population)		
- PNECs			
27813-02-1 meth	27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Oral PNEC oral		mg/kg Food (General population)	
PNEC Fresh	nwater	0.904 mg/l (General population)	
PNEC Fresh	nwater sed	6.28 mg/kg (General population)	
PNEC Mari	newater	0.904 mg/l (General population)	
PNEC Soil		0.727 mg/kg (General population)	
PNEC STP		10 mg/l (General population)	
PNEC Marinewater sed		6.28 mg/kg (General population)	

- Additional information: The lists valid during the making were used as basis.
- -8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 5)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

(Contd. of page 4)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

-9.1 Information on basic physical and chemical properties

- General Information

- Colour: Dark blue
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

- Lower and upper explosion limit

- Lower:
- Upper:
- Upper:
- Flash point:
- Decomposition temperature:
- pH

Not determined.
101 °C
Not determined.
Not determined.
Not determined.

- Viscosity:

- Kinematic viscosity Not determined.

- Kinematic viscosity

- **Dynamic at 20 °C:** 6,000 mPas (Brookfield (4/25))

- Solubility

- water: Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)
 - Vapour pressure:
 Not determined.
 Not determined.

- Vapour pressure:

- Density and/or relative density

- Density at 20 °C:

- Relative density

- Vapour density

Not determined.

Not determined.

-9.2 Other information

- Appearance:

- Form: Fluid
- Important information on protection of health and

environment, and on safety.

- **Ignition temperature:** Product is not self-igniting.

- **Explosive properties:** Product does not present an explosion hazard.

Change in conditionSoftening point/range

- Oxidising properties
- Evaporation rate

Not determined.

Not determined.

- Information with regard to physical hazard classes

- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Void

(Contd. on page 6)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

		(Contd. of page 5
- Flammable solids	Void	
- Self-reactive substances and mixtures	Void	
- Pyrophoric liquids	Void	
- Pyrophoric solids	Void	
- Self-heating substances and mixtures	Void	
- Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
- Oxidising liquids	Void	
- Oxidising solids	Void	
- Organic peroxides	Void	
- Corrosive to metals	Void	
- Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- -10.1 Reactivity No further relevant information available.
- -10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50	- LD/LC50 values relevant for classification:		
10595-06-	10595-06-9 2-phenoxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (Rat, male/female)	
868-77-9 2	868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (Rat, male/female)	
Dermal	LD50	3,000 mg/kg (Rabbit)	
79-41-4 m	79-41-4 methacrylic acid		
Oral	LD50	1,320 - 2,260 mg/kg (Rat, male/female)	
Dermal	LD50	500 - 1,000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	7,100 mg/l (Rat, male/female)	

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

- Additional toxicological information:

(Contd. of page 6)

- Additional toxicological information.
- No experimentally found toxicological data are available for this preparation.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2
- -11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- Toxicity to fish:

868-77-9 2-hydroxyethyl methacrylate

LC50/96 h 213 - 242 mg/l (Pimephales promelas)

- -12.2 Persistence and degradability No further relevant information available.
- -12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- -12.7 Other adverse effects No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number - ADR, IMDG, IATA	UN3082
- 14.2 UN proper shipping name	
- ADR	3082 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate)
- IMDG	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl
	methacrylate), MARINE POLLUTANT
- IATA	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate)

(Contd. on page 8)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

9 (M6) Miscellaneous dangerous substances an articles.
9
9 Miscellaneous dangerous substances and articles.9
III
Product contains environmentally hazardou substances: 2-phenoxyethyl methacrylate
Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
Warning: Miscellaneous dangerous substances an articles.
90
F-A,S-F A
10
Not applicable.
ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
5L
Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
3
(-) SN275
SV375: These substances are not subject to the other provision of ADR / RID if they are transported in individual of composite packaging with a net quantity of no more than 5 l of liquid substances or a net mass of no more than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to the general provisions of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

	(Contd. of page 8
- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
D 1	Maximum net quantity per outer packaging: 1000 ml
- Remarks:	2.10.2.7: Marina pollutants in individual packaging or composit
	Marine pollutants in individual packaging or composit packaging with a net quantity per individual or inne
	packaging of no more than 5 L for liquids or a net mas
	per individual or inner packaging of no more than 5 kg
	for solids are not subject to any other provisions of thi
	Code applicable to marine pollutants, provided that th
	packaging complies with the general Meet th
	requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8
	In the case of marine pollutants that also meet th criteria for inclusion in another class, all provisions of
	this Code that apply to any further hazards continue to
	apply.
- IATA	
- Remarks:	A 197 (375):
	These substances when transported in single o
	combination packagings containing a net quantity pe
	single or inner packaging of 5 L or less for liquids o
	having a net mass of 5 kg or less for solids, are no subject to any other provisions of these Regulation
	provided the packagings meet the general provisions of
	5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS
_	SUBSTANCE, LIQUID, N.O.S. (2
	PHENOXYETHYL METHACRYLATE), 9, III

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- -15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.

(Contd. on page 10)

Printing date 10.04.2023 Version number 6 (replaces version 5) Revision: 10.04.2023

Trade name: 1306 - Component B 1307

(Contd. of page 9) H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. - Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4 - * Data compared to the previous version altered.

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

CH-EN