11.04.2023	Kit Components	
Product code	Description	
KIS 1315-220624	1315	
Components:		
KIS 1313-220624	1313 - Component A 1315	
KIS 1314-220623	1314 - Component B 1315	





Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- -1.1 Product identifier
- Trade name: 1313 Component A 1315
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Adhesives

Resin

- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- -1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

-2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms







GHS08



GHS09

GHS05 GHS07

- Signal word Danger

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate

2-hydroxyethyl methacrylate

α,α -dimethylbenzyl hydroperoxide

methacrylic acid, monoester with propane-1,2-diol mequinol

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

(Contd. of page 1)

H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

-2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	≥ 25 - ≤ 30%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	≥ 10 - ≤ 15%
CAS: 40220-08-4 EINECS: 254-843-6	(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate Eye Dam. 1, H318	> 5 - ≤ 15%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	> 5 - ≤ 15%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α, $α$ -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 %	≥ 3 - ≤ 5%
CAS: 107-21-1 EINECS: 203-473-3 Index number: 603-027-00-1	ethanediol STOT RE 2, H373; Acute Tox. 4, H302	> 1 - ≤ 5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Aquatic Chronic 1, H410	$\geq 0.25 - \leq 1\%$ (Contd. on page 3)

- CH-EN

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

_			(Contd. of page 2)
	CAS: 150-76-5	mequinol	≥ 0.1 - < 1%
	EINECS: 205-769-8	Repr. 2, H361d; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin	
	Index number: 604-044-00-7	Sens. 1, H317; Aquatic Chronic 3, H412	
	CAS: 79-41-4	methacrylic acid	< 1%
	EINECS: 201-204-4	Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318;	
	Index number: 607-088-00-5	Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335	
		Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	

⁻ Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

-4.1 Description of first aid measures

- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eve contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- -5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- -5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- -5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

(Contd. of page 3)

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- 8.1 (-8.1 Control parameters				
- Ingr	- Ingredients with limit values that require monitoring at the workplace:				
107-2	107-21-1 ethanediol				
MAK	MAK (Switzerland) Short-term value: 52 mg/m³, 20 ppm Long-term value: 26 mg/m³, 10 ppm H SSc;				
79-4	1-4 methacrylic	acid			
MAK	Ĺ		m value: 360 mg/m³, 100 ppm m value: 180 mg/m³, 50 ppm		
- DNE	ELs				
2781	3-02-1 methacry	ylic acid	, monoester with propane-1,2-diol		
Dern	nal Longterm Sys	stem 4.2	2 mg/kg bw/day (General population)		
- PNE	Cs				
2781	3-02-1 methacry	ylic acid	, monoester with propane-1,2-diol		
Oral	PNEC oral		mg/kg Food (General population)		
	PNEC Freshwate	er	0.904 mg/l (General population)		
	PNEC Freshwate	er sed	6.28 mg/kg (General population)		
	PNEC Marinewater 0.904 mg/l (General population)		0.904 mg/l (General population)		
	PNEC Soil		0.727 mg/kg (General population)		
	PNEC STP		10 mg/l (General population)		
	PNEC Marinewa	ater sed	6.28 mg/kg (General population)		
	•		(Contd on page 5)		

(Contd. on page 5)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

(Contd. of page 4)

- Additional information: The lists valid during the making were used as basis.
- -8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information	on hasic nhysi	cal and chem	ical properties
- 7.1 IIIIVI IIIAUVI	1 UH DASIC DHYSI	Cai anu Chen	ucai bi obci ucs

- General Information

Colour: Yellowish
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

- Lower and upper explosion limit

- Lower:
- Upper:
- Flash point:
- Decomposition temperature:
- pH

Not determined.
Not determined.
Not determined.
Not determined.

- Viscosity:

- Kinematic viscosity
- Dynamic at 20 °C:

Not determined.
5,500 mPas

- Solubility

- water: Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)
 - Vapour pressure:
 Not determined.
 Not determined.

(Contd. on page 6)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

	(Contd. of page 5
- Density and/or relative density	
- Density at 20 °C:	1.06 g/cm^3
- Relative density	Not determined.
- Vapour density	Not determined.
-9.2 Other information	
- Appearance:	
- Form:	Fluid
- Important information on protection of heal environment, and on safety.	th and
- Ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Change in condition	
- Softening point/range	
- Oxidising properties	Not determined.
- Evaporation rate	Not determined.
- Information with regard to physical hazard	classes
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Void
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flamma	able
gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

	(Contd. of page 6	
values rel	evant for classification:	
9 2-pheno	xyethyl methacrylate	
LD50	5,050 mg/kg (Rat, male/female)	
2-hydroxy	ethyl methacrylate	
LD50	5,050 mg/kg (Rat, male/female)	
LD50	3,000 mg/kg (Rabbit)	
α -dimethy	ylbenzyl hydroperoxide	
LD50	382 mg/kg (Rat, male/female)	
LD50	500 mg/kg (Rat, male/female)	
LC50/4 h	1.37 mg/l (Rat, male/female)	
107-21-1 ethanediol		
LD50	4,700 - 5,840 mg/kg (Rat, male/female)	
LD50	9,530 - 10,600 mg/kg (Rabbit)	
79-41-4 methacrylic acid		
LD50	1,320 - 2,260 mg/kg (Rat, male/female)	
LD50	500 - 1,000 mg/kg (Rabbit)	
LC50/4 h	7,100 mg/l (Rat, male/female)	
	P 2-phenon LD50 2-hydroxyo LD50 LD50 Δ -dimethy LD50 LC50/4 h ethanediol LD50 LD50 LD50 LD50 LD50 LD50 LD50 LD50	

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2
- -11.2 Information on other hazards

- Endocrin	e disrupting properties	
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.

- Toxicity to	o fish:		
868-77-9 2	868-77-9 2-hydroxyethyl methacrylate		
LC50/96 h	213 - 242 mg/l (Pimephales promelas)		
107-21-1 e	107-21-1 ethanediol		
LC0/96 h	8,050 - 72,900 mg/l (Fish)		

- -12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

(Contd. of page 7)

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects No further relevant information available.
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information - 14.1 UN number or ID number UN3082 - ADR, IMDG, IATA - 14.2 UN proper shipping name 3082 ENVIRONMENTALLY HAZARDOUS - ADR SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate) - IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate, cumene hydroperoxide), MARINE **POLLUTANT** ENVIRONMENTALLY HAZARDOUS -IATA SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate) - 14.3 Transport hazard class(es) - ADR - Class 9 (M6) Miscellaneous dangerous substances and articles. - Label 9 - IMDG, IATA - Class 9 Miscellaneous dangerous substances and articles. - Label

Version number 4 (replaces version 3) Printing date 11.04.2023 Revision: 11.04.2023

Trade name: 1313 - Component A 1315

- 14.4 Packing group	(Contd. of page 8
- ADR, IMDG, IATA	III
- 14.5 Environmental hazards: - Marine pollutant: - Special marking (ADR): - Special marking (IATA):	Product contains environmentally hazardous substances: 2-phenoxyethyl methacrylate Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
- 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
- Hazard identification number (Kemler code):- EMS Number:- Stowage Category	90 F-A,S-F A
- 14.7 Maritime transport in bulk according to IN instruments	Not applicable.
- Transport/Additional information:	ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code - Remarks:	3 (-) SV375: These substances are not subject to the other provision of ADR / RID if they are transported in individual o composite packaging with a net quantity of no mor than 5 l of liquid substances or a net mass of no mor than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to th general provisions of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
- Remarks:	Maximum net quantity per outer packaging: 1000 ml 2.10.2.7: Marine pollutants in individual packaging or composit packaging with a net quantity per individual or inne packaging of no more than 5 L for liquids or a net mas per individual or inner packaging of no more than 5 k for solids are not subject to any other provisions of thi Code applicable to marine pollutants, provided that th packaging complies with the general Meet th requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 In the case of marine pollutants that also meet th criteria for inclusion in another class, all provisions of this Code that apply to any further hazards continue to apply.

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

	(Contd. of page 9
- IATA	
- Remarks:	A 197 (375):
	These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-PHENOXYETHYL METHACRYLATE), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 11)

(Contd. of page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1313 - Component A 1315

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. E: Organic peroxides – Type E/F Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

- * Data compared to the previous version altered.

CH-EN





Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

-1.1 Product identifier

- Trade name: 1314 Component B 1315
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Adhesives

Hardening agent / Curing agent

- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- -1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

-2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms









GHS05

GHS07

GHS08

GHS09

- Signal word Danger

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate

2-hydroxyethyl methacrylate

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide methacrylic acid, monoester with propane-1,2-diol

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 1)

H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

-2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	≥ 25 - ≤ 30%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	≥ 10 - ≤ 15%
CAS: 40220-08-4 EINECS: 254-843-6	(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate Eye Dam. 1, H318	> 5 - ≤ 15%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	> 5 - ≤ 15%
CAS: 1187441-10-6 EC number: 810-703-1	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide Eye Dam. 1, H318; Skin Sens. 1B, H317	≥ 3 - ≤ 5%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5	methacrylic acid Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C≥1 %	< 1%
EC number: 911-490-9	N,N-Bis-(2-hydroxyethyl)-para-toluidine, ethoxylated Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 150-76-5 EINECS: 205-769-8 Index number: 604-044-00-7	mequinol Repr. 2, H361d; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 92-84-2 EINECS: 202-196-5	phenothiazine STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317 the wording of the listed bazard phrases refer to section 16	≥ 0.1 - < 0.25%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

- CH-EN

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 2)

SECTION 4: First aid measures

-4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eve contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

-5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

-5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

-5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

-6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

(Contd. on page 4)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 3)

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- 8.1 C	- 8.1 Control parameters						
- Ingr	- Ingredients with limit values that require monitoring at the workplace:						
79-41	79-41-4 methacrylic acid						
MAK	MAK (Switzerland) Short-term value: 360 mg/m³, 100 ppm						
	-	rm value: 180 mg/m³, 50 ppm					
	SSc;						
92-84	92-84-2 phenothiazine						
MAK	(Switzerland) Long-ter	m value: 5 e mg/m³					
	H;						
- DNE	-DNELs						
2781	27813-02-1 methacrylic acid, monoester with propane-1,2-diol						
Dern	Dermal Longterm System 4.2 mg/kg bw/day (General population)						
- PNE	- PNECs						
2781	27813-02-1 methacrylic acid, monoester with propane-1,2-diol						
Oral	PNEC oral	mg/kg Food (General population)					
	PNEC Freshwater	0.904 mg/l (General population)					
	PNEC Freshwater sed	6.28 mg/kg (General population)					
	PNEC Marinewater	0.904 mg/l (General population)					
	PNEC Soil	0.727 mg/kg (General population)					
	PNEC STP	10 mg/l (General population)					
	PNEC Marinewater sed	6.28 mg/kg (General population)					

- Additional information: The lists valid during the making were used as basis.
- -8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

(Contd. on page 5)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

-9.1 Information on basic physical and chemical properties

- General Information

Colour: Green
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

- Lower and upper explosion limit

- Lower:
- Upper:
- Flash point:
- Decomposition temperature:
- pH

Not determined.
> 100 °C

Not determined.

Not determined.

- Viscosity:

- Kinematic viscosity
 - Dynamic:
 Not determined.
 Not determined.

- Solubility

- water: Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)
 - Vapour pressure:
 Not determined.
 Not determined.

- Density and/or relative density

- Density:
- Relative density
- Vapour density

Not determined.
Not determined.
Not determined.

-9.2 Other information

- Appearance:

- Form: Fluid

- Important information on protection of health and environment, and on safety.

- **Ignition temperature:** Product is not self-igniting.

- **Explosive properties:** Product does not present an explosion hazard.

Change in conditionSoftening point/range

- Oxidising properties
- Evaporation rate

Not determined.
Not determined.

- Information with regard to physical hazard classes

- Explosives Void

(Contd. on page 6)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

		(Contd. of page 5
- Flammable gases	Void	
- Aerosols	Void	
- Oxidising gases	Void	
- Gases under pressure	Void	
- Flammable liquids	Void	
- Flammable solids	Void	
- Self-reactive substances and mixtures	Void	
- Pyrophoric liquids	Void	
- Pyrophoric solids	Void	
- Self-heating substances and mixtures	Void	
- Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
- Oxidising liquids	Void	
- Oxidising solids	Void	
- Organic peroxides	Void	
- Corrosive to metals	Void	
- Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50	- LD/LC50 values relevant for classification:					
10595-06-	10595-06-9 2-phenoxyethyl methacrylate					
Oral	LD50	5,050 mg/kg (Rat, male/female)				
868-77-9 2	868-77-9 2-hydroxyethyl methacrylate					
Oral	LD50	5,050 mg/kg (Rat, male/female)				
Dermal	LD50	3,000 mg/kg (Rabbit)				
79-41-4 m	79-41-4 methacrylic acid					
Oral	LD50	1,320 - 2,260 mg/kg (Rat, male/female)				
Dermal	LD50	500 - 1,000 mg/kg (Rabbit)				
Inhalative	LC50/4 h	7,100 mg/l (Rat, male/female)				
N,N-Bis-(2	N,N-Bis-(2-hydroxyethyl)-para-toluidine, ethoxylated					
Oral	LD50	619 mg/kg				
Dermal	LD50	> 2,000 mg/kg				

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

(Contd. on page 7)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 6)

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 Repr. 2
- -11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- Toxicity to fish:

868-77-9 2-hydroxyethyl methacrylate

LC50/96 h 213 - 242 mg/l (Pimephales promelas)

- -12.2 Persistence and degradability No further relevant information available.
- -12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- -12.7 Other adverse effects No further relevant information available.
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA

UN3082

(Contd. on page 8)

Version number 4 (replaces version 3) Printing date 11.04.2023 Revision: 11.04.2023

Trade name: 1314 - Component B 1315

	(Contd. of page
- 14.2 UN proper shipping name	
-ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate)
- IMDG	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
- IATA	methacrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOU:
-IAIA	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate)
- 14.3 Transport hazard class(es)	
- ADR	
- Class	9 (M6) Miscellaneous dangerous substances an
	articles.
- Label	9
- IMDG, IATA	
- Class - Label	9 Miscellaneous dangerous substances and articles.9
- 14.4 Packing group	
- ADR, IMDG, IATA	III
- 14.5 Environmental hazards:	
- Marine pollutant:	Symbol (fish and tree)
- Special marking (ADR):	Symbol (fish and tree)
- Special marking (IATA):	Symbol (fish and tree)
- 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
	articles.
- Hazard identification number (Kemler code):- EMS Number:	90 F-A,S-F
- Stowage Category	г-A,5-г А
- 14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
- Transport/Additional information:	ADR: SV375
	IMDG-Code: 2.10.2.7
	IATA-DGR: A197 (375)
-ADR	at .
- Limited quantities (LQ)	5L Code: E1
- Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category	3
- Tunnel restriction code	(-)
- Remarks:	SV375:
	These substances are not subject to the other provision
	(Contd. on page

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

	(Contd. of page 8
-	of ADR / RID if they are transported in individual o composite packaging with a net quantity of no more than 5 l of liquid substances or a net mass of no more than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to the general provisions of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG	
- Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Remarks:	2.10.2.7: Marine pollutants in individual packaging or composit packaging with a net quantity per individual or inne packaging of no more than 5 L for liquids or a net mas per individual or inner packaging of no more than 5 k for solids are not subject to any other provisions of thi Code applicable to marine pollutants, provided that the packaging complies with the general Meet the requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 In the case of marine pollutants that also meet the criteria for inclusion in another class, all provisions of this Code that apply to any further hazards continue to apply.
- IATA - Remarks:	A 197 (375): These substances when transported in single or combination packagings containing a net quantity persingle or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2 PHENOXYETHYL METHACRYLATE), 9, III

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- -15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

(Contd. on page 10)

Printing date 11.04.2023 Version number 4 (replaces version 3) Revision: 11.04.2023

Trade name: 1314 - Component B 1315

(Contd. of page 9) H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. - Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation - Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- * Data compared to the previous version altered.

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

CH-EN