

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 1318 - Component A 1320

UFI: DU30-30RC-N006-UNEJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants
Resins (prepolymers)

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Dam. 1; H318
Skin Sens. 1; H317
Repr. 2; H361d
STOT SE 3; H335
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

2-hydroxyethyl methacrylate
2-phenoxyethyl methacrylate
alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide
hydroquinone monomethyl ether

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 2 of 18

Signal word: Danger

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.


Precautionary statements

P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P391	Collect spillage.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H317-H318-H361d

Precautionary statements

P280-P305+P351+P338-P310

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 3 of 18

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
868-77-9	2-hydroxyethyl methacrylate			30 - < 50 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
10595-06-9	2-phenoxyethyl methacrylate			15 - < 30 %
	234-201-1		01-2120752383-55	
	Repr. 2, Skin Sens. 1, Aquatic Chronic 2; H361d H317 H411			
80-15-9	alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide			1 - < 5 %
	201-254-7	617-002-00-8		
	Org. Perox. E, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, STOT RE 2, Aquatic Chronic 2; H242 H331 H312 H302 H314 H373 H411			
150-76-5	hydroquinone monomethyl ether			0.1 - < 1 %
	205-769-8	604-044-00-7		
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H302 H319 H317 H412			
79-41-4	methacrylic acid; 2-methylpropenoic acid			0.1 - < 1 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3; H311 H332 H302 H314 H318 H335			
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane			0.1 - < 1 %
	247-952-5			
	Aquatic Chronic 1; H410			
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			< 0.1 %
	204-617-8	604-005-00-4		
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H351 H341 H302 H318 H317 H400			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	30 - < 50 %
		dermal: LD50 = >3000 mg/kg; oral: LD50 = 5050 mg/kg	
80-15-9	201-254-7	alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide	1 - < 5 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0.5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 382 mg/kg Skin Corr. 1B; H314: >= 10 - 100 Skin Irrit. 2; H315: >= 3 - < 10 Eye Dam. 1; H318: >= 3 - < 10 Eye Irrit. 2; H319: >= 1 - < 3 STOT SE 3; H335: >= 1 - 100	
150-76-5	205-769-8	hydroquinone monomethyl ether	0.1 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: ATE = 500 mg/kg	
79-41-4	201-204-4	methacrylic acid; 2-methylpropenoic acid	0.1 - < 1 %
		inhalation: LC50 = 7,1 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 500 mg/kg; oral: LD50 = 1320 mg/kg STOT SE 3; H335: >= 1 - 100	
26741-53-7	247-952-5	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	0.1 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Chronic 1; H410: M=1	
123-31-9	204-617-8	1,4-dihydroxybenzene; hydroquinone; quinol	< 0.1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 375 mg/kg Aquatic Acute 1; H400: M=10	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 5 of 18

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special handling advices are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

Hints on joint storage

none

Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

7.3. Specific end use(s)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 6 of 18

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
10595-06-9	2-phenoxyethyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	12 mg/m³
Worker DNEL, long-term		inhalation	local	84 mg/m³
Worker DNEL, long-term		dermal	systemic	3,5 mg/kg bw/day
150-76-5	hydroquinone monomethyl ether			
Worker DNEL, long-term		inhalation	systemic	3 mg/m³
79-41-4	methacrylic acid; 2-methylpropenoic acid			
Worker DNEL, long-term		inhalation	systemic	39,3 mg/m³
Worker DNEL, long-term		inhalation	local	44 mg/m³
Worker DNEL, long-term		dermal	systemic	4,25 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,38 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	11,7 mg/m³
Consumer DNEL, long-term		inhalation	local	8,8 mg/m³
Consumer DNEL, long-term		dermal	systemic	5,35 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,23 mg/cm²
Consumer DNEL, long-term		oral	systemic	5,35 mg/kg bw/day
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane			
Worker DNEL, long-term		inhalation	systemic	2,75 mg/m³
Worker DNEL, long-term		dermal	systemic	0,78 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,68 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,39 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,39 mg/kg bw/day
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			
Worker DNEL, long-term		inhalation	systemic	2,1 mg/m³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,05 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,66 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,6 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 7 of 18

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
10595-06-9	2-phenoxyethyl methacrylate	
Freshwater		0,0142 mg/l
Freshwater (intermittent releases)		0,012 mg/l
Marine water		0,00142 mg/l
Freshwater sediment		0,665 mg/kg
Marine sediment		0,067 mg/kg
Micro-organisms in sewage treatment plants (STP)		1,77 mg/l
Soil		0,125 mg/kg
150-76-5	hydroquinone monomethyl ether	
Freshwater		0,014 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,125 mg/kg
Marine sediment		0,013 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,017 mg/kg
79-41-4	methacrylic acid; 2-methylpropenoic acid	
Freshwater		0,82 mg/l
Freshwater (intermittent releases)		0,45 mg/l
Marine water		0,082 mg/l
Freshwater sediment		3,09 mg/kg
Marine sediment		0,309 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,137 mg/kg
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,707 mg/l
Marine water		0 mg/l
Freshwater sediment		2000000 mg/kg
Marine sediment		200000 mg/kg
Micro-organisms in sewage treatment plants (STP)		42 mg/l
Soil		1 mg/kg
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	
Freshwater		0,00057 mg/l
Freshwater (intermittent releases)		0,00134 mg/l
Marine water		0,000057 mg/l
Freshwater sediment		0,0049 mg/kg
Marine sediment		0,00049 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,71 mg/l
Soil		0,00064 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 8 of 18



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Hand protection EN ISO 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	yellow	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		ca. 149 °C
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		>100 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		not determined
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density (at 20 °C):		not determined
Relative density:		not determined
Relative vapour density:		not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 9 of 18

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Viscosity / dynamic:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 11997 mg/kg; ATE (dermal) 30352 mg/kg; ATE (inhalation vapour) 94.22 mg/l; ATE (inhalation dust/mist) 15.70 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 10 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg 5050	Rat	Pre-supplier/manufact urer	
	dermal	LD50 mg/kg >3000	Rabbit	Pre-supplier/manufact urer	
80-15-9	alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide				
	oral	LD50 mg/kg 382	Rat	IUCLID	
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0.5 mg/l			
150-76-5	hydroquinone monomethyl ether				
	oral	ATE mg/kg 500			
	dermal	LD50 mg/kg > 2000	Rat	Study report (2008)	EU Method B.3
79-41-4	methacrylic acid; 2-methylpropenoic acid				
	oral	LD50 mg/kg 1320	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 mg/kg 500	Rabbit	Pre-supplier/manufact urer	
	inhalation (4 h) vapour	LC50 7,1 mg/l	Rat	Pre-supplier/manufact urer	OECD 403
	inhalation dust/mist	ATE 1.5 mg/l			
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane				
	oral	LD50 mg/kg > 5000	Rat	Study report (1984)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rabbit	Study report (1994)	OECD Guideline 402
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol				
	oral	LD50 mg/kg > 375	Rat	Food Chem Toxicol 45, 70 - 78 (2007)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rabbit	Food Chem Toxicol 45, 70 - 78 (2007)	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (2-hydroxyethyl methacrylate; 2-phenoxyethyl methacrylate; hydroquinone monomethyl ether; 1,4-dihydroxybenzene; hydroquinone; quinol)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (2-phenoxyethyl methacrylate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 11 of 18

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 12 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50 227 mg/l	96 h	Pimephales promelas	Pre-supplier/manu facturer	
	Acute crustacea toxicity	EC50 >380 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/manu facturer	
10595-06-9	2-phenoxyethyl methacrylate					
	Acute algae toxicity	ErC50 4,4 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	ISO 8692
	Acute bacteria toxicity	(EC50 177 mg/l)	3 h	Activated sludge	REACH Registration Dossier	ISO 8192
150-76-5	hydroquinone monomethyl ether					
	Acute bacteria toxicity	(EC50 4,6 mg/l)	0.5 h	Photobacterium phosphoreum	Chemosphere, 12(11/12), 1421-1442. (1983	other: microtox test
79-41-4	methacrylic acid; 2-methylpropenoic acid					
	Acute fish toxicity	LC50 85 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 45 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 130 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 10 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 53 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(EC50 13500 mg/l)	3 h	Activated sludge	Publication (2008)	ISO 8192
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane					
	Acute fish toxicity	LC50 70,7 mg/l	96 h	Danio rerio	Study report (2013)	OECD Guideline 203
	Acute algae toxicity	ErC50 97 mg/l	72 h	Desmodesmus subspicatus	Study report (2013)	OECD Guideline 201
	Crustacea toxicity	NOEC 0,1 mg/l	21 d	Daphnia magna	Study report (2013)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 > 1000 mg/l)	3 h	activated sludge, domestic	Study report (2012)	OECD Guideline 209
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol					
	Acute fish toxicity	LC50 0,638 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 0,33 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,134 mg/l	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 13 of 18

	Fish toxicity	NOEC mg/l	>= 0,1	32 d	Pimephales promelas	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,006	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

No data available

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane			
	Activated sludge, Concentration: 31 mg/l	<10%	28	Pre-supplier/manufactur er
	Not readily biodegradable (according to OECD criteria)			
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol			
	OECD 301C (Activated sludge, Concentration:100 mg/l)	70%	14	Pre-supplier/manufactur er
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47
10595-06-9	2-phenoxyethyl methacrylate	3,137
150-76-5	hydroquinone monomethyl ether	1,62
79-41-4	methacrylic acid; 2-methylpropenoic acid	0,93
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	10,9
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	0,59

BCF

CAS No	Chemical name	BCF	Species	Source
26741-53-7	3,9-bis(2,4-di-tert-butylphenoxy)-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane	0,89		SAR and QSAR in Envi
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol	3,16		

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 14 of 18

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318


Page 15 of 18



Classification code: M6
Special Provisions: 274 335 375 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: 274 335 969
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: A97 A158 A197 A215
Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 16 of 18

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 31.443 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320

Revision date: 08.01.2024

Product code: 1318

Page 17 of 18

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).
Org. Perox: Organic peroxide
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
Muta: Germ cell mutagenicity
Carc: Carcinogenicity
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1318 - Component A 1320		
Revision date: 08.01.2024	Product code: 1318	Page 18 of 18

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H242	Heating may cause a fire.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

LCS: Life cycle stages
PC: Product categories
ERC: Environmental release categories
TF: Technical functions

SU: Sectors of use
PROC: Process categories
AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)