

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 1600 - Component A 1625, 1645

UFI: M940-N06C-500P-4CAV

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

#### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Company name: Kisling AG  
Street: Motorenstrasse 102  
Place: CH-8620 Wetzikon  
Telephone: +41 58 272 0 272  
E-mail: customerservice@kisling.com  
Internet: www.kisling.com

#### Supplier

Company name: Kisling (Deutschland) GmbH  
Street: Salzstraße 15  
Place: D-74676 Niedernhall  
Telephone: +49 7940 50961 61  
E-mail: customerservice@kisling.com  
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143  
E-mail: compliance@kisling.com  
Internet: www.kisling.com

### 1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Skin Sens. 1; H317  
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

##### Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane  
dibenzoyl peroxide; benzoyl peroxide

Signal word: Warning

## Safety Data Sheet

according to Regulation (EC) No 1907/2006


### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 2 of 13

#### Pictograms:



#### Hazard statements

- H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H410 Very toxic to aquatic life with long lasting effects.


#### Precautionary statements

- P261 Avoid breathing Vapour.  
P273 Avoid release to the environment.  
P280 Wear protective gloves and eye/face protection.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P391 Collect spillage.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

#### Pictograms:



#### Hazard statements

H317

#### Precautionary statements

P261-P280-P333+P313-P362+P364

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of substances listed below with nonhazardous components.

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			50 - < 100 %
	216-823-5	603-073-00-2		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
94-36-0	dibenzoyl peroxide; benzoyl peroxide			15 - < 30 %
	202-327-6	617-008-00-0		
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 1; H241 H319 H317 H410			
9038-95-3	Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether			1 - < 5 %
	Acute Tox. 4, Eye Irrit. 2; H302 H319			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 3 of 13

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	50 - < 100 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
94-36-0	202-327-6	dibenzoyl peroxide; benzoyl peroxide	15 - < 30 %
		Aquatic Chronic 1; H410: M=10	
9038-95-3		Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	1 - < 5 %
		oral: ATE = 500 mg/kg	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Take off immediately all contaminated clothing.

##### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. When in doubt or if symptoms are observed, get medical advice.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Co-ordinate fire-fighting measures to the fire surroundings.

##### Unsuitable extinguishing media

No information available.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 4 of 13

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

No special handling advices are necessary.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### Further information on handling

Keep only in the original container in a cool, well-ventilated place.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

#### Hints on joint storage

none

#### Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

### 7.3. Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 5 of 13

#### DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m³
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,5 mg/kg bw/day
94-36-0	dibenzoyl peroxide; benzoyl peroxide			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	39 mg/m³
Worker DNEL, long-term		dermal	systemic	13.3 mg/kg bw/day

#### PNEC values

CAS No	Name of agent		Value
	Environmental compartment		
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane		
Freshwater			0,006 mg/l
Freshwater (intermittent releases)			0,018 mg/l
Marine water			0,001 mg/l
Freshwater sediment			0,341 mg/kg
Marine sediment			0,034 mg/kg
Secondary poisoning			11 mg/kg
Micro-organisms in sewage treatment plants (STP)			10 mg/l
Soil			0,065 mg/kg
94-36-0	dibenzoyl peroxide; benzoyl peroxide		
Freshwater			0.00002 mg/l
Freshwater (intermittent releases)			0.000602 mg/l
Marine water			0.000002 mg/l
Freshwater sediment			0.013 mg/kg
Marine sediment			0.001 mg/kg
Micro-organisms in sewage treatment plants (STP)			0.35 mg/l
Soil			0.003 mg/kg

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 6 of 13

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.  
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	not determined	not applicable
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	not determined	
Auto-ignition temperature:	not determined	
Decomposition temperature:	SADT: 50°C °C	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density:	1,15 g/cm³	
Relative density:	not determined	
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

not determined

Other safety characteristics

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 7 of 13

Evaporation rate: not determined  
Solid content: not determined  
Viscosity / dynamic: 15000 mPa·s

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

No further relevant information available.

##### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

##### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

##### 10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

##### 10.5. Incompatible materials

No further relevant information available.

##### 10.6. Hazardous decomposition products

No further relevant information available.

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### Toxicokinetics, metabolism and distribution

No data available

###### Acute toxicity

Based on available data, the classification criteria are not met.

###### ATEmix calculated

ATE (oral) 17241 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 mg/kg	19800	Rabbit	Publication (1958)
	dermal	LD50 mg/kg	23000	Rabbit	Pre-supplier/manufact urer
9038-95-3	Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether				
	oral	ATE mg/kg	500		

###### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

###### Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxy)phenyl]propane; dibenzoyl peroxide; benzoyl peroxide)

###### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

###### STOT-single exposure

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 8 of 13

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

No information available.

#### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### SECTION 12: Ecological information

#### 12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	Study report (2007)	OECD Guideline 201
94-36-0	dibenzoyl peroxide; benzoyl peroxide					
	Acute fish toxicity	LC50 0.06 mg/l	96 h	Oncorhynchus mykiss	Study report (2010)	EU Method C.1
	Acute algae toxicity	ErC50 0.071 mg/l	72 h	Raphidocelis subcapitata	Study report (2010)	EU Method C.3
	Acute crustacea toxicity	EC50 0.11 mg/l	48 h	Daphnia magna	Study report (2010)	EU Method C.2
	Acute bacteria toxicity	(EC50 35 mg/l)		activated sludge of a predominantly domestic sewage	Study report (1990)	OECD Guideline 209

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	>= 2,64
94-36-0	dibenzoyl peroxide; benzoyl peroxide	3.2

#### BCF

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	31		Study report (2010)

#### 12.4. Mobility in soil

No further relevant information available.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 9 of 13

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 3082

##### 14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Dibenzoyl peroxide)

##### 14.3. Transport hazard class(es):


9

##### 14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 10 of 13

Hazard No: 90  
Tunnel restriction code: -

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibenzoyl peroxide)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
Hazard label: 9



Classification code: M6  
Special Provisions: 274 335 375 601  
Limited quantity: 5 L  
Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibenzoyl peroxide)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
Hazard label: 9



Special Provisions: 274 335 969  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-A, S-F

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 3082  
**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibenzoyl peroxide)  
**14.3. Transport hazard class(es):** 9  
**14.4. Packing group:** III  
Hazard label: 9



Special Provisions: A97 A158 A197 A215  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y964  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 964  
IATA-max. quantity - Passenger: 450 L  
IATA-packing instructions - Cargo: 964  
IATA-max. quantity - Cargo: 450 L

#### 14.5. Environmental hazards

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 11 of 13

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: (DIBENZOYL PEROXIDE)

#### **14.6. Special precautions for user**

Warning : Organic peroxides !

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

##### **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

2 - obviously hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 1600 - Component A 1625, 1645

Revision date: 13.03.2024

Product code: 1600

Page 12 of 13

#### Abbreviations and acronyms

CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 CAS: Chemical Abstracts Service  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).  
 Org. Perox: Organic peroxide  
 Acute Tox: Acute toxicity  
 Skin Irrit: Skin irritation  
 Eye Irrit: Eye irritation  
 Skin Sens: Skin sensitisation  
 Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 1; H410	Calculation method

#### Relevant H and EUH statements (number and full text)

H241 Heating may cause a fire or explosion.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1600 - Component A 1625, 1645		
Revision date: 13.03.2024	Product code: 1600	Page 13 of 13

H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

LCS: Life cycle stages  
PC: Product categories  
ERC: Environmental release categories  
TF: Technical functions

SU: Sectors of use  
PROC: Process categories  
AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)