

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 1 of 21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 1624 - Component B 1625

UFI: 2FG4-40PX-A003-3K8R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	Kisling AG	
Street:	Motorenstrasse 102	
Place:	CH-8620 Wetzikon	
Telephone:	+41 58 272 0 272	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

Supplier

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number: 24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Dam. 1; H318
Skin Sens. 1; H317
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 2 of 21

Hazard components for labelling

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
n-butyl methacrylate
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)
methacrylic acid; 2-methylpropenoic acid
Zinc methacrylate
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine
Silicone acrylate

Signal word: Danger**Pictograms:**

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves and eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P403+P235 Store in a well-ventilated place. Keep cool.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger**Pictograms:**

Hazard statements

H317-H318

Precautionary statements

P280-P305+P351+P338-P310

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 3 of 21

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	30 - < 50 %
	201-297-1	607-035-00-6
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
97-88-1	n-butyl methacrylate	30 - < 50 %
	202-615-1	607-033-00-5
	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H226 H315 H319 H317 H335	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	1 - < 5 %
	500-033-5	603-074-00-8
	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
79-41-4	methacrylic acid; 2-methylpropenoic acid	1 - < 5 %
	201-204-4	607-088-00-5
	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3; H311 H332 H302 H314 H318 H335	
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	1 - < 5 %
	258-053-2	
	Skin Irrit. 2, Eye Dam. 1; H315 H318	
13189-00-9	Zinc methacrylate	1 - < 5 %
	236-144-8	01-2119976363-30
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B, Aquatic Acute 1; H302 H319 H317 H400	
911674-82-3	1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	0.1 - < 1 %
	423-300-7	01-0000016979-49
	Skin Sens. 1, Aquatic Chronic 4; H317 H413	
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol	0.1 - < 1 %
	254-075-1	01-2119980937-17
	Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412	
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	0.1 - < 1 %
	309-629-8	01-2119979085-27
	Skin Sens. 1, Aquatic Chronic 3; H317 H412	
125455-52-9	Silicone acrylate	0.1 - < 1 %
	603-070-6	
	Skin Sens. 1B; H317	
79-10-7	acrylic acid; prop-2-enoic acid	0.1 - < 1 %
	201-177-9	607-061-00-8
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 2; H226 H332 H312 H302 H314 H318 H335 H400 H411	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 4 of 21

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	30 - < 50 %
		inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = ca. 7900 mg/kg	
97-88-1	202-615-1	n-butyl methacrylate	30 - < 50 %
		dermal: LD50 = 10181 mg/kg; oral: LD50 = > 17900 mg/kg	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	1 - < 5 %
		Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
79-41-4	201-204-4	methacrylic acid; 2-methylpropenoic acid	1 - < 5 %
		inhalation: LC50 = 7,1 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 500 mg/kg; oral: LD50 = 1320 mg/kg Eye Dam. 1; H318: >= 3 - 100 Eye Irrit. 2; H319: >= - < 3 STOT SE 3; H335: >= 1 - 100	
52628-03-2	258-053-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	1 - < 5 %
		oral: LD50 = > 2000 mg/kg	
13189-00-9	236-144-8	Zinc methacrylate	1 - < 5 %
		inhalation: LC50 = > 5.32 mg/l (dusts or mists); oral: LD50 = ca. 500 mg/kg Aquatic Acute 1; H400: M=1	
38668-48-3	254-075-1	1,1'-(p-tolylimino)dipropan-2-ol	0.1 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg	
79-10-7	201-177-9	acrylic acid; prop-2-enoic acid	0.1 - < 1 %
		inhalation: LC50 = > 5,1 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = ca. 1000 - < 2000 mg/kg STOT SE 3; H335: >= 1 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage
May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 5 of 21

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 6 of 21

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
79-10-7	Acrylic acid; Prop-2-enoic acid	10	29		TWA (8 h)	
		20	59		STEL (1 min)	
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 7 of 21

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate			
Worker DNEL, long-term		inhalation	systemic	348,4 mg/m ³
Worker DNEL, long-term		inhalation	local	208 mg/m ³
Worker DNEL, acute		inhalation	local	416 mg/m ³
Worker DNEL, long-term		dermal	systemic	13,67 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,5 mg/cm ²
Worker DNEL, acute		dermal	local	1,5 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	74,3 mg/m ³
Consumer DNEL, long-term		inhalation	local	104 mg/m ³
Consumer DNEL, acute		inhalation	local	208 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8,2 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	1,5 mg/cm ²
Consumer DNEL, acute		dermal	local	1,5 mg/cm ²
Consumer DNEL, long-term		oral	systemic	8,2 mg/kg bw/day
97-88-1	n-butyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	415.9 mg/m ³
Worker DNEL, long-term		inhalation	local	409 mg/m ³
Worker DNEL, long-term		dermal	systemic	5 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1 %
Worker DNEL, acute		dermal	local	1 %
Consumer DNEL, long-term		inhalation	systemic	66.5 mg/m ³
Consumer DNEL, long-term		inhalation	local	366.4 mg/m ³
Consumer DNEL, long-term		dermal	systemic	3 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	1 %
Consumer DNEL, acute		dermal	local	1 %
79-41-4	methacrylic acid; 2-methylpropenoic acid			
Worker DNEL, long-term		inhalation	systemic	39,3 mg/m ³
Worker DNEL, long-term		inhalation	local	44 mg/m ³
Worker DNEL, long-term		dermal	systemic	4,25 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,38 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	11,7 mg/m ³
Consumer DNEL, long-term		inhalation	local	8,8 mg/m ³
Consumer DNEL, long-term		dermal	systemic	5,35 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,23 mg/cm ²
Consumer DNEL, long-term		oral	systemic	5,35 mg/kg bw/day
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate			
Worker DNEL, long-term		inhalation	systemic	7,04 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 8 of 21

Consumer DNEL, long-term	inhalation	systemic	1,74 mg/m ³
13189-00-9	Zinc methacrylate		
Worker DNEL, long-term	inhalation	systemic	5.28 mg/m ³
Worker DNEL, long-term	dermal	systemic	0.749 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0.931 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0.268 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0.268 mg/kg bw/day
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol		
Worker DNEL, long-term	inhalation	systemic	2.47 mg/m ³
Worker DNEL, long-term	dermal	systemic	0.7 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0.25 mg/kg bw/day
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine		
Worker DNEL, long-term	inhalation	local	0.308 mg/m ³
Consumer DNEL, long-term	inhalation	local	0.055 mg/m ³
79-10-7	acrylic acid; prop-2-enoic acid		
Worker DNEL, long-term	inhalation	systemic	30 mg/m ³
Worker DNEL, acute	inhalation	systemic	30 mg/m ³
Worker DNEL, long-term	inhalation	local	30 mg/m ³
Worker DNEL, acute	inhalation	local	30 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	3,6 mg/m ³
Consumer DNEL, acute	inhalation	systemic	3,6 mg/m ³
Consumer DNEL, long-term	inhalation	local	3,6 mg/m ³
Consumer DNEL, acute	inhalation	local	3,6 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,4 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,2 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 9 of 21

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	
Freshwater		0,94 mg/l
Freshwater (intermittent releases)		0,69 mg/l
Marine water		0,094 mg/l
Freshwater sediment		10,2 mg/kg
Marine sediment		1,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1,48 mg/kg
97-88-1	n-butyl methacrylate	
Freshwater		0.017 mg/l
Freshwater (intermittent releases)		0.056 mg/l
Marine water		0.002 mg/l
Freshwater sediment		4.73 mg/kg
Marine sediment		0.473 mg/kg
Micro-organisms in sewage treatment plants (STP)		31.7 mg/l
Soil		0.935 mg/kg
79-41-4	methacrylic acid; 2-methylpropenoic acid	
Freshwater		0,82 mg/l
Freshwater (intermittent releases)		0,45 mg/l
Marine water		0,082 mg/l
Freshwater sediment		3,09 mg/kg
Marine sediment		0,309 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,137 mg/kg
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	
Freshwater		0,068 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,007 mg/l
Freshwater sediment		0,481 mg/kg
Marine sediment		0,048 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,546 mg/l
Soil		0,056 mg/kg
13189-00-9	Zinc methacrylate	
Freshwater		0.00056 mg/l
Freshwater (intermittent releases)		0.0056 mg/l
Freshwater sediment		6.14 mg/kg
Marine sediment		0.614 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		1.23 mg/kg
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 10 of 21

Freshwater	0.017 mg/l
Freshwater (intermittent releases)	0.17 mg/l
Marine water	0.002 mg/l
Freshwater sediment	0.163 mg/kg
Marine sediment	0.016 mg/kg
Micro-organisms in sewage treatment plants (STP)	199.5 mg/l
Soil	0.023 mg/kg
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine
Freshwater sediment	0.058 mg/kg
Marine sediment	0.0058 mg/kg
Soil	0.484 mg/kg
79-10-7	acrylic acid; prop-2-enoic acid
Freshwater	0,003 mg/l
Freshwater (intermittent releases)	0,001 mg/l
Marine water	0,0003 mg/l
Freshwater sediment	0,024 mg/kg
Marine sediment	0,002 mg/kg
Secondary poisoning	30 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,9 mg/l
Soil	1 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

EN ISO 374

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 11 of 21

Colour: cream
 Odour: characteristic
 Odour threshold: not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	> 100 °C	
Flammability:	not determined	not applicable
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	10 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	Test Series H, part II,28
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	37 hPa	
(at 20 °C)		
Density (at 20 °C):	1,03 g/cm ³	
Relative density:	not determined	
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
 The product is not: Explosive.
 Oxidizing properties
 not determined

Other safety characteristics

Evaporation rate: not determined
 Solid content: not determined
 Viscosity / dynamic: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.
 Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 12 of 21

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 2152 mg/kg; ATE (dermal) 20080 mg/kg; ATE (inhalation vapour) 441.8 mg/l; ATE (inhalation dust/mist) 60.24 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 13 of 21

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	oral	LD50 mg/kg	ca. 7900	Rat	J. Ind. Hyg. Toxicol. 23: 343-351 (1941)	Study to assess the acute oral toxicity
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50	29,8 mg/l	Rat	J. Dent. Res. 59: 1074 (1980)	Study to assess the acute inhalative tox
97-88-1	n-butyl methacrylate					
	oral	LD50 mg/kg	> 17900	Rat	J. Ind. Hyg. Toxicol. 23: 343-351 (1941)	other: pre-guideline development
	dermal	LD50 mg/kg	10181	Rabbit	Amer. Ind. Hyg. Assoc. J. Vol 30 (5): 47	other
79-41-4	methacrylic acid; 2-methylpropenoic acid					
	oral	LD50 mg/kg	1320	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 mg/kg	500	Rabbit	Pre-supplier/manufac turer	
	inhalation (4 h) vapour	LC50	7,1 mg/l	Rat	Pre-supplier/manufac turer	OECD 403
	inhalation dust/mist	ATE	1.5 mg/l			
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate					
	oral	LD50 mg/kg	> 2000	Rat	Study report (2013)	OECD Guideline 425
13189-00-9	Zinc methacrylate					
	oral	LD50 mg/kg	ca. 500	Rat	Study report (2008)	OECD Guideline 423
	inhalation (4 h) dust/mist	LC50 mg/l	> 5.32	Rat	Study report (2013)	OECD Guideline 436
38668-48-3	1,1'-(p-tolylimino)diprop-2-en-1-ol					
	oral	LD50 mg/kg	> 25 - < 200	Rat	Study report (2001)	OECD Guideline 423
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2012)	OECD Guideline 402
79-10-7	acrylic acid; prop-2-enoic acid					
	oral	LD50 mg/kg	ca. 1000 - < 2000	Rat	Study report (2015)	OECD Guideline 423
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (2011)	OECD Guideline 402
	inhalation (4 h) vapour	LC50	> 5,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
	inhalation dust/mist	ATE	1.5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 14 of 21

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; n-butyl methacrylate; reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700); Zinc methacrylate; 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene; Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine; Silicone acrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; n-butyl methacrylate; methacrylic acid; 2-methylpropenoic acid)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 15 of 21

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate					
	Acute fish toxicity	LC50 > 79 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 > 110 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 9,4 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 3162 mg/l ()	3 h	Activated sludge	Publication (2008)	ISO 8192
97-88-1	n-butyl methacrylate					
	Acute fish toxicity	LC50 11 mg/l	96 h	Pimephales promelas	Study report (1993)	OECD Guideline 203
	Acute algae toxicity	ErC50 31.2 mg/l	72 h	Raphidocelis subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 25.4 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC 1.1 mg/l	21 d	Daphnia magna	Study report (1998)	OECD Guideline 211
79-41-4	methacrylic acid; 2-methylpropenoic acid					
	Acute fish toxicity	LC50 85 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	EPA OTS 797.1400
	Acute algae toxicity	ErC50 45 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 130 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 10 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 53 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 13500 mg/l ()	3 h	Activated sludge	Publication (2008)	ISO 8192
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate					
	Acute fish toxicity	LC50 > 112 mg/l	96 h	Oncorhynchus mykiss	Study report (2013)	OECD Guideline 203

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 16 of 21

	Acute algae toxicity	ErC50 mg/l	> 120	72 h	Raphidocelis subcapitata	Study report (2013)	OECD Guideline 201
13189-00-9	Zinc methacrylate						
	Acute fish toxicity	LC50 mg/l	> 2.1	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	ca. 0.56	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	ca. 8.7	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol						
	Acute fish toxicity	LC50	17 mg/l	96 h	Danio rerio	Study report (1984)	other: Guideline F.1.1. of UBA
	Acute algae toxicity	ErC50	245 mg/l	72 h	Desmodesmus subspicatus	Study report (2012)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	28.8	48 h	Daphnia magna	Study report (1999)	OECD Guideline 202
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine						
	Acute fish toxicity	LL50 mg/l	> 10	96 h	Oncorhynchus mykiss	Study report (2013)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	Study report (2013)	EU Method C.3
	Acute crustacea toxicity	EL50 mg/l	> 10	48 h	Daphnia magna	Study report (2013)	OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	>= 10	21 d	Daphnia magna	Study report (2018)	OECD Guideline 211
79-10-7	acrylic acid; prop-2-enoic acid						
	Acute fish toxicity	LC50	27 mg/l	96 h	Oncorhynchus mykiss	European Union Risk Assessment Report, 1	EPA OTS 797.1400
	Acute algae toxicity	ErC50 mg/l	0,13	72 h	Desmodesmus subspicatus	Chemosphere 45: 653-658 (1994)	EU Method C.3
	Acute crustacea toxicity	EC50	95 mg/l	48 h	Daphnia magna	Chemosphere 40: 29 - 38 (1990)	EPA OTS 797.1300
	Fish toxicity	NOEC mg/l	>= 10,1	45 d	Oryzias latipes	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC	19 mg/l	21 d	Daphnia magna	Chemosphere 40: 29-38 (1996)	EPA OTS 797.1330

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 17 of 21

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	1,38
97-88-1	n-butyl methacrylate	2.99
79-41-4	methacrylic acid; 2-methylpropenoic acid	0,93
52628-03-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	1 - < 2,72
13189-00-9	Zinc methacrylate	< 0.3
38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol	2.1
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>= 5.86
79-10-7	acrylic acid; prop-2-enoic acid	0,46

BCF

CAS No	Chemical name	BCF	Species	Source
97-88-1	n-butyl methacrylate	70		J. Fish Board Can. 3
100545-48-0	Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	56.23	not specified	Other company data (
79-10-7	acrylic acid; prop-2-enoic acid	3,162		Unpublished calculat

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 18 of 21

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 19 of 21

Hazard label:

3



Special Provisions:

A3

Limited quantity Passenger:

1 L

Passenger LQ:

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:

353

IATA-max. quantity - Passenger:

5 L

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions:

85.56 % (881.268 g/l)

Information according to Directive 2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 20 of 21

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1624 - Component B 1625

Revision date: 20.11.2024

Product code: 1624

Page 21 of 21

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)