

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1675-1 MA structural adhesive - 1673-1 resin

Further trade names

Product 1675-1: 1673-1 resin + 1664 Hardener

Product group:

UFI: 2FAG-A1X2-D009-6SHD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail (Contact person): compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail Contact person: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Dam. 1; H318
Skin Sens. 1; H317
STOT SE 3; H335
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Benzyl methacrylate
methacrylic acid

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 2 of 18

Dibenzyl ether
 Propylidynetrimethanol, ethoxylated, esters with acrylic acid
 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide
 Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol
 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-
 2-hydroxyethyl methacrylate

Signal word: Danger

Pictograms:



Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing Vapour.
 P280 Wear protective gloves and eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water and soap.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H317-H318-H412

Precautionary statements

P261-P280-P302+P352-P305+P351+P338-P310-P333+P313

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	Classification (Regulation (EC) No 1272/2008)	REACH No

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 3 of 18

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
2495-37-6	Benzyl methacrylate			50 - < 100 %
	219-674-4		01-2119960155-39	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			
25852-47-5	Polyethylene glycol dimethacrylate			5 - < 15 %
	Aquatic Chronic 3; H412			
79-41-4	methacrylic acid			3 - < 5 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3; H311 H332 H302 H314 H318 H335			
103-50-4	Dibenzyl ether			0.1 - < 1 %
	203-118-2		01-2119782240-44	
	Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid			0.1 - < 1 %
	500-066-5		01-2119489900-30	
	Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H319 H317 H411			
1187441-1 0-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide			0.1 - < 1 %
	810-703-1		01-2120140608-57	
	Eye Dam. 1, Skin Sens. 1; H318 H317			
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-			0.1 - < 1 %
	911-490-9		01-2119979579-10	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H315 H318 H317 H412			
91-66-7	N,N-diethylaniline			0.1 - < 1 %
	202-088-8	612-054-00-8	01-2119943758-22	
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 2; H331 H311 H301 H373 H411			
868-77-9	2-hydroxyethyl methacrylate			0.1 - < 1 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
102-82-9	tributylamine			0.1 - < 1 %
	203-058-7		01-2119474898-14	
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2; H330 H310 H302 H315			
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]			< 0.1 %
	253-039-2		01-2119956160-44	
	Aquatic Chronic 1; H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
2495-37-6	219-674-4	Benzyl methacrylate	50 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3980 mg/kg		
79-41-4	201-204-4	methacrylic acid	3 - < 5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 500 mg/kg; oral: LD50 = 1320 mg/kg Eye Dam. 1; H318: >= 3 - 100 Eye Irrit. 2; H319: >= - < 3 STOT SE 3; H335: >= 1 - 100		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
103-50-4	203-118-2	Dibenzyl ether	0.1 - < 1 %
		oral: LD50 = 4807 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
28961-43-5	500-066-5	Propylidyntrimethanol, ethoxylated, esters with acrylic acid	0.1 - < 1 %
		dermal: LD50 = > 13200 mg/kg; oral: LD50 = > 2000 mg/kg	
1187441-1 0-6	810-703-1	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	0.1 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	0.1 - < 1 %
		oral: ATE = 500 mg/kg	
91-66-7	202-088-8	N,N-diethylaniline	0.1 - < 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = > 400 mg/kg; oral: ATE = 100 mg/kg	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	0.1 - < 1 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5564 mg/kg	
102-82-9	203-058-7	tributylamine	0.1 - < 1 %
		inhalation: LC50 = 0.5 mg/l (vapours); inhalation: ATE = 0,005 mg/l (dusts or mists); dermal: LD50 = 195 mg/kg; oral: LD50 = 420 mg/kg	
36443-68-2	253-039-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]	< 0.1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 7000 mg/kg Aquatic Chronic 1; H410: M=10	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage
May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 5 of 18

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent				
		DNEL type	Exposure route	Effect	Value

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 6 of 18

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
2495-37-6	Benzyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	24,2 mg/m ³
Worker DNEL, long-term		dermal	systemic	6,94 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	7,2 mg/m ³
Consumer DNEL, long-term		dermal	systemic	4,17 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,17 mg/kg bw/day
79-41-4	methacrylic acid			
Worker DNEL, long-term		inhalation	systemic	39.3 mg/m ³
Worker DNEL, long-term		inhalation	local	44 mg/m ³
Worker DNEL, long-term		dermal	systemic	4.25 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0.38 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	11.7 mg/m ³
Consumer DNEL, long-term		inhalation	local	8.8 mg/m ³
Consumer DNEL, long-term		dermal	systemic	5.35 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0.23 mg/cm ²
Consumer DNEL, long-term		oral	systemic	5.35 mg/kg bw/day
103-50-4	Dibenzyl ether			
Worker DNEL, long-term		inhalation	systemic	43.7 mg/m ³
Worker DNEL, long-term		dermal	systemic	6.2 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	10.8 mg/m ³
Consumer DNEL, long-term		dermal	systemic	3.1 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	3.1 mg/kg bw/day
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid			
Worker DNEL, long-term		inhalation	systemic	37 mg/m ³
Worker DNEL, long-term		dermal	systemic	10.5 mg/kg bw/day
1187441-10-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide			
Worker DNEL, long-term		inhalation	systemic	7.05 mg/m ³
Worker DNEL, long-term		dermal	systemic	1 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	3.53 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0.5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0.5 mg/kg bw/day
91-66-7	N,N-diethylaniline			
Worker DNEL, long-term		dermal	systemic	7 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,0167 mg/kg bw/day
868-77-9	2-hydroxyethyl methacrylate			
Worker DNEL, long-term		inhalation	systemic	4.9 mg/m ³
Worker DNEL, long-term		dermal	systemic	1.39 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1.45 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0.83 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0.83 mg/kg bw/day
102-82-9	tributylamine			
Worker DNEL, long-term		inhalation	systemic	5.3 mg/m ³
Worker DNEL, acute		inhalation	systemic	10.6 mg/m ³
Worker DNEL, long-term		inhalation	local	15.2 mg/m ³
Worker DNEL, acute		inhalation	local	15.2 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 7 of 18

PNEC values

CAS No	Name of agent	Value
2495-37-6	Benzyl methacrylate	
	Freshwater	0,01 mg/l
	Freshwater (intermittent releases)	0,005 mg/l
	Marine water	0,001 mg/l
	Freshwater sediment	0,423 mg/kg
	Marine sediment	0,042 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1,33 mg/l
	Soil	0,079 mg/kg
79-41-4	methacrylic acid	
	Freshwater	0.82 mg/l
	Freshwater (intermittent releases)	0.45 mg/l
	Marine water	0.082 mg/l
	Freshwater sediment	3.09 mg/kg
	Marine sediment	0.309 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	0.137 mg/kg
103-50-4	Dibenzyl ether	
	Freshwater	0.002 mg/l
	Freshwater (intermittent releases)	0.008 mg/l
	Marine water	0 mg/l
	Freshwater sediment	0.12 mg/kg
	Marine sediment	0.012 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1.38 mg/l
	Soil	0.023 mg/kg
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	
	Freshwater	0.002 mg/l
	Freshwater (intermittent releases)	0.019 mg/l
	Marine water	0 mg/l
	Freshwater sediment	0.038 mg/kg
	Marine sediment	0.004 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0.006 mg/kg
1187441-10-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	
	Freshwater	0.165 mg/l
	Freshwater (intermittent releases)	1.65 mg/l
	Marine water	0.017 mg/l
	Freshwater sediment	2.8 mg/kg
	Marine sediment	0.28 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0.4 mg/l
	Soil	0.46 mg/kg
91-66-7	N,N-diethylaniline	
	Freshwater	0,00936 mg/l
	Freshwater (intermittent releases)	0,0742 mg/l
	Marine water	0,000936 mg/l
	Freshwater sediment	2,52 mg/kg
	Marine sediment	0,252 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0,018 mg/l
	Soil	0,498 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 8 of 18

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
868-77-9	2-hydroxyethyl methacrylate	
Freshwater		0.482 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0.048 mg/l
Freshwater sediment		3.79 mg/kg
Marine sediment		3.79 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0.476 mg/kg
102-82-9	tributylamine	
Freshwater		0.008 mg/l
Freshwater (intermittent releases)		0.08 mg/l
Marine water		0.0008 mg/l
Freshwater sediment		35.85 mg/kg
Marine sediment		3.59 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		7.17 mg/kg
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]	
Freshwater		0.001 mg/l
Marine water		0 mg/l
Freshwater sediment		0.195 mg/kg
Marine sediment		0.019 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn (EN ISO 374)
Breakthrough times and swelling properties of the material must be taken into consideration.
NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: A/P2

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 9 of 18

Colour: white
 Odour: characteristic
 Odour threshold: not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	not determined	not applicable
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	>90 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density:	not determined	
Relative density:	not determined	
Relative vapour density:	not determined	
Particle characteristics:	Polymer preparations and compounds	
	Particle size < 5 mm	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
 The product is not: Explosive.

Oxidizing properties
 not determined

Other safety characteristics

Evaporation rate: not determined
 Solid content: not determined
 Viscosity / dynamic: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.
 Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 10 of 18

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2495-37-6	Benzyl methacrylate				
	oral	LD50 3980 mg/kg	Rat	Study report (1984)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2011)	EU Method B.3
79-41-4	methacrylic acid				
	oral	LD50 1320 mg/kg	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 500 mg/kg	Rabbit	Pre-supplier/manufacturer	
	inhalation vapour	ATE 11 mg/l			OECD 403
	inhalation dust/mist	ATE 1,5 mg/l			
103-50-4	Dibenzyl ether				
	oral	LD50 4807 mg/kg	Rat	Study report (1976)	Ten male rats received a single oral app
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1998)	OECD Guideline 401
	dermal	LD50 > 13200 mg/kg	Rabbit	Study report (1984)	An acute dermal toxicity study was performed
1187441-10-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2004)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	REACH Registration Dossier	OECD Guideline 423
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-				
	oral	ATE 500 mg/kg			
91-66-7	N,N-diethylaniline				
	oral	ATE 100 mg/kg			
	dermal	LD50 > 400 mg/kg	Rabbit	ChemIDplus (2018)	other: As mentioned below
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 11 of 18

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 5564 mg/kg	Rat	Study report (1977)	other: Appraisal of the safety of chem b
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	The test substance, as received, was hel
102-82-9	tributylamine				
	oral	LD50 420 mg/kg	Rat	Publication (1974)	Method: acute oral toxicity test Screeni
	dermal	LD50 195 mg/kg	Rabbit	Publication (1974)	Method: acute dermal toxicity Screening
	inhalation (4 h) vapour	LC50 0.5 mg/l	Rat	Study report (1987)	OECD Guideline 403
	inhalation dust/mist	ATE 0,005 mg/l			
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]				
	oral	LD50 > 7000 mg/kg	Rat	Study report (1979)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1992)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (Benzyl methacrylate; Dibenzyl ether; Propylidynetrimethanol, ethoxylated, esters with acrylic acid; 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-; 2-hydroxyethyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Benzyl methacrylate; methacrylic acid)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 12 of 18

No data available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
2495-37-6	Benzyl methacrylate					
	Acute fish toxicity	LC50 4,67 mg/l	96 h	Pimephales promelas	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 2,28 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Crustacea toxicity	NOEC 4,21 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
79-41-4	methacrylic acid					
	Acute fish toxicity	LC50 833 mg/l	96 h	Scophthalmus maximus	Publication (2001)	other: OSPAR Protocols on Methods for th
	Acute algae toxicity	ErC50 54 mg/l	72 h	Raphidocelis subcapitata	Study report, unpublished, cover page mi	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 130 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Fish toxicity	NOEC 10 mg/l	35 d	Danio rerio	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 53 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 13500 mg/l ()	3 h	Activated sludge	Publication (2008)	ISO 8192
103-50-4	Dibenzyl ether					
	Acute fish toxicity	LC50 6.8 mg/l	96 h	Oryzias latipes	Study report (1996)	OECD Guideline 203
	Acute crustacea toxicity	EC50 0.77 mg/l	48 h	Daphnia magna	Study report (1996)	OECD Guideline 202
	Acute bacteria toxicity	EC50 138 mg/l ()		Activated sludge	Study report (1996)	other: Official Journal of the European
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid					
	Acute fish toxicity	LC50 1.95 mg/l	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 2.2 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 70.7 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
1187441-1 0-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Cyprinus carpio	REACH Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50 90 mg/l	72 h	Selenastrum capricornutum, strain: NIVA CHL 1.	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
91-66-7	N,N-diethylaniline					
	Acute fish toxicity	LC50 42,25 mg/l	96 h	Danio rerio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 7,42 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 35,2 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC 0,936 mg/l	21 d	Daphnia magna	REACH Registration Dossier	other: modelling data
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 345 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 380 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC 24.1 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
102-82-9	tributylamine					
	Acute fish toxicity	LC50 16.3 mg/l	96 h	Oryzias latipes	Study report (2000)	other: Testing Methods for Industrial Wa
	Acute algae toxicity	ErC50 10.1 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 8 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/man ufacturer	OECD 202

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 14 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]					
	Acute fish toxicity	LC50 43 mg/l	96 h	Lepomis macrochirus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h		REACH Registration Dossier	
	Fish toxicity	NOEC > 0.115 mg/l	7 d	Pimephales promelas	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC > 0.045 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

No data available

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
102-82-9	tributylamine				
	OECD 301B	88 %	28	Pre-supplier/manufacturer	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2495-37-6	Benzyl methacrylate	3,1
79-41-4	methacrylic acid	0.93
103-50-4	Dibenzyl ether	3.31
28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89
1187441-10-6	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction products with phosphorus oxide	>= 0.3
91-66-7	N,N-diethylaniline	3,904
868-77-9	2-hydroxyethyl methacrylate	0.42
102-82-9	tributylamine	3.338
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]	4.7

BCF

CAS No	Chemical name	BCF	Species	Source
103-50-4	Dibenzyl ether	>= 171	Cyprinus carpio	Study report (2009)
91-66-7	N,N-diethylaniline	>= 44 - = 17	Cyprinus carpio	REACH Registration D
102-82-9	tributylamine	7.3	Cyprinus carpio	REACH Registration D
36443-68-2	Ethylenebis(oxyethylene) bis[3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate]	2 - 12	Cyprinus carpio	REACH Registration D

12.4. Mobility in soil

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 15 of 18

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 16 of 18

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

Other applicable information

1673-1+1664: UN 3527 = POLYESTER RESIN KIT, solid base material, Class 4.1, III

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions: 5.159 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

(EU) EINECS/ELINCS/NLP: yes

(RC) TCSI: no

(NZ) NZIoC: no

(USA) TSCA: yes

(CDN) DSL: no

(ROK) KECI/ECL: yes

(RP) PICCS: unknown

(JP) MITI: yes

(CHN) IECSC: no

(AUS) AIIC: yes

(CDN) NDSL: no

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

Acute Tox. 1: Acute toxicity, hazard category 1
 Acute Tox. 2: Acute toxicity, hazard category 2
 Acute Tox. 3: Acute toxicity, hazard category 3
 Acute Tox. 4: Acute toxicity, hazard category 4
 Skin Corr. 1A: Skin corrosion, sub-category 1A

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 17 of 18

Skin Irrit. 2: Skin irritation, hazard category 2
 Eye Dam. 1: Serious eye damage, hazard category 1
 Eye Irrit. 2: Eye irritation, hazard category 2
 Skin Sens. 1: Skin sensitisation, hazard category 1
 Skin Sens. 1B: Skin sensitisation, hazard category 1B
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H301 Toxic if swallowed.
 H302 Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

1675-1 MA structural adhesive - 1673-1 resin

Revision: 28.01.2026

Product code: 1673-1

Page 18 of 18

Relevant H and EUH statements (number and full text)

H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)