

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

UFI: NVK4-D09T-J00W-J7KA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	Kisling AG	
Street:	Motorenstrasse 102	
Place:	CH-8620 Wetzikon	
Telephone:	+41 58 272 0 272	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

Supplier

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number: 24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Org. Perox. E; H242
Eye Irrit. 2; H319
Skin Sens. 1; H317
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

dibenzoyl peroxide; benzoyl peroxide
bis-[4-(2,3-epoxypropoxy)phenyl]propane
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 2 of 13

Pictograms:



Hazard statements

- H242 Heating may cause a fire.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P234 Keep only in original packaging.
 P273 Avoid release to the environment.
 P280 Wear protective gloves and eye protection/face protection.
 P403 Store in a well-ventilated place.
 P411 Store at temperatures not exceeding 50 °C/122 °F.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H317

Precautionary statements

P280

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
94-36-0	dibenzoyl peroxide; benzoyl peroxide	30 - < 50 %
	202-327-6	617-008-00-0
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 1; H241 H319 H317 H410	
1675-54-3	bis-[4-(2,3-epoxypropoxy)phenyl]propane	1 - < 5 %
	216-823-5	603-073-00-2
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
94-36-0	202-327-6	dibenzoyl peroxide; benzoyl peroxide	30 - < 50 %
		Aquatic Chronic 1; H410: M=10	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	1 - < 5 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 4 of 13

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
94-36-0	dibenzoyl peroxide; benzoyl peroxide		
Worker DNEL, long-term	inhalation	systemic	39 mg/m ³
Worker DNEL, long-term	dermal	systemic	13.3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2 mg/kg bw/day
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane		
Worker DNEL, long-term	inhalation	systemic	4,93 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,0893 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,5 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,5 mg/kg bw/day

PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
94-36-0	dibenzoyl peroxide; benzoyl peroxide	
Freshwater	0.00002 mg/l	
Freshwater (intermittent releases)	0.000602 mg/l	
Marine water	0.000002 mg/l	
Freshwater sediment	0.013 mg/kg	
Marine sediment	0.001 mg/kg	
Micro-organisms in sewage treatment plants (STP)	0.35 mg/l	
Soil	0.003 mg/kg	
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater	0,006 mg/l	
Freshwater (intermittent releases)	0,018 mg/l	
Marine water	0,001 mg/l	
Freshwater sediment	0,341 mg/kg	
Marine sediment	0,034 mg/kg	
Secondary poisoning	11 mg/kg	
Micro-organisms in sewage treatment plants (STP)	10 mg/l	
Soil	0,065 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 6 of 13

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

EN ISO 374

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	blue
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	not determined	not applicable
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	not determined	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	1,15 g/cm ³	
Relative density:	not determined	
Relative vapour density:	not determined	
Particle characteristics:	Polymer preparations and compounds	
	Particle size < 5 mm	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 7 of 13

Oxidizing properties
not determined

Other safety characteristics

Evaporation rate: not determined
Solid content: not determined
Viscosity / dynamic: 60.000 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.
Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 mg/kg	19800	Rabbit	Publication (1958) Rabbits were orally gavaged with test ma
	dermal	LD50 mg/kg	23000	Rabbit	Pre-supplier/manufac turer

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (dibenzoyl peroxide; benzoyl peroxide; bis-[4-(2,3-epoxipropoxy)phenyl]propane)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 8 of 13

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
94-36-0	dibenzoyl peroxide; benzoyl peroxide					
	Acute fish toxicity	LC50 0.06 mg/l	96 h	Oncorhynchus mykiss	Study report (2010)	EU Method C.1
	Acute algae toxicity	ErC50 0.071 mg/l	72 h	Raphidocelis subcapitata	Study report (2010)	EU Method C.3
	Acute crustacea toxicity	EC50 0.11 mg/l	48 h	Daphnia magna	Study report (2010)	EU Method C.2
	Acute bacteria toxicity	EC50 35 mg/l ()		activated sludge of a predominantly domestic sewage	Study report (1990)	OECD Guideline 209
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	Study report (2007)	OECD Guideline 201

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 9 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	dibenzoyl peroxide; benzoyl peroxide	3.2
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	>= 2,64

BCF

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	31		Study report (2010)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3108
14.2. UN proper shipping name:	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide; benzoyl peroxide)
14.3. Transport hazard class(es):	5.2
14.4. Packing group:	-
Hazard label:	5.2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 10 of 13



Classification code: P1
 Special Provisions: 122 274
 Limited quantity: 500 g
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3108
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide; benzoyl peroxide)
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
 Hazard label: 5.2



Classification code: P1
 Special Provisions: 122 274
 Limited quantity: 500 g
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 3108
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide; benzoyl peroxide)
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
 Hazard label: 5.2



Special Provisions: 122 274
 Limited quantity: 500 g
 Excepted quantity: E0
 EmS: F-J, S-R
 Segregation group: 16 - peroxides

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3108
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
 Hazard label: 5.2



Special Provisions: A20 A802
 Limited quantity Passenger: Forbidden
 Passenger LQ: Forbidden

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 11 of 13

Excepted quantity:	E0	
IATA-packing instructions - Passenger:		570
IATA-max. quantity - Passenger:		10 kg
IATA-packing instructions - Cargo:		570
IATA-max. quantity - Cargo:		25 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: (DIBENZOYL PEROXIDE)

14.6. Special precautions for user

Warning : Organic peroxides !

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

1663+1664, 1668+1664:

UN 3527 = POLYESTER RESIN KIT, solid base material, Class 4.1, II

1673-1+1664, 1678-1+1664:

UN 3527 = POLYESTER RESIN KIT, solid base material, Class 4.1, III

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions: 0.002 % (0.023 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
Additional information: E1

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 12 of 13

Abbreviations and acronyms

Org. Perox
 Skin Irrit: Skin irritation
 Eye Irrit: Eye irritation
 Skin Sens: Skin sensitisation
 Aquatic Chronic: Chronic aquatic hazard
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Org. Perox. E; H242	On basis of test data
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H241 Heating may cause a fire or explosion.
 H242 Heating may cause a fire.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 1664 - Component B 1665, 1670, 1675-1, 1680-1

Revision date: 09.12.2024

Product code: 1664

Page 13 of 13

H319	Causes serious eye irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)