

Page 1/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 1906 - Component B ergo 1907

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41- 58-272 0 272

- Only representative (REACH) and importer (CLP):

Kisling Deutschland GmbH

Salzstraße 15

D-74676 Niedernhall

Tel +49 8171 99982 30

- Further information obtainable from: ergo@kisling.com
- Department issuing MSDS: ergo@kisling.com
- 1.4 Emergency telephone number: +49-700-24 112 112 (KAR)

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms







GHS07 GHS08 GHS09

- Signal word Warning

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

2-hydroxyethyl methacrylate

hydroxypropyl methacrylate, mixture of CAS 923-26-2 and 2761-09-3

Ethoxylated Bisphenol-A Dimethacrylate

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 1)

H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.

## - Precautionary statements

P261 Avoid breathing vapours.

P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

## - Labelling of packages where the contents do not exceed 125 ml

#### - Hazard pictograms







GHS07 GHS08 GHS09

#### - Signal word Warning

## - Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

2-hydroxyethyl methacrylate

hydroxypropyl methacrylate, mixture of CAS 923-26-2 and 2761-09-3

Ethoxylated Bisphenol-A Dimethacrylate

#### - Hazard statements

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

#### - Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves / eye protection.

P308+P313 IF exposed or concerned: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- 2.3 Other hazards

## - Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### - 3.2 Mixtures

- **Description:** Adhesive

- Dangerous components:			
CAS: 10595-06-9 EINECS: 234-201-1 Reg.nr.: 01-2120752383-55-xxxx	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	> 30 - ≤ 50%	
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X Reg.nr.: 01-2119490169-29-xxxx	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%	
CAS: 923-26-2 EINECS: 213-090-3 Index number: 607-125-00-5	hydroxypropyl methacrylate, mixture of CAS 923-26-2 and 2761-09-3 Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%	
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 4, H413	> 15 - < 20%	
		(Contd. on nogo 2)	

(Contd. on page 3)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

		(Contd. of page 2)
CAS: 121-69-7	N,N-dimethylaniline	≥ 0.25 - ≤ 1%
EINECS: 204-493-5	Flam. Liq. 3, H226; Acute Tox. 3, H301; Acute Tox. 3,	
Index number: 612-016-00-0	H311; Acute Tox. 3, H331; Carc. 2, H351; Aquatic	
	Chronic 2, H411	

- Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

#### - 4.1 Description of first aid measures

- General information: Remove any clothing soiled by the product.

#### - After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### - After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

#### - After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### - After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

## - 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### - 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

## - 5.1 Extinguishing media

## - Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

## - 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

## - 5.3 Advice for firefighters

## - Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

### - Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

## - 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

## - 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

## - 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

## - 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

(Contd. on page 4)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

See Section 13 for disposal information.

(Contd. of page 3)

## **SECTION 7: Handling and storage**

#### - 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

No special precautions are necessary if used and stored according to specifications.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- Maximum storage temperature: 28 °C
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- -8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

T				
	- Ingredients with limit values that require monitoring at the workplace:			
868-77-9 2-hydr	868-77-9 2-hydroxyethyl methacrylate			
MAK (Germany)	vgl.Abschn.IIb			
923-26-2 hydrox	xypropyl methacrylate, mixture of CAS 923-26-2 and 2761-09-3			
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IV			
· · · · · · · · · · · · · · · · · · ·	121-69-7 N,N-dimethylaniline			
AGW (Germany	Long-term value: 25 mg/m³, 5 ppm 2(II);DFG, H			

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

#### - Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

filter A (EN 141)

#### - Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### - Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

(Contd. on page 5)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 4)

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Chloropren Nitril I, Nr. 0727

Viton, Nr. 0890 Butyl II, Nr. 0897 Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403 Chloropren Nitril II, Nr. 0717

Chloropren, Nr. 0720, 0722, 0723, 0725 oder 0726

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

of KCL company (e-mail: vertrieb@kcl.de).

.

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## - Penetration time of glove material

Permeation time / penetration time: see above (material of gloves)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

## **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties - General Information		
- Appearance:		
Form:	Fluid	
Colour:	Green	
- Odour:	Characteristic	
- Odour threshold:	Not determined.	
- pH-value:	Not determined.	
- Change in condition Melting point/freezing point: Initial boiling point and boiling rang	Undetermined. e: Undetermined.	
- Flash point:	> 70 °C	
- Flammability (solid, gas):	Not applicable.	
- Decomposition temperature:	Not determined.	
- Auto-ignition temperature:	Product is not self-igniting.	
- Explosive properties:	Product does not present an explosion hazard.	
- Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
- Oxidising properties	Not determined.	

(Contd. on page 6)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

	(Contd. of page 5
- Vapour pressure:	Not determined.
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	1 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
- Solubility in / Miscibility with water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity: Dynamic at 25 °C: Kinematic:	7000 mPas Not determined.
- 9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

Protect from exposure to the light.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

## **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:			
10595-0	10595-06-9 2-phenoxyethyl methacrylate		
Oral	Oral LD50 5050 mg/kg (Rat, male/female)		
868-77-	868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5050 mg/kg (Rat, male/female)	
Dermal	LD50	3000 mg/kg (Rabbit)	
121-69-	121-69-7 N,N-dimethylaniline		
Oral	LD50	1410 mg/kg (Rat, male/female)	

- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 6)

- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- Toxicity to fish:

## 868-77-9 2-hydroxyethyl methacrylate

LC50/96 h 213 - 242 mg/l (Pimephales promelas)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

- 14.1 UN-Number - ADR, IMDG, IATA	UN3082
- 14.2 UN proper shipping name - ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl
- IMDG	methacrylate, N,N-DIMETHYLANILINE) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate, N,N- DIMETHYLANILINE), MARINE POLLUTANT
- IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethyl methacrylate, N,N-DIMETHYLANILINE)

(Contd. on page 8)

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 7
9 (M6) Miscellaneous dangerous substances and articles.
9 Miscellaneous dangerous substances and articles.
Ш
Product contains environmentally hazardous substances 2-phenoxyethyl methacrylate Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
Warning: Miscellaneous dangerous substances and
articles. 90 F-A,S-F A
of Not applicable.
ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
SV375: These substances are not subject to the other provisions of ADR / RID if they are transported in individual of composite packaging with a net quantity of no more than a lof liquid substances or a net mass of no more than 5 kg of solids per individual or inner packaging, provided that the packaging is used correspond to the general provision of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 8)

- Remarks:

- Limited quantities (LQ) 5L Code: E1 - Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

2.10.2.7:

Marine pollutants in individual packaging or composite packaging with a net quantity per individual or inner packaging of no more than 5 L for liquids or a net mass per individual or inner packaging of no more than 5 kg for solids are not subject to any other provisions of this Code applicable to marine pollutants, provided that the packaging complies with the general Meet the requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants that also meet the criteria for inclusion in another class, all provisions of this Code that apply to any further hazards continue to apply.

- IATA

- Remarks: A 197 (375):

> These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1,

5.0.2.6.1.1 and 5.0.2.8.

- UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (2-PHENOXYETHYL METHACRYLATE, N,N-DIMETHYLANILINE), 9, III

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Chemical safety assessment
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

## - Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 26.02.2021 Version number 3 Revision: 26.02.2021

Trade name: ergo 1906 - Component B ergo 1907

(Contd. of page 9)

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### - Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

#### - Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

- \* Data compared to the previous version altered.

- EU-EN