10.04.2023	Kit Components	
Product code	Description	
KIS 1925-200801	1925	
Components:		
KIS 1923-200801	1923 - Component A 1925	
KIS 1924-200801	1924 - Component B 1925	



Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- -1.1 Product identifier
- Trade name: 1923 Component A 1925
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives
- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360 May damage fertility or the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

-2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms







GHS07

7 GHS08

08 GHS09

- Signal word Danger

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate methacrylic acid, monoester with propane-1,2-diol 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol

2-ethylhexyl methacrylate

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360 May damage fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

(Contd. of page 1)

- Precautionary statements

P261 Avoid breathing mist/vapours/spray. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Additional information:

10-30 percent of the mixture consists of one or more ingredients of unknown acute oral toxicity.

10-30 percent of the mixture consists of one or more ingredients of unknown acute dermal toxicity.

40-60 percent of the mixture consists of one or more components of unknown acute inhalation toxicity.

Contains 10-30 % of components with unknown hazards to the aquatic environment.

Restricted to professional users.

- -2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	20-40%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 688-84-6 EINECS: 211-708-6 Index number: 607-134-00-4	2-ethylhexyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	> 15 - < 20%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	5-10%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α,α -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 %	<5%
CAS: 119-47-1 EINECS: 204-327-1 Index number: 604-095-00-5	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Repr. 1B, H360	≥ 0.3 - ≤ 1%
- The product may contain:		
CAS: 107-13-1 EINECS: 203-466-5 Index number: 608-003-00-4	acrylonitrile Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; A H331; Carc. 1B, H350; Eye Dam. 1, H318; Aquatic Chronic 2 Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

(Contd. on page 3)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

	(Contd. of page 2)	
CAS: 106-99-0	1,3-butadiene	
EINECS: 203-450-8	Flam. Gas 1A, H220; Acute Tox. 2, H330; Muta. 1B, H340; Carc. 1A, H350;	
Index number: 601-013-00-X	Press. Gas (Comp.), H280	
-SVHC		
119-47-1 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol		
- Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

-4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- -5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- -5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- -5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

(Contd. of page 3)

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Protect from frost.

- Maximum storage temperature: 28 °C
- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 6.1 C
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

-8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- DNE	Ls		
2781	27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Dern	Dermal Longterm System 4.2 mg/kg bw/day (General population)		
- PNE	Cs		
2781	27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Oral	PNEC oral	mg/kg Food (General population)	
	PNEC Freshwater	0.904 mg/l (General population)	
	PNEC Freshwater sed	6.28 mg/kg (General population)	
	PNEC Marinewater	0.904 mg/l (General population)	
	PNEC Soil	0.727 mg/kg (General population)	
	PNEC STP	10 mg/l (General population)	
	PNEC Marinewater sed	6.28 mg/kg (General population)	

- Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

(Contd. of page 4)

-8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

filter A (EN 141)

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I, Nr. 0395 oder 0403

Chloropren Nitril II, Nr. 0717

Chloropren Nitril I, Nr. 0727

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

Permeation time / penetration time: see above (material of gloves)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

- -9.1 Information on basic physical and chemical properties
- General Information

- Colour: Yellow - Odour: Light

(Contd. on page 6)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

	(Contd. of page
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling	
range	Undetermined.
- Flammability	Not applicable.
- Lower and upper explosion limit	11
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	> 100 °C
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	1,00,000
- Kinematic viscosity	Not determined.
- Kinematic viscosity	Tot determined.
- Dynamic at 20 °C:	20,000 mPas
- Solubility	20,000 iii us
- Solubility - water:	Not miscible or difficult to mix.
- water: - Partition coefficient n-octanol/water (log value)	Not determined.
	Not determined.
- Vapour pressure:	Not determined.
- Vapour pressure:	
- Density and/or relative density	1 / 2
- Density at 20 °C:	1 g/cm³
- Relative density	Not determined.
- Vapour density	Not determined.
-9.2 Other information	
- Appearance:	
- Form:	Viscous
- Important information on protection of health an	d
environment, and on safety.	
- Ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Change in condition	1 1
- Softening point/range	
- Oxidising properties	Not determined.
- Evaporation rate	Not determined.
- Information with regard to physical hazard classe	
- Explosives	Void Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Void
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flammable	
gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void

(Contd. on page 7)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

- 10.3 Possibility of hazardous reactions

Reacts with peroxides and other radical forming substances.

Reacts with strong alkali.

Reacts with strong acids.

Reacts with amines.

Forms explosive gas mixture with air.

Exothermic polymerisation.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50	- LD/LC50 values relevant for classification:		
10595-06-	10595-06-9 2-phenoxyethyl methacrylate		
Oral	LD50 5,050 mg/kg (Rat, male/female)		
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide		
Oral	LD50	382 mg/kg (Rat, male/female)	
Dermal	LD50	500 mg/kg (Rat, male/female)	
Inhalative	LC50/4 h	1.37 mg/l (Rat, male/female)	

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

May damage fertility or the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

-CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
Repr. 1B

(Contd. on page 8)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

-11.2 Information on other hazards

(Contd. of page 7)

11.2 Information on other nazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- -12.2 Persistence and degradability No further relevant information available.
- -12.3 Bioaccumulative potential No further relevant information available.
- -12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects No further relevant information available.
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

- 14.1 UN number or ID number - ADR, IMDG, IATA	UN3082
- ADK, IMDG, IATA	UN3002
- 14.2 UN proper shipping name	
-ADR	3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate)
- IMDG	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate), MARINE POLLUTANT
- IATA	ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy
	methacrylate)

CH-EN -

Version number 2 (replaces version 1) Printing date 10.04.2023 Revision: 10.04.2023

Trade name: 1923 - Component A 1925

	(Contd. of page
- 14.3 Transport hazard class(es)	
- ADR	
- Class	9 (M6) Miscellaneous dangerous substances an articles.
- Label	9
- IMDG, IATA	
- Class - Label	9 Miscellaneous dangerous substances and articles.
- 14.4 Packing group - ADR, IMDG, IATA	III
- 14.5 Environmental hazards:	Product contains environmentally hazardou substances: 2-phenoxyethyl methacrylate
-Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
-14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
- Hazard identification number (Kemler code):	90
- EMS Number:	F-A,S-F
- Stowage Category	A
- 14.7 Maritime transport in bulk according to IM instruments	Not applicable.
- Transport/Additional information:	ADR: SV375
	IMDG-Code: 2.10.2.7
	IATA-DGR: A197 (375)
- ADR - Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category - Tunnel restriction code	3 (-)
- Remarks:	(-) SV375:
	These substances are not subject to the other provision of ADR / RID if they are transported in individual composite packaging with a net quantity of no mor than 5 l of liquid substances or a net mass of no mor than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to the general provisions of subsections 4.1.1.1, 4.1.1.2 an 4.1.1.4 to 4.1.1.8.

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1923 - Component A 1925

	(Contd. of page 9
- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
D 1	Maximum net quantity per outer packaging: 1000 ml
- Remarks:	2.10.2.7:
	Marine pollutants in individual packaging or composit packaging with a net quantity per individual or inne
	packaging of no more than 5 L for liquids or a net mas
	per individual or inner packaging of no more than 5 k
	for solids are not subject to any other provisions of the
	Code applicable to marine pollutants, provided that the
	packaging complies with the general Meet th
	requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 In the case of marine pollutants that also meet the
	criteria for inclusion in another class, all provisions of
	this Code that apply to any further hazards continue t
	apply.
-IATA	
- Remarks:	A 197 (375):
	These substances when transported in single of
	combination packagings containing a net quantity pe
	single or inner packaging of 5 L or less for liquids of having a net mass of 5 kg or less for solids, are no
	subject to any other provisions of these Regulation
	provided the packagings meet the general provisions of
	5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
S	SUBSTANCE, LIQUID, N.O.S. (2
	PHENOXYETHYL METHACRYLATE), 9, III

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- -15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H242 Heating may cause a fire.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.

(Contd. on page 11)

Revision: 10.04.2023 Printing date 10.04.2023 Version number 2 (replaces version 1)

Trade name: 1923 - Component A 1925

(Contd. of page 10) H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H335 May cause respiratory irritation. H340 May cause genetic defects. H350 May cause cancer. H360 May damage fertility or the unborn child. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. - Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Org. Perox. E: Organic peroxides - Type E/F Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 1B: Reproductive toxicity - Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

- * Data compared to the previous version altered.

CH-EN



Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- -1.1 Product identifier
- Trade name: 1924 Component B 1925
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives
- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361d Suspected of damaging the unborn child.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

-2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms









GHS05

05 GHS07

GHS08

GHS09

- Signal word Danger

- Hazard-determining components of labelling:

2-phenoxyethyl methacrylate

2-Propenoic acid, 2-methyl-, 2-hydroxyethylester, phosphate methacrylic acid, monoester with propane-1,2-diol

2-ethylhexyl methacrylate

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 1)

- Precautionary statements

P261 Avoid breathing mist/vapours/spray. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Additional information:

10-30 percent of the mixture consists of one or more ingredients of unknown acute oral toxicity.

10-30 percent of the mixture consists of one or more ingredients of unknown acute dermal toxicity.

50-70 percent of the mixture consists of one or more components of unknown acute inhalation toxicity.

Contains 10-30 % of components with unknown hazards to the aquatic environment.

-2.3 Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

-3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 10595-06-9 EINECS: 234-201-1	2-phenoxyethyl methacrylate Repr. 2, H361d; Aquatic Chronic 2, H411; Skin Sens. 1A, H317	20-40%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5	methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317	> 15 - ≤ 30%
CAS: 688-84-6 EINECS: 211-708-6 Index number: 607-134-00-4	2-ethylhexyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥ 10 - ≤ 15%
CAS: 41637-38-1 EC number: 609-946-4	Ethoxylated Bisphenol-A Dimethacrylate Aquatic Chronic 4, H413	> 5 - ≤ 15%
CAS: 52628-03-2 EINECS: 258-053-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethylester, phosphate Eye Dam. 1, H318; Skin Irrit. 2, H315	≥ 3 - ≤ 5%
CAS: 92-84-2 EINECS: 202-196-5	phenothiazine STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	≥ 0.1 - < 0.25%
CAS: 150-76-5 EINECS: 205-769-8 Index number: 604-044-00-7	mequinol Repr. 2, H361d; Acute Tox. 4, H302; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥ 0.1 - < 1%
- The product may contain:		
CAS: 107-13-1	acrylonitrile	

acrylonitrile
Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3,
H331; Carc. 1B, H350; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin
Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335
1,3-butadiene
Flam. Gas 1A, H220; Acute Tox. 2, H330; Muta. 1B, H340; Carc. 1A, H350;
Press. Gas (Comp.), H280

(Contd. on page 3)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 2)

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

-4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

-5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- -5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

-5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

CH EN

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 3)

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire and explosion protection: No special measures required.
- -7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

-8.1 Control parameters			
- Ingredients with limit	- Ingredients with limit values that require monitoring at the workplace:		
92-84-2 phenothiazine	92-84-2 phenothiazine		
MAK (Switzerland) Lo	ng-term value: 5 e mg/m³		
- DNELs			
27813-02-1 methacryli	c acid, monoester with propane-1,2-diol		
Dermal Longterm Syste	em 4.2 mg/kg bw/day (General population)		
- PNECs			
27813-02-1 methacryli	c acid, monoester with propane-1,2-diol		
Oral PNEC oral	mg/kg Food (General population)		
PNEC Freshwater	0.904 mg/l (General population)		
PNEC Freshwater	sed 6.28 mg/kg (General population)		
PNEC Marinewate	er 0.904 mg/l (General population)		
PNEC Soil	0.727 mg/kg (General population)		
PNEC STP	10 mg/l (General population)		
PNEC Marinewate	er sed 6.28 mg/kg (General population)		

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

filter A (EN 141)

(Contd. on page 5)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 4)

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I, Nr. 0395 oder 0403 Chloropren Nitril II, Nr. 0717 Chloropren Nitril I, Nr. 0727 Viton, Nr. 0890

Viton, Nr. 0890 Butyl II, Nr. 0897 Butyl, Nr. 0898

.

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

Permeation time / penetration time: see above (material of gloves)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eve/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

-9.1 Information on basic physical and chemical properties	- 9.1	Information	on basic	physical a	and chemical	properties
--	-------	-------------	----------	------------	--------------	------------

- General Information

- Colour: Grey - Odour: Light

- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

- Lower and upper explosion limit

- Lower: Not determined.
- Upper: Not determined.
- Flash point: > 100 °C
- Decomposition temperature: Not determined.
- pH Not determined.

- Viscosity:

- Kinematic viscosity Not determined.

- Kinematic viscosity

- **Dynamic at 20 °C:** 20,000 mPas

(Contd. on page 6)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

	(Contd. of page
Solubility	
-water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
-Vapour pressure:	Not determined.
- Vapour pressure:	
- Density and/or relative density	
- Density at 20 °C:	1 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
- 9.2 Other information	
- Appearance:	
- Form:	Viscous
- Important information on protection of health an	d
environment, and on safety.	
- Ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Change in condition	
- Softening point/range	
- Oxidising properties	Not determined.
- Evaporation rate	Not determined.
- Information with regard to physical hazard classe	es
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Void
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flammable	
gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

CH-EN

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 6)

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:		
10595-06-9 2-phenoxyethyl methacrylate		
Oral	ral LD50 5,050 mg/kg (Rat, male/female)	
868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (Rat, male/female)
Dermal	LD50	3,000 mg/kg (Rabbit)

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr. 2
- -11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.

- 11	oxicity	, L.,	113	
		,		

868-77-9 2-hydroxyethyl methacrylate

LC50/96 h 213 - 242 mg/l (Pimephales promelas)

- -12.2 Persistence and degradability No further relevant information available.
- -12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

CH-EN

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 7)

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
 Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

- 141 IIV 1 ID 1	
- 14.1 UN number or ID number - ADR, IMDG, IATA	UN3082
- 14.2 UN proper shipping name - ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy methacrylate)
- IMDG - IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy methacrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-phenoxyethy methacrylate)
- 14.3 Transport hazard class(es)	
- ADR	
- Class	9 (M6) Miscellaneous dangerous substances an articles.
- Label	9
- IMDG, IATA - Class	9 Miscellaneous dangerous substances and articles.
- Label	9
- 14.4 Packing group - ADR, IMDG, IATA	III
- 14.5 Environmental hazards:	Product contains environmentally hazardou substances: 2-phenoxyethyl methacrylate
- Marine pollutant:	Symbol (fish and tree)
- Special marking (ADR): - Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
- 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
- Hazard identification number (Kemler code): - EMS Number: - Stowage Category	articles. 90 F-A,S-F A
- Stowage Category	A (Contd. on page

(Contd. on page 9)

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

147 Manitima turanament in bulbanan P	(Contd. of page
14.7 Maritime transport in bulk according instruments	Not applicable.
Transport/Additional information:	ADR: SV375 IMDG-Code: 2.10.2.7 IATA-DGR: A197 (375)
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
-Transport category -Tunnel restriction code -Remarks:	3 (-) SV375: These substances are not subject to the other provision of ADR / RID if they are transported in individual of composite packaging with a net quantity of no more than 5 l of liquid substances or a net mass of no more than 5 kg of solids per individual or inner packaging provided that the packaging is used correspond to the general provisions of subsections 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
-Remarks:	2.10.2.7: Marine pollutants in individual packaging or composit packaging with a net quantity per individual or inner packaging of no more than 5 L for liquids or a net may per individual or inner packaging of no more than 5 k for solids are not subject to any other provisions of the Code applicable to marine pollutants, provided that the packaging complies with the general Meet the requirements in 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.3. In the case of marine pollutants that also meet the criteria for inclusion in another class, all provisions of this Code that apply to any further hazards continue tapply.
-IATA - Remarks:	A 197 (375): These substances when transported in single of combination packagings containing a net quantity passingle or inner packaging of 5 L or less for liquids of having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulation provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (2 PHENOXYETHYL METHACRYLATE), 9, III

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

(Contd. of page 9)

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

(Contd. on page 11)

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2023 Version number 2 (replaces version 1) Revision: 10.04.2023

Trade name: 1924 - Component B 1925

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard — Category 4 -* Data compared to the previous version altered.

(Contd. of page 10)

CH-EN