

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 3120 Druckdose

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture

Adhesives

Silicate sealing

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41- 58-272 0 272

- Only representative (REACH) and importer (CLP):

Kisling Deutschland GmbH

Salzstraße 15

D-74676 Niedernhall

Tel +49 8171 99982 30

- Further information obtainable from: Product safety department

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number: +49-700-24 112 112 (KAR)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02

- Signal word Danger

- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description:

Adhesive
Silicate sealing

- Dangerous components:

CAS: 37859-55-5 ELINCS: 484-460-1 Reg.nr.: 01-2120004323-76-xxxx	2-Pentanone, O,O',O''-(methylsilyldyne)trioxime ----- Acute Tox. 4, H302; Eye Irrit. 2, H319	> 1 - ≤ 5%
CAS: 623-40-5 ELINCS: 484-470-6 Reg.nr.: 01-2119980079-27-xxxx	2-Pentanone oxime ----- Acute Tox. 4, H302; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	> 1 - < 2.5%
CAS: 58190-62-8 EC number: 700-810-0 Reg.nr.: 01-2120006148-66-xxxx	2-Pentanone,O,O',O''-(ethenylsilyldyne)trioxime ----- Acute Tox. 4, H302; Eye Irrit. 2, H319	≥ 0 - ≤ 5%
CAS: 68928-76-7 EINECS: 273-028-6	Dimethylbis[(1-oxoneodecyl)oxy]stannane ----- Repr. 2, H361d; STOT RE 1, H372; Acute Tox. 4, H302; Aquatic Chronic 4, H413	≤ 1%

- In the compressed gas mixture:

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane	Flam. Gas 1A, H220; Press. Gas (Comp.), H280
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure	Flam. Gas 1A, H220; Press. Gas (Comp.), H280

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- **General information:** Remove any clothing soiled by the product.

- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** After contact with skin, wash with plenty of water.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting; seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 2)

- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

Fumes can combine with air to form an explosive mixture.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions:

Protect from frost.

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- Maximum storage temperature: 30 °C

- Minimum storage temperature: 5 °C

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 2 B

- 7.3 Specific end use(s) No further relevant information available.

EU-EN

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **Additional information:**

If used according to specifications the propellant (contains propane/butane) is not liberated.
The lists valid during the making were used as basis.

- 8.2 Exposure controls

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- **Protection of hands:**

Protective gloves on prolonged contact with skin.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Find below a list of appropriate protective gloves for chemical surrounding:

.

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403

Naturlatex II , Nr. 0706 oder 0708

Chloropren Nitril II, Nr. 0717

Chloropren Nitril I, Nr. 0727

Chloropren, Nr. 0720, 0722, 0723, 0725 oder 0726

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Nitril II, Nr. 0740, 0741, 0742 oder 0759

Nitril III, Nr. 0743

Nitril VI, Nr. 0754

Nitril V, Nr. 0764

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

.

of KCL company (e-mail: vertrieb@kcl.de).

.

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 4)

- Penetration time of glove material

Permeation time / penetration time: see above (material of gloves)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Avoid contact with the eyes.**SECTION 9: Physical and chemical properties****- 9.1 Information on basic physical and chemical properties****- General Information****- Appearance:****Form:** Pasty**Colour:** Red**- Odour:** Characteristic**- Odour threshold:** Not determined.**- pH-value:** Not determined.**- Change in condition****Melting point/freezing point:** Undetermined.**Initial boiling point and boiling range:** Undetermined.**- Flash point:** Undetermined.**- Flammability (solid, gas):** Not applicable.**- Decomposition temperature:** Not determined.**- Auto-ignition temperature:** Product is not self-igniting.**- Explosive properties:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.**- Explosion limits:****Lower:** Not determined.**Upper:** Not determined.**- Oxidising properties** Not determined.**- Vapour pressure:** Not determined.**- Density at 20 °C:** 1.25 g/cm³**- Relative density** Not determined.**- Vapour density** Not determined.**- Evaporation rate** Not applicable.**- Solubility in / Miscibility with water:**

Hydrolised.

- Partition coefficient: n-octanol/water: Not determined.**- Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.**- 9.2 Other information**

The information applies to the active substance.

SECTION 10: Stability and reactivity**- 10.1 Reactivity** No further relevant information available.**- 10.2 Chemical stability****- Thermal decomposition / conditions to be avoided:** Protect from heat and direct sunlight.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 5)

- **10.3 Possibility of hazardous reactions** Danger of bursting.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

37859-55-5 2-Pentanone, O,O',O''-(methylsilyldiyl)trioxime		
Oral	LD50	1,234 mg/kg (Rat, male/female)
623-40-5 2-Pentanone oxime		
Oral	LD50	1,133 mg/kg (Rat, male/female)
68928-76-7 Dimethylbis[(1-oxoneodecyl)oxy]stannane		
Oral	LD50	894 mg/kg (Rat, male/female) (OECD 401)
Dermal	LD50	> 2,000 mg/kg (Rat, male/female) (OECD 402)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
No experimentally found toxicological data are available for this preparation.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class (German Regulation) is valid for the active agent.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.
Do not allow product to reach ground water, water course or undiluted sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

EU-EN

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 6)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number

- **ADR, IMDG, IATA** UN1950

- 14.2 UN proper shipping name

- **ADR** 1950 AEROSOLS
 - **IMDG** AEROSOLS
 - **IATA** AEROSOLS, flammable

- 14.3 Transport hazard class(es)

- ADR



- **Class** 2 5F Gases.
 - **Label** 2.1

- IMDG



- **Class** 2 Gases.
 - **Label** 2.1

- IATA



- **Class** 2.1
 - **Label** 2.1

- 14.4 Packing group

- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:** Not applicable.

- 14.6 Special precautions for user

- **Hazard identification number (Kemler code):** -
 - **EMS Number:** F-D,S-U
 - **Stowage Code** SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 - **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 7)

-	except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
---	--

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
--	-----------------

- **Transport/Additional information:**

- ADR	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
- Transport category	2
- Tunnel restriction code	D

- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

- UN "Model Regulation":	UN 1950 AEROSOLS, 2.1
---------------------------------	-----------------------

* **SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Chemical safety assessment**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **National regulations:**

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.07.2021

Version number 3

Revision: 25.07.2021

Trade name: ergo 3120 Druckdose

(Contd. of page 8)

H413 May cause long lasting harmful effects to aquatic life.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

- * Data compared to the previous version altered.

EU-EN