



Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: ergo 4211
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling Deutschland GmbH Bürgermeister-Seidl-Straße 2 D-82515 Wolfratshausen Tel +49 791 407 27-0 Fax +49 791 407 27-50

- Further information obtainable from: Safety Department
- Department issuing MSDS: ergo@kisling.com
- 1.4 Emergency telephone number: Tox Info Suisse: 145 / +41-44-2 51 51 51

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS07

GHS09

- Signal word Warning
- Hazard-determining components of labelling:

(octahydro-4,7-methano-1H-indenediyl)bis(methylene) bismethacrylate

1,3-butylglycol-dimethacrylate

- Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms





GHS07

GHS09

- Signal word Warning
- Hazard-determining components of labelling:

(octahydro-4,7-methano-1H-indenediyl)bis(methylene) bismethacrylate 1,3-butylglycol-dimethacrylate

- Hazard statements

H317 May cause an allergic skin reaction.

- Precautionary statements

Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description: Adhesive

- Dangerous components:		
CAS: 43048-08-4 EINECS: 256-062-6	(octahydro-4,7-methano-1H-indenediyl)bis(methylene) bismethacrylate Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥ 25 - < 30%
CAS: 1189-08-8 Reg.nr.: 01-2119969461-31-xxxx	1,3-butylglycol-dimethacrylate Skin Sens. 1B, H317	15 - < 30%
CAS: 3290-92-4 EINECS: 221-950-4	trimethylol propane trimethacrylate Aquatic Chronic 2, H411	≥ 10 - < 15%
CAS: 20882-04-6 EINECS: 244-096-4	{2-[(2-methyl-1-oxoallyl)oxy]ethyl} hydrogen succinate Skin Irrit. 2, H315; Eye Irrit. 2, H319	1 - < 5%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α,α -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335	≥ 1 - ≤ 2.5%
CAS: 114-83-0 EINECS: 204-055-3	2'-phenylacetohydrazide Acute Tox. 3, H301	≥ 0.1 - < 1%
CAS: 102-82-9 EINECS: 203-058-7	tributylamine Acute Tox. 3, H311; Acute Tox. 1, H330; Acute Tox. 4, H302; Skin Irrit. 2, H315	≥ 0.1 - < 1%
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4	1,4-dihydroxybenzene Muta. 2, H341; Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Sens. 1, H317	≥ 0.025 - ≤ 0.1%

(Contd. on page 3)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 2)

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Remove any clothing soiled by the product.

- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- 5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

- -7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

No special precautions are necessary if used and stored according to specifications.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters

- 8.1 Control parameters			
	- Ingredients with limit values that require monitoring at the workplace:		
	80-15-9 α,α -dimethylbenzyl hydroperoxide		
MAK (Ge	ak (Germany) als Dampf und Aerosol;vgl.Abschn.Xa		
102-82-9 1	102-82-9 tributylamine		
MAK (Ge	MAK (Germany) als Dampf und Aerosol;vgl.Abschn.IIb		
123-31-9	123-31-9 1,4-dihydroxybenzene		
MAK (Ge	rmany) als Dampf	und Aerosol	
- DNELs	·		
1189-08-8	1189-08-8 1,3-butylglycol-dimethacrylate		te
Dermal	Langzeit, System	ische Effekte	4.2 mg/kg bw/day (ber)
Inhalative	Langzeit, System	ische Effekte	14.5 mg/m³ (ber)
123-31-9	3-31-9 1,4-dihydroxybenzene		
Dermal	Langzeit, System	ische Effekte	64 mg/kg bw/day (all)
	Inhalative Langzeit, Lokale Effekte		128 mg/kg bw/day (ber)
Inhalative			0.5 mg/m³ (all)
			1 mg/m³ (ber)
	Langzeit, System	ische Effekte	1.74 mg/m³ (all)
			7 mg/m³ (ber)
- PNECs	-PNECs		
123-31-9	123-31-9 1,4-dihydroxybenzene		
PNEC Süßwasser 0.114 mg/l		0.114 mg/l	
PNEC Süß	Bwassersediment	0.00098 mg/	kg Sediment
PNEC Meerwasser 0.0114 mg/l PNEC Boden 0.000129 mg/kg		0.0114 mg/l	
		0.000129 mg	t/kg Boden
			(Contd. on page 5)

(Contd. on page 5)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

PNEC Kläranlage 0.71 mg/l
PNEC Meerwassersediment 0.000097 mg/kg Sediment (Contd. of page 4)

- CAS No. Designation of material % Type Value Unit

- Additional Occupational Exposure Limit Values for possible hazards during processing:		
144-62-7 oxalic acid		
IOELV (European Union)	Long-term value: 1 mg/m³	
AGW (Germany)	Long-term value: 1 E mg/m³ 1(I);H, EU, 13	

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403 Naturlatex II , Nr. 0706 oder 0708

Chloropren Nitril II, Nr. 0717

Chloropren Nitril I, Nr. 0727

Chloropren, Nr. 0720, 0722, 0723, 0725 oder 0726

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Nitril II, Nr. 0740, 0741, 0742 oder 0759

Nitril III, Nr. 0743 Nitril VI, Nr. 0754

Nitril V, Nr. 0764

Viton, Nr. 0890

Butyl II, Nr. 0897

Dutyl II, 181. 009

Butyl, Nr. 0898

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 5)

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties	
- General Information	
- Appearance:	Fluid
Form: Colour:	Violet
- Odour:	Characteristic
- Odour : - Odour threshold:	Not determined.
- pH-value:	Not determined.
•	Not determined.
- Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
- Flash point:	> 90 °C
- Flammability (solid, gas):	Not applicable.
- Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Vapour pressure:	Not determined.
- Density at 25 °C:	1.1 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity: Dynamic at 25 °C: Kinematic:	7 000 - 15 000 mPas (Brookfield (6/2,5)) Not determined.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

- 10.3 Possibility of hazardous reactions Reacts with metal-salts.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 6)

- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50	- LD/LC50 values relevant for classification:		
80-15-9 α,	80-15-9 α,α -dimethylbenzyl hydroperoxide		
Oral	LD50	382 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rat)	
Inhalative	LC50/4 h	220 mg/l (rat)	
114-83-0 2	114-83-0 2'-phenylacetohydrazide		
Oral	LD50	270 mg/kg (rat)	
102-82-9 t	102-82-9 tributylamine		
Inhalative	LC50/4 h	0.5 mg/l (rat)	
123-31-9	123-31-9 1,4-dihydroxybenzene		
Oral	LD50	375 mg/kg (rat) (OECD 401)	
Dermal	LD50	> 2,000 mg/kg (rab) (OECD 402)	

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic to	- Aquatic toxicity:	
1189-08-8	1189-08-8 1,3-butylglycol-dimethacrylate	
EC50/72 h	EC50/72 h 9.79 mg/l (Desmodesmus subspicatus) (OECD 201)	
123-31-9 1	123-31-9 1,4-dihydroxybenzene	
LC50/96 h	0.638 mg/l (Oncorhynchus mykiss)	
EC50/48 h	0.061 mg/l (Daphnia magna)	
EC50/72 h	0.33 mg/l (Pseudokirchneriella subcapitata)	

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark: Harmful to fish

(Contd. on page 8)

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 7)

- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- **Recommendation** Disposal must be made according to official regulations.

- European waste catalogue		
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number - ADR, IMDG, IATA	UN3082
- 14.2 UN proper shipping name - ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tricyclodecane-Dimethanol-Dimethacrylate, trimethylol propane
- IMDG	trimethacrylate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tricyclodecane-Dimethanol- Dimethacrylate, trimethylol propane trimethacrylate),
- IATA	MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tricyclodecane-Dimethanol- Dimethacrylate, trimethylol propane trimethacrylate)

- 14.3 Transport hazard class(es)
- ADR



- **Class** 9 (M6) Miscellaneous dangerous substances and articles.

(Contd. on page 9)

DEGEN

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

	(Contd. of page
- Label	9
- IMDG, IATA	
- Class - Label	9 Miscellaneous dangerous substances and articles.9
- 14.4 Packing group - ADR, IMDG, IATA	Ш
 - 14.5 Environmental hazards: - Marine pollutant: - Special marking (ADR): - Special marking (IATA): 	Product contains environmentally hazardous substances 1,4-dihydroxybenzene, Tricyclodecane-Dimethanol Dimethacrylate Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
- 14.6 Special precautions for user- Danger code (Kemler):- EMS Number:- Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
- 14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
- Transport/Additional information:	
- ADR - Limited quantities (LQ) - Excepted quantities (EQ) - Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRICYCLODECANE DIMETHANOL-DIMETHACRYLATE) TRIMETHYLOL PROPANE TRIMETHACRYLATE) 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

- DEGEN

Printing date 05.03.2018 Version number 3 Revision: 05.03.2018

Trade name: ergo 4211

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. E: Organic peroxides - Type E/F

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- * Data compared to the previous version altered.

DEGEN