

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: 4900

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Activator

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41- 58-272 0 272

- Further information obtainable from: Product safety department

- Department issuing MSDS: info@kisling.com

- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02 GHS07

- Signal word Danger

- Hazard-determining components of labelling:

propan-2-ol

- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- 2.3 Other hazards**- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****- 3.2 Mixtures****- Description:** Mixture of substances listed below with nonhazardous additions.**- Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	> 50 - ≤ 100%
CAS: 68084-48-0 EINECS: 268-439-2	copper (2+) neodecanoate Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411; Acute Tox. 4, H302	≥ 0.25 - < 2.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****- 4.1 Description of first aid measures****- General information:** Remove any clothing soiled by the product.**- After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: After contact with skin, wash with plenty of soap and water.**- After eye contact:**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting; seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**- 5.1 Extinguishing media****- Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

(Contd. on page 3)

CH-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 2)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Avoid contact with the eyes and skin.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
Fumes can combine with air to form an explosive mixture.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 10 for information on "stability and reactivity".
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Protect from heat and direct sunlight.
- **Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 3**
- **7.3 Specific end use(s)** No further relevant information available.

CH-EN

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

MAK (Switzerland)	Short-term value: 1000 mg/m ³ , 400 ppm Long-term value: 500 mg/m ³ , 200 ppm B SSc;
-------------------	--

- DNELs

67-63-0 propan-2-ol

Oral	Longterm System	26 mg/kg bw/day (General population)
Dermal	Longterm System	319 mg/kg bw/day (General population) 888 mg/kg bw/day (Worker)
Inhalative	Longterm System	89 mg/m ³ (General population) 500 mg/m ³ (Worker)

- PNECs

67-63-0 propan-2-ol

PNEC Freshwater	140.9 mg/l
PNEC Freshwater sed	552 mg/kg
PNEC Marinewater	140.9 mg/l
PNEC Soil	28 mg/kg
PNEC STP	2,251 mg/l
PNEC Marinewater sed	552 mg/kg

- Ingredients with biological limit values:

67-63-0 propan-2-ol

BAT (Switzerland)	25 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Biol. Parameter: Aceton
	25 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Biol. Parameter: Aceton

- **Additional information:** The lists valid during the making were used as basis.

- 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

filter A (EN 141)

- **Hand protection**

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

CH-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Chloropren Nitril II, Nr. 0717

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

Permeation time / penetration time: see above (material of gloves)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Safety glasses

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties**- General Information**

- Colour:	Blue-green
- Odour:	Alcohol-like
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	82 °C
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	13 °C
- Decomposition temperature:	Not determined.
- pH at 20 °C	7
- Viscosity:	
- Kinematic viscosity	Not determined.
- Dynamic at 20 °C:	10 mPas (Brookfield (2/100))
- Solubility	
- water:	Fully miscible.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Vapour pressure:	Not determined.
- Density and/or relative density	
- Density at 20 °C:	0.8 g/cm ³

(Contd. on page 6)

CH-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 5)

- Relative density	Not determined.
- Vapour density	Not determined.
- 9.2 Other information	
- Appearance:	
- Form:	Fluid
- Important information on protection of health and environment, and on safety.	
- Ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Change in condition	
- Softening point/range	
- Oxidising properties	Not determined.
- Evaporation rate	Not determined.
- Information with regard to physical hazard classes	
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	
Highly flammable liquid and vapour.	
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flammable gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
Protect from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

CH-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 6)

- LD/LC50 values relevant for classification:**67-63-0 propan-2-ol**

Oral	LD50	4,570 mg/kg (Rat, male/female)
Dermal	LD50	13,400 mg/kg (Rabbit)
Inhalative	LC50/4 h	30 mg/l (Rat, male/female)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

- **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause drowsiness or dizziness.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

No experimentally found toxicological data are available for this preparation.

May cause drowsiness or dizziness.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation** Disposal must be made according to official regulations.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

- **European waste catalogue**

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10: packaging containing residues of or contaminated by dangerous substances

(Contd. on page 8)

CH-EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 7)

- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number

- ADR, IMDG, IATA

UN1219

- 14.2 UN proper shipping name

- ADR

1219 ISOPROPANOL (ISOPROPYL ALCOHOL) solution

- IMDG, IATA

ISOPROPANOL (ISOPROPYL ALCOHOL) solution

- 14.3 Transport hazard class(es)

- ADR



- Class

3 (F1) Flammable liquids.

- Label

3

- IMDG, IATA



- Class

3 Flammable liquids.

- Label

3

- 14.4 Packing group

- ADR, IMDG, IATA

II

- 14.5 Environmental hazards:

Not applicable.

- 14.6 Special precautions for user

Warning: Flammable liquids.

- Hazard identification number (Kemler code):

33

- EMS Number:

F-E,S-D

- Stowage Category

B

- 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ)

1L

- Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

- Transport category

2

- Tunnel restriction code

D/E

- IMDG

- Limited quantities (LQ)

1L

- Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.04.2023

Version number 5 (replaces version 4)

Revision: 12.04.2023

Trade name: 4900

(Contd. of page 8)

- UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
SOLUTION, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- * Data compared to the previous version altered.

CH-EN