

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 1 of 14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 5100 liquid

UFI: VPC0-50JG-H007-1QFE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

#### Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Company name:	Kisling AG	
Street:	Motorenstrasse 102	
Place:	CH-8620 Wetzikon	
Telephone:	+41 58 272 0 272	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

#### Supplier

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

**1.4. Emergency telephone number:** 24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics

**Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006


### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 2 of 14

**Pictograms:**



**Hazard statements**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P273 Avoid release to the environment.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P391 Collect spillage.
- P403+P235 Store in a well-ventilated place. Keep cool.

**Labelling of packages where the contents do not exceed 125 ml**

**Signal word:** Danger

**Pictograms:**



**Hazard statements**

H304

**Precautionary statements**

P301+P310-P331

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Chemical characterization**

Mixture of substances listed below with nonhazardous components.

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics			50 - < 100 %
	927-510-4			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
99-97-8	N,N-dimethyl-p-toluidine			0.1 - < 1 %
	202-805-4	612-056-00-9	01-2119956633-31	
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H331 H311 H301 H373 H412			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 3 of 14

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-49-0	927-510-4	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics	50 - < 100 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >5840 mg/kg	
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	0.1 - < 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0.5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Never give anything by mouth to an unconscious person or a person with cramps.  
If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. In case of skin irritation, consult a physician.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Powder.

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.  
Danger of serious damage to health by prolonged exposure.  
Use appropriate respiratory protection.

### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.  
Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 4 of 14

#### General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid release to the environment. In use, may form flammable/explosive vapour-air mixture.  
Only use the material in places where open light, fire and other flammable sources can be kept away.  
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools.

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. When using do not eat, drink or smoke.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

#### Further information on handling

Keep only in the original container in a cool, well-ventilated place.  
Never use pressure to empty container. Do not allow to enter into surface water or drains.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Hints on joint storage

Do not store together with: ,

#### Further information on storage conditions

Follow the instructions for use on the label.  
15-30°C  
Keep container dry.  
Keep away from sources of ignition - No smoking. Protect from direct sunlight.

### 7.3. Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 5 of 14

#### DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics		
Worker DNEL, long-term	inhalation	systemic	2085 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	447 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	149 mg/kg bw/day
99-97-8	N,N-dimethyl-p-toluidine		
Worker DNEL, long-term	inhalation	systemic	0,128 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,624 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,336 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,223 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,02 mg/kg bw/day

#### PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
99-97-8	N,N-dimethyl-p-toluidine	
Freshwater	0,153 mg/l	
Freshwater (intermittent releases)	0,153 mg/l	
Marine water	0,015 mg/l	
Freshwater sediment	45,378 mg/kg	
Marine sediment	45,378 mg/kg	
Micro-organisms in sewage treatment plants (STP)	4,286 mg/l	
Soil	18,677 mg/kg	

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Hand protection EN ISO 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 6 of 14

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

(Natural fibres (e.g. cotton)/ heat-resistant synthetic fibres)

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		89 - 97 °C
Flammability:		not applicable
Lower explosion limits:		0,6 vol. %
Upper explosion limits:		7 vol. %
Flash point:		< 0 °C
Auto-ignition temperature:		> 200 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		practically insoluble
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		60 hPa
(at 20 °C)		
Density:		0.70 g/cm <sup>3</sup>
Relative density:		not determined
Relative vapour density:		not determined

### 9.2. Other information

#### Information with regard to physical hazard classes

##### Explosive properties

The product is not: Explosive.

##### Oxidizing properties

not determined

#### Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 7 of 14

Viscosity / dynamic:

not determined

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

No further relevant information available.

##### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

##### 10.3. Possibility of hazardous reactions

##### 10.4. Conditions to avoid

In case of warming: Thermal decomposition.

##### 10.5. Incompatible materials

No further relevant information available.

##### 10.6. Hazardous decomposition products

Carbon monoxide

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### Toxicokinetics, metabolism and distribution

No data available

###### Acute toxicity

Based on available data, the classification criteria are not met.

###### ATEmix calculated

ATE (oral) 12500 mg/kg; ATE (dermal) 37500 mg/kg; ATE (inhalation vapour) 375.0 mg/l; ATE (inhalation dust/mist) 62.50 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics				
	oral	LD50 >5840 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
99-97-8	N,N-dimethyl-p-toluidine				
	oral	ATE 100 mg/kg			
	dermal	ATE 300 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0.5 mg/l			

###### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 8 of 14

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May cause respiratory irritation. Potential hazards:

The product is skin resorptive.

Irritating to eyes. (reversible.)

#### 11.2. Information on other hazards

##### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 9 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
99-97-8	N,N-dimethyl-p-toluidine					
	Acute fish toxicity	LC50 52,8 mg/l	96 h	Pimephales promelas	REACH Registration Dossier	other: Standard test procedure ASTM, 198
	Acute algae toxicity	ErC50 23,69 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 15,27 mg/l	48 h	Daphnia magna	REACH Registration Dossier	other: Modeling database
	Acute bacteria toxicity	EC50 100 mg/l ( )	3 h	WoE 2. domestic activated sludge, WoE 3. Pseudomon	REACH Registration Dossier	other: as mentioned below

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
99-97-8	N,N-dimethyl-p-toluidine	2,81

#### BCF

CAS No	Chemical name	BCF	Species	Source
99-97-8	N,N-dimethyl-p-toluidine	33	Fish	REACH Registration D

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 10 of 14

#### Further information

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains.

##### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

##### Contaminated packaging

Completely emptied packages can be recycled.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number or ID number:</b>	UN 1206
<b>14.2. UN proper shipping name:</b>	HEPTANES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

#### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 1206
<b>14.2. UN proper shipping name:</b>	HEPTANES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 11 of 14



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Marine pollutant: P  
 Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1206  
**14.2. UN proper shipping name:** HEPTANES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No information available.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):  
 Entry 3, Entry 29, Entry 40

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 12 of 14

Directive 2010/75/EU on industrial emissions:

100 % (700 g/l)

Information according to Directive 2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

Additional information:

P5c

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 13 of 14

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid  
 Acute Tox: Acute toxicity  
 Asp. Tox: Aspiration hazard  
 Skin Irrit: Skin irritation  
 STOT SE: Specific target organ toxicity - single exposure  
 STOT RE: Specific target organ toxicity - repeated exposure  
 Aquatic Chronic: Chronic aquatic hazard  
 CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 CAS: Chemical Abstracts Service  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 5100 liquid

Revision date: 02.05.2024

Product code: 5100F

Page 14 of 14

H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*