



Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 5150 flüssig

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Primer

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: ergo@kisling.com

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life. Aquatic Acute 1

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms









GHS02

GHS07

GHS08 GHS09

- Signal word Danger
- Hazard-determining components of labelling:

heptane

- Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 1)

P261 Avoid breathing mist/vapours/spray.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P310

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

- Labelling of packages where the contents do not exceed 125 ml

- Hazard pictograms









GHS07 GHS02

GHS08

- Signal word Danger
- Hazard-determining components of labelling:

heptane

- Hazard statements

H304 May be fatal if swallowed and enters airways.

- Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT:** Not applicable. - **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	> 50 - ≤ 100%
CAS: 111-84-2 EINECS: 203-913-4	nonane Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥ 0.25 - ≤ 1%
CAS: 61788-93-0 EINECS: 263-020-0	Amines, coco alkyldimethyl Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥ 0.025 - < 0.25%

⁻ Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

(Contd. on page 3)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 2)

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- Information for doctor:

If swallowed or in the event of vomiting, risk of product entering the lungs. This may cause chemical pneumonia or suffucation.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

- 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

Fumes can combine with air to form an explosive mixture.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

CHGEN

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 3)

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 3
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- -8.1 Control parameters

	- 6.1 Control parameters		
- Ingredien	- Ingredients with limit values that require monitoring at the workplace:		
142-82-5 l	142-82-5 heptane		
MAK (Sw	MAK (Switzerland) Short-term value: 1600 mg/m³, 400 ppm		
	Long-term value: 1600 mg/m³, 400 ppm		
111-84-2 1	111-84-2 nonane		
MAK (Sw	MAK (Switzerland) Long-term value: 1050 mg/m³, 200 ppm		
- DNELs	- DNELs		
142-82-5 I	142-82-5 heptane		
Oral	Longterm System	149 mg/kg bw/day (General population)	
Dermal	Longterm System	149 mg/kg bw/day (General population)	
	300 mg/kg bw/day (Worker)		
Inhalative Longterm System 447 mg/m³ (General population)			
		2,085 mg/m³ (Worker)	

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

(Contd. on page 5)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 4)

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Chloropren Nitril I, Nr. 0727

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Chloropren Nitril II, Nr. 0717

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Permeation time / penetration time: see above (material of gloves)

- **Eve protection:** Safety glasses

- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and cl - General Information	nemical properties
- Appearance:	· ·
Form:	Fluid
Colour:	Colourless
- Odour:	Petrol-like
- Odour threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	Undetermined.
- Flash point:	-10 °C (DIN 55213)
- Flammability (solid, gas):	Not applicable.
- Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
	(Contd. on page 6)

(Contd. on page 6)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

	(Contd. of pa	age 5)
- Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
- Oxidising properties	Not determined.	
- Vapour pressure:	Not determined.	
- Density at 20 °C:	0.68 g/cm^3	
- Relative density	Not determined.	
- Vapour density	Not determined.	
- Evaporation rate	Not determined.	
- Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
- Partition coefficient: n-octanol/water:	Not determined.	
- Viscosity:		
Dynamic at 20 °C:	<20 mPas	
Kinematic:	Not determined.	
- 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

May cause drowsiness or dizziness.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

CHGEN

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 6)

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark: Very toxic for fish
- Additional ecological information:
- General notes:

Also very poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- **Recommendation** Disposal must be made according to official regulations.

- European waste catalogue		
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 01 00	wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals	
07 01 04*	other organic solvents, washing liquids and mother liquors	
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 07 00	07 07 00 wastes from the MFSU of fine chemicals and chemical products not otherwise specified	
07 07 04*	other organic solvents, washing liquids and mother liquors	

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number - ADR, IMDG, IATA	UN1206
- 14.2 UN proper shipping name - ADR	1206 HEPTANES solution, ENVIRONMENTALLY HAZARDOUS
- IMDG - IATA	HEPTANES solution, MARINE POLLUTANT HEPTANES solution

- 14.3 Transport hazard class(es)
- ADR





- Class 3 (F1) Flammable liquids.

(Contd. on page 8)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

	(Contd. of page 7
- Label	3
- IMDG	
- Class	3 Flammable liquids.
- Label 	3
- IATA	
- Class - Label	3 Flammable liquids.
- 14.4 Packing group - ADR, IMDG, IATA	II
- 14.5 Environmental hazards:- Marine pollutant:- Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
- 14.6 Special precautions for user- Hazard identification number (Kemler code):- EMS Number:- Stowage Category	Warning: Flammable liquids. 33 F-E,S-D B
- 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.
- Transport/Additional information:	
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- Transport category- Tunnel restriction code	2 D/E
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1206 HEPTANES SOLUTION, 3, II ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 9)

Printing date 30.03.2020 Version number 2 Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 8)

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

- * Data compared to the previous version altered.

CHGEN