

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: **ergo 5150 flüssig**

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Primer

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG
Motorenstrasse 102
CH-8620 Wetzikon
Tel: +41- 58-272 0 272

- Only representative (REACH) and importer (CLP):

Kisling Deutschland GmbH
Bürgermeister-Seidl-Strasse 2
D-82515 Wolfratshausen
Tel +49 8171 99982 30
Fax +49 322 224 299 35

- Further information obtainable from: ergo@kisling.com

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number: +49-700-24 112 112 (KAR)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02 GHS07 GHS08 GHS09

- Signal word Danger

- Hazard-determining components of labelling:

heptane

- Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 1)

H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing mist/vapours/spray.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

- Labelling of packages where the contents do not exceed 125 ml**- Hazard pictograms**

GHS02 GHS07 GHS08 GHS09

- Signal word Danger**- Hazard-determining components of labelling:**

heptane

- Hazard statements

H304 May be fatal if swallowed and enters airways.

- Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

- 2.3 Other hazards**- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****- 3.2 Mixtures****- Description:** Mixture of substances listed below with nonhazardous additions.**- Dangerous components:**

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	> 50 - ≤ 100%
CAS: 111-84-2 EINECS: 203-913-4	nonane Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥ 0.25 - ≤ 1%
CAS: 61788-93-0 EINECS: 263-020-0	Amines, coco alkyldimethyl Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	≥ 0.025 - < 0.25%

- Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****- 4.1 Description of first aid measures****- General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 2)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
After contact with skin, wash immediately with plenty of soap and water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Information for doctor:**
If swallowed or in the event of vomiting, risk of product entering the lungs. This may cause chemical pneumonia or suffocation.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Avoid contact with the eyes and skin.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
Fumes can combine with air to form an explosive mixture.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 3)

See Section 10 for information on "stability and reactivity".
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle.

- **Information about storage in one common storage facility:** Store away from foodstuffs.

- Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

- **Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers):** 3

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

142-82-5 heptane

IOELV (European Union)	Long-term value: 2085 mg/m ³ , 500 ppm
MAK (Germany)	Long-term value: 2100 mg/m ³ , 500 ppm vgl. Abschn. XII

- DNELs

142-82-5 heptane

Oral	Longterm System	149 mg/kg bw/day (General population)
Dermal	Longterm System	149 mg/kg bw/day (General population)
		300 mg/kg bw/day (Worker)
Inhalative	Longterm System	447 mg/m ³ (General population)
		2,085 mg/m ³ (Worker)

- **Additional information:** The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 5)

- DEGEN -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 4)

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Chloropren Nitril I, Nr. 0727

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Chloropren Nitril II, Nr. 0717

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Permeation time / penetration time: see above (material of gloves)

- Eye protection: Safety glasses

- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid
Colour: Colourless

- Odour: Petrol-like

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

- Flash point: -10 °C (DIN 55213)

- Flammability (solid, gas): Not applicable.

- Decomposition temperature: Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 5)

- Auto-ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Oxidising properties	Not determined.
- Vapour pressure:	Not determined.
- Density at 20 °C:	0.68 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
Dynamic at 20 °C:	<20 mPas
Kinematic:	Not determined.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
No experimentally found toxicological data are available for this preparation.
May cause drowsiness or dizziness.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 6)

- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Also very poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.
Do not allow product to reach ground water, water course or undiluted sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.

- European waste catalogue

07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES
07 01 00	wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals
07 01 04*	other organic solvents, washing liquids and mother liquors
07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES
07 07 00	wastes from the MFSU of fine chemicals and chemical products not otherwise specified
07 07 04*	other organic solvents, washing liquids and mother liquors

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---|
| - 14.1 UN-Number | UN1206 |
| - ADR, IMDG, IATA | |
| - 14.2 UN proper shipping name | 1206 HEPTANES solution, ENVIRONMENTALLY HAZARDOUS |
| - ADR | |
| - IMDG | HEPTANES solution, MARINE POLLUTANT |
| - IATA | HEPTANES solution |

(Contd. on page 8)

- DEGEN -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 7)

- 14.3 Transport hazard class(es)**- ADR**

- Class 3 (F1) Flammable liquids.
- Label 3

- IMDG

- Class 3 Flammable liquids.
- Label 3

- IATA

- Class 3 Flammable liquids.
- Label 3

- 14.4 Packing group

- ADR, IMDG, IATA II

- 14.5 Environmental hazards:

- Marine pollutant: Symbol (fish and tree)
- Special marking (ADR): Symbol (fish and tree)

- 14.6 Special precautions for user

Warning: Flammable liquids.

- Hazard identification number (Kemler code): 33

- EMS Number: F-E,S-D

- Stowage Category B

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

- Transport/Additional information:**- ADR**

- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- Transport category 2

- Tunnel restriction code D/E

- IMDG

- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

-DEGEN-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version number 2

Revision: 30.03.2020

Trade name: ergo 5150 flüssig

(Contd. of page 8)

- UN "Model Regulation":	UN 1206 HEPTANES SOLUTION, 3, II, ENVIRONMENTALLY HAZARDOUS
--------------------------	--

* **SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity - oral – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

- * **Data compared to the previous version altered.**

- DEGEN -