

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

5370 Instant adhesive 2K repair - 5368 resin

Further trade names

Product 5370: 5368 resin + 5369 Hardener

Product group:

UFI: 0VUF-30W7-100X-QQ09

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants resin

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail (Contact person): compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail Contact person: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

ethyl 2-cyanoacrylate

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 2 of 12

Pictograms:



Hazard statements

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Precautionary statements

- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves and eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7085-85-0	ethyl 2-cyanoacrylate			50 - < 100 %
	230-391-5	607-236-00-9	01-2119527766-29	
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			
123-31-9	hydroquinone			< 0.1 %
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H351 H341 H302 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7085-85-0	230-391-5	ethyl 2-cyanoacrylate	50 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg STOT SE 3; H335: >= 10 - 100		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
123-31-9	204-617-8	hydroquinone	< 0.1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 375 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Damage can be caused through mechanical influence of the product (eg. sticking).
Do not pull apart bonded skin areas. They can be carefully separated with a blunt object after soaking in warm soapy water. Cyanoacrylates release heat as they cure. In rare cases, a large amount of product can produce enough heat to cause burns. After the adhesive has been removed from the skin, the burns should be treated as ordinary burns. If the lips are accidentally glued together, apply warm water to the lips, ensure maximum wetting with saliva, and apply pressure from inside the mouth. Peel or roll the lips until they come apart. Do not try to pull the lips apart with opposing movements.

After contact with eyes

If the eye is so glued that it cannot be opened, loosen the eyelashes with warm water by applying a wet cotton pad. Cyanoacrylate hardens on the eye protein, causing tear flow. This helps to dissolve the adhesive again. Keep the eye covered until the adhesive is completely detached, which usually takes 1 to 3 days. Do not force the eye open. Seek medical attention if solid particles of cyanoacrylate are trapped under the lid and cause injury through friction.

After ingestion

Ensure that the airways are clear. The product polymerizes immediately in the mouth, making it almost impossible to swallow. Saliva slowly separates the hardened product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

Irritation to respiratory tract, Cough, Dyspnoea
Causes eye irritation. Conjunctival redness.
Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Powder.

Unsuitable extinguishing media

No information available.

5.2. Special hazards arising from the substance or mixture

Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 4 of 12

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Wash with plenty of water. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothes. Ventilate affected area.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations.

Hints on joint storage

none

Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
7085-85-0	ethyl 2-cyanoacrylate	inhalation	systemic	9.25 mg/m ³
Worker DNEL, long-term				

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 5 of 12

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
	DNEL type			
	Worker DNEL, acute	inhalation	systemic	9.25 mg/m ³
	Worker DNEL, long-term	inhalation	local	9.25 mg/m ³
	Worker DNEL, acute	inhalation	local	9.25 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	9.25 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	9.25 mg/m ³
	Consumer DNEL, long-term	inhalation	local	9.25 mg/m ³
	Consumer DNEL, acute	inhalation	local	9.25 mg/m ³
123-31-9	hydroquinone			
	Worker DNEL, long-term	inhalation	systemic	2.1 mg/m ³
	Worker DNEL, long-term	dermal	systemic	3.33 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	1.05 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	1.66 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0.6 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
	Environmental compartment	
123-31-9	hydroquinone	
	Freshwater	0.00057 mg/l
	Freshwater (intermittent releases)	0.00134 mg/l
	Marine water	0.000057 mg/l
	Freshwater sediment	0.0049 mg/kg
	Marine sediment	0.00049 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0.71 mg/l
	Soil	0.00064 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material:

Thickness of the glove material >0,4 mm

> 480 min

See information supplied by the manufacturer.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 6 of 12

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	169-187 °C
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	103 °C
Auto-ignition temperature:	421 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	not determined
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	1.04 g/cm ³
Relative density:	not determined
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties
not determined

Oxidizing properties
not determined

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Water, Amines, , Alcohol

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 7 of 12

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7085-85-0	ethyl 2-cyanoacrylate				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1973)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1973)	OECD Guideline 402
123-31-9	hydroquinone				
	oral	LD50 > 375 mg/kg	Rat	Food Chem Toxicol 45, 70 - 78 (2007)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Food Chem Toxicol 45, 70 - 78 (2007)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 8 of 12

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
123-31-9	hydroquinone					
	Acute fish toxicity	LC50 0.638 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 0.33 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 0.134 mg/l	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202
	Fish toxicity	NOEC >= 0.1 mg/l	32 d	Pimephales promelas	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC 0.006 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

No data available

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
7085-85-0	ethyl 2-cyanoacrylate			
	OECD 301D	57%		

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
7085-85-0	ethyl 2-cyanoacrylate	0.776
123-31-9	hydroquinone	0.59

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 9 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3334
14.2. UN proper shipping name: AVIATION REGULATED LIQUID, N.O.S. (ethyl-2-cyanoacrylate; 1,4-dihydroxybenzene; hydroquinone; quinol)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 10 of 12



Special Provisions:	A27
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

Other applicable information (air transport)

A27: Primary packs containing not more than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

(EU) EINECS/ELINCS/NLP: yes

(RC) TCSI: yes

(NZ) NZIoC: yes

(USA) TSCA: yes

(CDN) DSL: yes

(ROK) KECI/ECL: yes

(RP) PICCS: yes

(JP) MITI: yes

(CHN) IECSC: yes

(AUS) AIIC: yes

(CDN) NDSL: no

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 11 of 12

Changes

This data sheet contains changes from the previous version in section(s): 14.

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
 Skin Irrit. 2: Skin irritation, hazard category 2
 Eye Dam. 1: Serious eye damage, hazard category 1
 Eye Irrit. 2: Eye irritation, hazard category 2
 Skin Sens. 1: Skin sensitisation, hazard category 1
 Muta. 2: Germ cell mutagenicity, hazard category 2
 Carc. 2: Carcinogenicity, hazard category 2
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
 Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
 H315 Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5370 Instant adhesive 2K repair - 5368 resin

Revision: 04.03.2026

Product code: 5368

Page 12 of 12

Relevant H and EUH statements (number and full text)

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)