



according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 7348 - Component A 7350

UFI: 5YG0-G02A-T00Y-3SKN

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants Resins (prepolymers)

# Uses advised against

No information available.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG

Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272

E-mail: customerservice@kisling.com

Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH

Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61

E-mail: customerservice@kisling.com

Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143

E-mail: compliance@kisling.com

Internet: www.kisling.com

1.4. Emergency telephone 24 hr. emergency phone number +1 872 5888271 (KAR)

number: Medicines & Poisons Info Office +356 2545 6508

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

# Regulation (EC) No 1272/2008

# Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Signal word: Warning



according to Regulation (EC) No 1907/2006

# Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 2 of 12

### Pictograms:





#### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

## Special labelling of certain mixtures

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

# Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:





#### **Hazard statements**

H317

# **Precautionary statements**

P261-P280-P302+P352-P333+P313

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### **Chemical characterization**

Mixture of substances listed below with nonhazardous components.

## **Hazardous components**

CAS No	Chemical name	Chemical name						
	EC No	EC No Index No REACH No						
	Classification (Regulati	Classification (Regulation (EC) No 1272/2008)						
1675-54-3	bis-[4-(2,3-epoxipropox	bis-[4-(2,3-epoxipropoxi)phenyl]propane						
	216-823-5	216-823-5 603-073-00-2						
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411							

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	imits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	50 - < 100 %
	dermal: LD50 = Irrit. 2; H319: >=	: 23000 mg/kg; oral: LD50 = 19800 mg/kg	



Kisling AG

according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 3 of 12

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

Take off immediately all contaminated clothing.

#### After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder, Foam.

### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Remove all sources of ignition.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.





according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 4 of 12

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

## Advice on protection against fire and explosion

Take precautionary measures against static discharges.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

### Further information on handling

Keep only in the original container in a cool, well-ventilated place.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

### Hints on joint storage

none

#### Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

### 7.3. Specific end use(s)

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

## **DNEL/DMEL values**

CAS No	Name of agent						
DNEL type		Exposure route	Effect	Value			
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane						
Worker DNEL,	long-term	inhalation	systemic	4,93 mg/m³			
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day			
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³			
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day			
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day			
Consumer DN	EL, acute	oral	systemic	0,5 mg/kg bw/day			



according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 5 of 12

#### **PNEC values**

CAS No	Name of agent					
Environment	mental compartment Value					
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane					
Freshwater	0,006 mg/l					
Freshwater (intermittent releases) 0,018 mg/l						
Marine water	0,001 mg/l					
Freshwater sediment						
Marine sediment 0,034 mg/						
Secondary poisoning 11 mg/						
Micro-organisms in sewage treatment plants (STP)  10 mg/l						
Soil		0,065 mg/kg				

#### 8.2. Exposure controls





### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: goggles.

# **Hand protection**

Hand protection EN ISO 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Paste solid
Colour: white
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

>300 °C

boiling range:



according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 6 of 12

Flammability: not applicable Lower explosion limits: not determined not determined Upper explosion limits: Flash point: >100 °C Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined not determined Viscosity / kinematic: Water solubility: not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative density:

Relative vapour density:

not determined

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties not determined

# Other safety characteristics

Evaporation rate: not determined Solid content: not determined Viscosity / dynamic: 20000 - 25000 mPa·s

(at 25 °C)

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## 10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.5. Incompatible materials

No further relevant information available.

### 10.6. Hazardous decomposition products

No further relevant information available.

### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

No data available

#### **Acute toxicity**

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 7 of 12

## **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name									
	Exposure route	Dose	Source	Method						
1675-54-3	bis-[4-(2,3-epoxipropoxi)p	pis-[4-(2,3-epoxipropoxi)phenyl]propane								
	oral	LD50 mg/kg	19800	Rabbit	` ,	Rabbits were orally gavaged with test ma				
	dermal	LD50 mg/kg	23000	Rabbit	Pre-supplier/manufact urer					

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxi)phenyl]propane)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Specific effects in experiment on an animal

No data available

## Additional information on tests

No data available

## **Practical experience**

May be harmful if swallowed, in contact with skin or if inhaled.

# 11.2. Information on other hazards

## **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name									
	Aquatic toxicity	quatic toxicity Dose [h]   [d] Species Source Method								
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane									
	Acute algae toxicity	ErC50 > 100 mg/l		'	, ,	OECD Guideline 201				

# 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available



according to Regulation (EC) No 1907/2006

# Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 8 of 12

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	>= 2,64

### **BCF**

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-	31		Study report (2010)
	(2,3-epoxipropoxi)phenyl]propane			

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

#### List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in  $08\ 04\ 09$ 

### List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants other than those mentioned in 08 04 09

# Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

q

(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):



according to Regulation (EC) No 1907/2006

# Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 9 of 12

14.4. Packing group:

Hazard label:

Ш

Classification code:

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

9

Ш

Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3077

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

III 9

9



Special Provisions: 274 335 966 967 969

Limited quantity: 5 kg
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(4,4'-Isopropylidenediphen

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

Ш

Special Provisions: A97 A158 A179 A197 A215



according to Regulation (EC) No 1907/2006

Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 10 of 12

Limited quantity Passenger: 30 kg G
Passenger LQ: Y956
Excepted quantity: E1

IATA-packing instructions - Passenger:956IATA-max. quantity - Passenger:400 kgIATA-packing instructions - Cargo:956IATA-max. quantity - Cargo:400 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: 4,4'-Isopropylidenediphen

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

**SECTION 15: Regulatory information** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information** 



according to Regulation (EC) No 1907/2006

## Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 11 of 12

## Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules
MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

## Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.





according to Regulation (EC) No 1907/2006

# Kisling - 7348 - Component A 7350

Revision date: 08.03.2024 Product code: 7348 Page 12 of 12

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11,	110	K+D

LCS: Life cycle stages
PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use PROC: Process categories AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)