

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 7418 - Component A 7420

UFI: Y2J0-201G-T00E-Q75G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006


Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 2 of 12

Pictograms:



Hazard statements

- H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.


Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H317

Precautionary statements

P261-P280-P333+P313-P362+P364

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			50 - < 100 %
	216-823-5	603-073-00-2		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)			15 - < 30 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxypropoxy)phenyl]propane	50 - < 100 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
25068-38-6		4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)	15 - < 30 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

No information available.

5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 4 of 12

General advice

Provide adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special handling advices are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

none

Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 5 of 12

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m³
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,5 mg/kg bw/day

PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater	0,006 mg/l	
Freshwater (intermittent releases)	0,018 mg/l	
Marine water	0,001 mg/l	
Freshwater sediment	0,341 mg/kg	
Marine sediment	0,034 mg/kg	
Secondary poisoning	11 mg/kg	
Micro-organisms in sewage treatment plants (STP)	10 mg/l	
Soil	0,065 mg/kg	

8.2. Exposure controls



Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing. Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	light yellow
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	not determined	not applicable
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	>100 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	1.17 g/cm ³	
Relative density:	not determined	
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. not explosive.

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate: not determined

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

No further relevant information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 7 of 12

10.6. Hazardous decomposition products

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane				
	oral	LD50 mg/kg	19800	Rabbit	Publication (1958)
	dermal	LD50 mg/kg	23000	Rabbit	Pre-supplier/manufact urer
25068-38-6	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000)				
	oral	LD50 mg/kg	>2000	Rat	Pre-supplier/manufact urer
	dermal	LD50 mg/kg	>2000	Rabbit	Pre-supplier/manufact urer

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxy)phenyl]propane; 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane (average molecular weight 700-1000))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 8 of 12

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	Study report (2007)	OECD Guideline 201

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	>= 2,64

BCF

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	31		Study report (2010)

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 9 of 12

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):


9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(4,4'-Isopropylidenediphen)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 10 of 12

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Special Provisions:

274 335 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(4,4'-Isopropylidenediphen)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Special Provisions:

A97 A158 A197 A215

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450 L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

4,4'-Isopropylidenediphen

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU
(SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420

Revision date: 14.09.2023

Product code: 7418

Page 11 of 12

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).
 Skin Irrit: Skin irritation
 Eye Irrit: Eye irritation
 Skin Sens: Skin sensitisation
 Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7418 - Component A 7420		
Revision date: 14.09.2023	Product code: 7418	Page 12 of 12

- H317

May cause an allergic skin reaction.
- H319

Causes serious eye irritation.
- H411

Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

- LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions
- SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)