

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

7490 Epoxy adhesive - 7489 hardener

Further trade names

Product 7490: 7438 resin + 7489 Hardener

Product group:

UFI: DYQN-M0V6-P00K-QRY4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants Hardener

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail (Contact person): compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail Contact person: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Corr. 1C; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia
2-Propenenitrile, polymer with 1,3-butadiene,
1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 2 of 14

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
 1,3-Cyclohexanedimethanamine
 Amines, polyethylenepoly-, triethylenetetramine fraction

Signal word: Danger

Pictograms:



Hazard statements

- H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P260 Do not breathe Vapour.
 P280 Wear protective gloves and eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

Special labelling

The synthetic polymer microparticles supplied are subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council (contains 1 - 10% Polyamide).

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	30 - < 50 %
	618-561-0	01-2119557899-12
	Skin Corr. 1C, Eye Dam. 1, Aquatic Chronic 3; H314 H318 H412	
68683-29-4	2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	15 - < 30 %
	614-706-7	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	15 - < 30 %
	500-191-5	01-2119972320-44
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1A; H315 H319 H317	
2579-20-6	1,3-Cyclohexanedimethanamine	5 - < 15 %
	219-941-5	01-2119543741-41
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, Aquatic Chronic 3; H312 H302 H314 H318 H412	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener	
Revision: 27.01.2026	Product code: 7489
Page 3 of 14	

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction			1 - < 5 %
	292-588-2		01-2119487919-13	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H312 H302 H314 H318 H317 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
9046-10-0	618-561-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	30 - < 50 %
	dermal: LD50 = 2979,7 mg/kg; oral: LD50 = 2885,3 mg/kg		
68683-29-4	614-706-7	2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	15 - < 30 %
	dermal: LD50 = 3000 mg/kg; oral: LD50 = 15400 mg/kg		
68082-29-1	500-191-5	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	15 - < 30 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
2579-20-6	219-941-5	1,3-Cyclohexanedimethanamine	5 - < 15 %
	dermal: ATE = 1100 mg/kg; oral: LD50 = > 300 - ca. 2000 mg/kg		
90640-67-8	292-588-2	Amines, polyethylenepoly-, triethylenetetramine fraction	1 - < 5 %
	dermal: LD50 = 1465.4 mg/kg; oral: LD50 = 1861.9 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

May cause respiratory irritation. Dyspnoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 4 of 14

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

Do not wash equipment or storage containers.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
DNEL type				

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 5 of 14

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia			
Worker DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	5,29 mg/m ³
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine			
Worker DNEL, long-term		inhalation	systemic	0.952 mg/m ³
Worker DNEL, long-term		dermal	systemic	0.272 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0.169 mg/m ³
Consumer DNEL, long-term		oral	systemic	0.0972 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0.0972 mg/kg bw/day
2579-20-6	1,3-Cyclohexanedimethanamine			
Worker DNEL, long-term		dermal	systemic	0.1 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	25.2 mg/kg bw/day
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction			
Worker DNEL, long-term		inhalation	systemic	0.54 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0.096 mg/m ³
Consumer DNEL, long-term		oral	systemic	0.14 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	
Freshwater		0,015 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,014 mg/l
Freshwater sediment		0,132 mg/kg
Marine sediment		0,125 mg/kg
Secondary poisoning		6,93 mg/kg
Micro-organisms in sewage treatment plants (STP)		7,5 mg/l
Soil		0,018 mg/kg
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	
Freshwater		0.004 mg/l
Freshwater (intermittent releases)		0.043 mg/l
Marine water		0 mg/l
Freshwater sediment		434.02 mg/kg
Marine sediment		43.4 mg/kg
Micro-organisms in sewage treatment plants (STP)		3.84 mg/l
Soil		86.78 mg/kg
2579-20-6	1,3-Cyclohexanedimethanamine	
Freshwater		0.033 mg/l
Freshwater (intermittent releases)		0.331 mg/l
Marine water		0.003 mg/l
Freshwater sediment		0.218 mg/kg
Marine sediment		0.022 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0.024 mg/kg
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	
Freshwater		0.027 mg/l
Freshwater (intermittent releases)		0.2 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 6 of 14

PNEC values

CAS No	Name of agent	Value
	Environmental compartment	
	Marine water	0.003 mg/l
	Freshwater sediment	8.572 mg/kg
	Marine sediment	0.857 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0.13 mg/l
	Soil	1.25 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn (EN ISO 374)
Breakthrough times and swelling properties of the material must be taken into consideration.
NBR (Nitrile rubber) 0,4 mm, Breakthrough time: 480 min

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: A/P2

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste / solid
Colour:	black
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>65 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined

OECD 114

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 7 of 14

Water solubility:	practically insoluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,07 g/cm ³
Relative density:	not determined
Relative vapour density:	not determined
Particle characteristics:	*)

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Viscosity / dynamic (at 25 °C):

not determined

Further Information

*)

Polyamide: < 5mm

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 8 of 14

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia				
	oral	LD50 2885,3 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 2979,7 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402
68683-29-4	2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated				
	oral	LD50 15400 mg/kg	Rat	Pre-supplier/manufacter	
	dermal	LD50 3000 mg/kg	Rabbit	Pre-supplier/manufacter	
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2012)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2013)	OECD Guideline 402
2579-20-6	1,3-Cyclohexanedimethanamine				
	oral	LD50 > 300 - ca. 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 423
	dermal	ATE 1100 mg/kg			
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction				
	oral	LD50 1861.9 mg/kg	Rat	Study report (1992)	other: EPA FR Vol.50, No. 188, September
	dermal	LD50 1465.4 mg/kg	Rabbit	Study report (1993)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage. (On basis of test data)

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated; Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine; Amines, polyethylenepoly-, triethylenetetramine fraction)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 9 of 14

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia					
	Acute fish toxicity	LC50 772,14 mg/l	96 h	Cyprinodon variegatus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 15 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 80 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Acute bacteria toxicity	EC50 750 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine					
	Acute fish toxicity	LC50 7.07 mg/l	96 h	Danio rerio	Study report (2013)	OECD Guideline 203
	Acute algae toxicity	ErC50 4.34 mg/l	72 h	Raphidocelis subcapitata	Study report (2013)	OECD Guideline 201
	Acute crustacea toxicity	EC50 7,07 mg/l	48 h		Pre-supplier/manufacturer	
	Acute bacteria toxicity	EC50 384 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (2012)	OECD Guideline 209
2579-20-6	1,3-Cyclohexanedimethanamine					
	Acute fish toxicity	LC50 130 mg/l	96 h	Leuciscus idus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 56.7 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 33.1 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EU Method C.2
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	activated sludge, domestic	REACH Registration Dossier	OECD Guideline 209

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction					
	Acute fish toxicity	LC50 330 mg/l	96 h	Pimephales promelas	REACH Registration Dossier	other: U.S EPA-TSCA, 40 CFR Part 797.14
	Acute algae toxicity	ErC50 20 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 31.1 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EU Method C.2
	Acute bacteria toxicity	EC50 800 mg/l ()		activated sludge, domestic	REACH Registration Dossier	other: EEC L133 1988 p 118-122

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	1,34
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	10.34
2579-20-6	1,3-Cyclohexanedimethanamine	0.69
90640-67-8	Amines, polyethylenepoly-, triethylenetetramine fraction	-2.9

BCF

CAS No	Chemical name	BCF	Species	Source
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	3,16		REACH Registration D
68082-29-1	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	77.4	no data	(2013)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of contents/container to industrial incineration plant.

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 11 of 14

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - used product

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

Do not wash with:
Transfer wash-downs in sealed containers.
Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Classification code: C8
Special Provisions: 274
Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
Hazard label: 8



Classification code: C8
Special Provisions: 274
Limited quantity: 5 kg
Excepted quantity: E1

Marine transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 12 of 14

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Special Provisions: 223 274
 Limited quantity: 5 kg
 Excepted quantity: E1
 EmS: F-A, S-B
 Segregation group: 18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3259
14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 5 kg
 Passenger LQ: Y845
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 860
 IATA-max. quantity - Passenger: 25 kg
 IATA-packing instructions - Cargo: 864
 IATA-max. quantity - Cargo: 100 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 78

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 13 of 14

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
(EU) EINECS/ELINCS/NLP:	yes
(RC) TCSI:	no
(NZ) NZIoC:	no
(USA) TSCA:	yes
(CDN) DSL:	no
(ROK) KECI/ECL:	unknown
(RP) PICCS:	unknown
(JP) MITI:	unknown
(CHN) IECSC:	yes
(AUS) AIIC:	unknown
(CDN) NDSL:	no

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1A: Skin corrosion, sub-category 1A
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Corr. 1C: Skin corrosion, sub-category 1C
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
Skin Sens. 1A: Skin sensitisation, hazard category 1A
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

7490 Epoxy adhesive - 7489 hardener

Revision: 27.01.2026

Product code: 7489

Page 14 of 14

IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1C; H314	On basis of test data
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)