



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 7600

UFI: CH1P-T0G8-P00H-4NN9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants, Resins (prepolymers)

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG

Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: info@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling Deutschland GmbH

Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 5096161
E-mail: info@kisling.com

Contact person: Isabel Winter Telephone: +49 7941 92054087

E-mail: info@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone 24 hr. emergency phone number +1 872 5888271 (KAR)

number: Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether

4-morpholinecarbaldehyde

Signal word: Warning





according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 2 of 14

Pictograms:





Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:





Hazard statements

H317

Precautionary statements

P261-P280-P333+P313-P362+P364

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.





according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 3 of 14

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)			
9003-36-5	Formaldehyde, oligomeric reaction	products with 1-chloro-2,3-epoxypro	pane and phenol	30 - < 50 %	
	500-006-8		01-2119454392-40		
	Skin Irrit. 2, Skin Sens. 1, Aquatic 0	Chronic 2; H315 H317 H411			
90529-77-4	1,2,3-Propanetriol, glycidyl ethers			1 - < 5 %	
	292-011-4				
	Skin Irrit. 2, Eye Irrit. 2; H315 H319				
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether			1 - < 5 %	
	219-371-7	603-072-00-7	01-2119494060-45		
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H332 H312 H302 H315 H318 H317 H412				
4394-85-8	4-morpholinecarbaldehyde			0.1 - < 1 %	
	224-518-3		01-2119987993-12		
	Skin Sens. 1B; H317	•			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
9003-36-5	500-006-8	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			
	dermal: LD50	dermal: LD50 = >2000 mg/kg; oral: LD50 = >10000 mg/kg			
2425-79-8	219-371-7	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether	1 - < 5 %		
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 1163 mg/kg			
4394-85-8	224-518-3	4-morpholinecarbaldehyde	0.1 - < 1 %		
	dermal: LD50 = > 18400 mg/kg; oral: LD50 = > 7314 mg/kg				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.



Kisling AG

according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 4 of 14

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

No information available.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special handling advices are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 5 of 14

Hints on joint storage

none

Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent				
DNEL type		Exposure route	Effect	Value	
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl eth	ner		·	
Worker DNEL,	long-term	inhalation	systemic	4,7 mg/m³	
Worker DNEL,	long-term	dermal	systemic	6,66 mg/kg bw/day	
Consumer DN	EL, long-term	inhalation	systemic	1,16 mg/m³	
Consumer DN	EL, long-term	dermal	systemic	3,33 mg/kg bw/day	
Consumer DN	Consumer DNEL, long-term		systemic	0,33 mg/kg bw/day	
4394-85-8	4-morpholinecarbaldehyde				
Worker DNEL,	long-term	inhalation	systemic	50,3 mg/m³	
Worker DNEL,	long-term	inhalation	local	13,3 mg/m³	
Worker DNEL,	Worker DNEL, long-term		systemic	11,7 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	8,93 mg/m³	
Consumer DNEL, long-term		inhalation	local	13,3 mg/m³	
Consumer DNEL, long-term		dermal	systemic	4,17 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	4,17 mg/kg bw/day	



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 6 of 14

PNEC values

· ···		
CAS No	Name of agent	
Environmenta	al compartment	Value
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether	
Freshwater		0,024 mg/l
Freshwater (i	ntermittent releases)	0,24 mg/l
Marine water		0,002 mg/l
Freshwater s	ediment	0,084 mg/kg
Marine sedim	nent	0,008 mg/kg
Secondary po	pisoning	0,028 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,003 mg/kg
4394-85-8	4-morpholinecarbaldehyde	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1,85 mg/kg
Marine sediment		0,185 mg/kg
Micro-organisms in sewage treatment plants (STP)		2000 mg/l
Soil		0,076 mg/kg

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 7 of 14

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: black
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flammability: not applicable Lower explosion limits: not determined Upper explosion limits: not determined >93 °C Flash point: Auto-ignition temperature: not determined Decomposition temperature: not determined not determined pH-Value: Viscosity / kinematic: not determined Water solubility: completely miscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative density:

Relative vapour density:

not determined
not determined
not determined
not determined
not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties not explosive.
Oxidizing properties not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Kisling AG

according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 8 of 14

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 84275 mg/kg; ATE (dermal) 79710 mg/kg; ATE (inhalation vapour) 797.1 mg/l; ATE (inhalation dust/mist) 108.7 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
9003-36-5	Formaldehyde, oligomeri	c reaction pr	oducts with	1-chloro-2,3-epoxypropan	e and phenol	
	oral	LD50 mg/kg	>10000	Rat	Pre-supplier/manufact urer	
	dermal	LD50 mg/kg	>2000	Rat	Pre-supplier/manufact urer	
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether					
	oral	LD50 mg/kg	1163	Rat	Study report (1988)	OECD Guideline 401
	dermal	ATE mg/kg	1100			
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1.5 mg/l			
4394-85-8	4-morpholinecarbaldehyo	de				
	oral	LD50 mg/kg	> 7314	Rat	Study report (1967)	OECD Guideline 401
	dermal	LD50 mg/kg	> 18400	Rabbit	Toxicology and Applied Pharmacology 28:	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Formaldehyde, oligomeric reaction products with

 $1-chloro-2, 3-epoxypropane\ and\ phenol;\ 1, 4-bis (2, 3\ epoxypropoxy) butane;\ butanediol diglycidyl\ ether;$

4-morpholinecarbaldehyde)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 9 of 14

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; bu	tanedioldigly	cidyl ethe	er		
	Acute algae toxicity	ErC50 mg/l	> 160	72 h	Raphidocelis subcapitata	Study report (2010)	OECD Guideline 201
4394-85-8	4-morpholinecarbaldehyd	e					
	Acute fish toxicity	LC50 mg/l	> 500	96 h	Leuciscus idus	Study report (1984)	other: German Industrial Standard DIN 38
	Acute algae toxicity	ErC50 mg/l	23880	72 h	Desmodesmus subspicatus	Study report (1990)	other: German Industrial Standard DIN 38
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna	Study report (1987)	other: Directive 79/831/EEC, Annex V, Pa
	Crustacea toxicity	NOEC	38 mg/l	21 d	Daphnia magna	QSAR Toolbox (2021)	- Principle of test: Estimation method f

12.2. Persistence and degradability

No data available

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether				
	OECD 301F	43%	28	Pre-supplier/manufactur	
				er	
	Not readily biodegradable (according to OECD criteria)				

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3,6
2425-79-8	1,4-bis(2,3 epoxypropoxy)butane; butanedioldiglycidyl ether	-0,269
4394-85-8	4-morpholinecarbaldehyde	-1,2

BCF

CAS No	Chemical name	BCF	Species	Source
4394-85-8	4-morpholinecarbaldehyde	< 1,9	Cyprinus carpio	Study report (1986)

12.4. Mobility in soil

No further relevant information available.



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 10 of 14

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances:

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Formaldehyde, oligomeric reaction products with

1-chloro-2,3-epoxypropane and phenol) 9

14.3. Transport hazard class(es):

14.4. Packing group: Hazard label:

III

9



Classification code:

M6 274 335 375 601

Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1



according to Regulation (EC) No 1907/2006

 Kisling - 7600

 Revision date: 11.07.2023
 Product code: 7600
 Page 11 of 14

Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Formaldehyde, oligomeric reaction products with

1-chloro-2,3-epoxypropane and phenol)

14.3. Transport hazard class(es):

14.4. Packing group:IIIHazard label:9



Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Formaldehyde, oligomeric reaction products with

1-chloro-2,3-epoxypropane and phenol)

14.3. Transport hazard class(es):

14.4. Packing group:IIIHazard label:9



9

Special Provisions: 274 335 969

Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Formaldehyde, oligomeric reaction products with

1-chloro-2,3-epoxypropane and phenol)

14.3. Transport hazard class(es):

14.4. Packing group:IIIHazard label:9



9

Special Provisions: A97 A158 A197 A215

Limited quantity Passenger: 30 kg G Passenger LQ: Y964 Excepted quantity: E1

IATA-packing instructions - Passenger:964IATA-max. quantity - Passenger:450 LIATA-packing instructions - Cargo:964IATA-max. quantity - Cargo:450 L





according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 12 of 14

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Formaldehyde, oligomeric reaction products with

1-chloro-2,3-epoxypropane and phenol

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

Kisling - 7600

Revision date: 11.07.2023 Product code: 7600 Page 13 of 14

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.

H317 May cause an allergic skin reaction.





according to Regulation (EC) No 1907/2006

Revision date: 11.07.2023 Product code: 7600 Page 14 of 14

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

LCS: Life cycle stages
PC: Product categories
ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use PROC: Process categories AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)