

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 7608 - Component A 7610

UFI: N62P-V00F-400G-ED9T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006


Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 2 of 12

Pictograms:



Hazard statements

- H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.


Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.
Restricted to professional users.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H317

Precautionary statements

P261-P280-P333+P313-P362+P364

2.3. Other hazards

Pressurised container: May burst if heated.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			50 - < 100 %
	216-823-5	603-073-00-2		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol			30 - < 50 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	50 - < 100 %
		dermal: LD50 = 23000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
9003-36-5	500-006-8	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	30 - < 50 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 4 of 12

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13 See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special handling advices are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

none

Further information on storage conditions

Store in a cool dry place. Protect from direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			
Worker DNEL, long-term		inhalation	systemic	4,93 mg/m³
Worker DNEL, long-term		dermal	systemic	0,75 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,0893 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,5 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 5 of 12

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	
Freshwater		0,006 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,341 mg/kg
Marine sediment		0,034 mg/kg
Secondary poisoning		11 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,065 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Suitable material: CR (polychloroprene, chloroprene rubber) NR (natural rubber, Natural latex) Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,45mm
= 480 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing. Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless / light yellow
Odour:	odourless
Odour threshold:	No data available

Melting point/freezing point:	No data available	Test method
Boiling point or initial boiling point and boiling range:	No data available	
Flammability:	not determined	not applicable
Lower explosion limits:	No data available	
Upper explosion limits:	No data available	
Flash point:	>200 °C	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 6 of 12

Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	No data available
Viscosity / kinematic:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	>3
Vapour pressure:	No data available
Density (at 20 °C):	1,17 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

- Explosive properties
 - No data available
- Oxidizing properties
 - No data available

Other safety characteristics

- Evaporation rate: not determined
- Viscosity / dynamic: 6000 - 8000 mPa·s
(at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures. Avoid high temperatures or direct sunlight.

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid high temperatures or direct sunlight.

10.5. Incompatible materials

Peroxides , alkalines , Radical former

10.6. Hazardous decomposition products

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 7 of 12

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	oral	LD50 mg/kg	19800	Rabbit	Publication (1958)	Rabbits were orally gavigated with test ma
	dermal	LD50 mg/kg	23000	Rabbit	Pre-supplier/manufact urer	
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol					
	oral	LD50 mg/kg	>5000	Rat	Pre-supplier/manufact urer	
	dermal	LD50 mg/kg	>2000	Rat	Pre-supplier/manufact urer	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxy)phenyl]propane; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards**Other information**

No information available.

Further information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane					
	Acute algae toxicity	ErC50 mg/l	> 100	72 h Raphidocelis subcapitata	Study report (2007)	OECD Guideline 201

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 8 of 12

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	>= 2,64
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3,6

BCF

CAS No	Chemical name	BCF	Species	Source
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane	31		Study report (2010)

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Send to a hazardous waste incinerator facility under observation of official regulations.

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 9 of 12

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin (Mn ≤ 700), reaction product: bisphenol-A-(epichlorhydrin))

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):


9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Special Provisions:

274 335 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 10 of 12



Special Provisions:	A97 A158 A197 A215
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: epoxy resin (Mn <= 700), reaction product: bisphenol-A-(epichlorhydrin)

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 49.9 % (583.83 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 7608 - Component A 7610

Revision date: 06.11.2023

Product code: 7608

Page 11 of 12

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).
 Skin Irrit: Skin irritation
 Eye Irrit: Eye irritation
 Skin Sens: Skin sensitisation
 Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 06.11.2023

Kisling - 7608 - Component A 7610

Product code: 7608

Page 12 of 12

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

- LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions
- SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)