

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

8901 PU Hardener

UFI: TWFF-04DV-U00J-KSDW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener (Crosslinker)

Uses advised against

Do not use for injecting or spraying.

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	customerservice@kisling.com	
Contact person:	Product Compliance	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H332
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Resp. Sens. 1; H334
Skin Sens. 1; H317
Carc. 2; H351
STOT SE 3; H335
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Diphenylmethane diisocyanate, isomers and homologs
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate
2,2'-methylenediphenyl diisocyanate; diphenylmethane-2,2'-diisocyanate

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 2 of 12

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves and eye protection/face protection.
P284	Wear respiratory protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.


Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H317-H334-H351

Precautionary statements

P280-P284-P304+P340-P342+P311

2.3. Other hazards

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
9016-87-9	Diphenylmethane diisocyanate, isomers and homologs	50 - < 100 %
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373	

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
9016-87-9		Diphenylmethane diisocyanate, isomers and homologs	50 - < 100 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = >9400 mg/kg; oral: LD50 = >10000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Wash with plenty of water/soap. Do not wash with:

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Powder.
In case of major fire and large quantities: Water spray jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Carbon monoxide, Carbon dioxide, Nitrogen oxides (NOx), Isocyanates, Hydrogen cyanide (hydrocyanic acid),
Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection. Emergency cooling must be provided for in case of a fire in the vicinity.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

No information available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 4 of 12

See protective measures under point 7 and 8.

For non-emergency personnel

No information available.

For emergency responders

No information available.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.

Dispose of contents/container to hazardous or special waste collection point.

Other information

The contaminated area should be cleaned up immediately with:

- 1 - a mixture of 95% water and 5% sodium carbonate & Soap
- 2 - 20ml anionic surfactants in aqueous solution, 700 ml Water, 350 ml Polyethylene glycol 400
- 3 - 30% Laundry detergents (monoethanolamine), 70 %

Add the decontaminant to the remnants and let stand for several days in a non-sealed container until no further reaction is observed. Once reaction is finished, close container and dispose of.

6.4. Reference to other sections

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Examination of lung function should be carried out on a regular basis on persons spraying this product.

Avoid release to the environment. In use, may form flammable/explosive vapour-air mixture.

Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools.

Handle and open container with care. Formation of: Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.

Never use pressure to empty container. Keep/Store only in original container.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. When using do not eat, drink or smoke.

Further information on handling

Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Hints on joint storage

Do not store together with: ,

Further information on storage conditions

Keep container dry.

Keep away from sources of ignition - No smoking. Protect from direct sunlight.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 5 of 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Examination of lung function should be carried out on a regular basis on persons spraying this product.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material: Butyl caoutchouc (butyl rubber)

See information supplied by the manufacturer.

Skin protection

(Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

Respiratory protection

During spraying wear suitable respiratory equipment.

Thermal hazards

No information available.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	brown
Odour:	earthy

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	> 300 °C
Flammability:	not applicable
Lower explosion limits:	not applicable
Upper explosion limits:	not determined
Flash point:	226 °C
Auto-ignition temperature:	> 500 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	Immiscible

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 6 of 12

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

<0,00001 hPa

(at 20 °C)

Vapour pressure:

<0,00005 hPa

(at 50 °C)

Density (at 20 °C):

1,24 g/cm³

Relative vapour density:

not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

not determined

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Pour point:

- 24 °C

Viscosity / dynamic:

296 mPa·s

(at 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

(Yes, slowly)

Formation of:

10.2. Chemical stability

Decomposition takes place from temperatures above: 200°C.

10.3. Possibility of hazardous reactions

,

Due to gaseous decomposition products, overpressure can occur in tightly sealed containers. Danger of bursting container.

10.4. Conditions to avoid

In case of warming: Thermal decomposition.

10.6. Hazardous decomposition products

Carbon monoxide (monomer)

Further information

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 0.0000 mg/l; ATE (inhalation dust/mist) 0.0000 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9016-87-9	Diphenylmethane diisocyanate, isomers and homologs				
	oral	LD50 >10000 mg/kg	Rat	Pre-supplier/manufacter	OECD 401
	dermal	LD50 >9400 mg/kg	Rabbit	Pre-supplier/manufacter	OECD 402
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1.5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethane diisocyanate, isomers and homologs)

May cause an allergic skin reaction. (Diphenylmethane diisocyanate, isomers and homologs)

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethane diisocyanate, isomers and homologs)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Diphenylmethane diisocyanate, isomers and homologs; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diphenylmethane diisocyanate, isomers and homologs; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No information available.

Specific effects in experiment on an animal

No information available.

Additional information on tests

No information available.

Practical experience

May cause respiratory irritation. Potential hazards:

The product is skin resorptive.

Irritating to eyes. (reversible.)

11.2. Information on other hazards

Other information

Isocyanate containing product.

Respiratory or skin sensitisation/ May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 8 of 12

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
9016-87-9	Diphenylmethane diisocyanate, isomers and homologs					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Danio rerio (zebrafish)	Pre-supplier/manufacturer	OECD 203
	Acute algae toxicity	ErC50 >1640 mg/l	72 h	Desmodesmus subspicatus	Pre-supplier/manufacturer	OECD 201
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	Pre-supplier/manufacturer	OECD 202
	Crustacea toxicity	NOEC >10 mg/l	21 d	Daphnia magna (Big water flea)	Pre-supplier/manufacturer	OECD 211
	Acute bacteria toxicity	EC50 >100 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	OECD 209

12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
9016-87-9	Diphenylmethane diisocyanate, isomers and homologs			
	Activated sludge , aerob	0%	28	OECD 302C
	nicht leicht biologisch abbaubar			

12.3. Bioaccumulative potential

No information available.

BCF

CAS No	Chemical name	BCF	Species	Source
9016-87-9	Diphenylmethane diisocyanate, isomers and homologs	<14	Cyprinus carpio (Common Carp)	OECD 305 C

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 9 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

080501 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes not otherwise specified in 08; waste isocyanates; hazardous waste

List of Wastes Code - used product

080501 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes not otherwise specified in 08; waste isocyanates; hazardous waste

List of Wastes Code - contaminated packaging

080501 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes not otherwise specified in 08; waste isocyanates; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.
Moisture-sensitive.
Protect against: Cold < +10°C
Short-term maximum storage temperature permitted: +50°C
Store separately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 10 of 12

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 56

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 11 of 12

Abbreviations and acronyms

Acute Tox: Acute toxicity

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation

Carc: Carcinogenicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8901 PU Hardener

Revision date: 24.10.2024

Product code: 50002

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)