

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision: 28.11.2025

8519-30N PU Resin

Product code: 8519-30N

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

8519-30N PU Resin

Further trade names

Product: 8519-30N resin + 8973 Hardener

Product group:

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants resin

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG
Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail (Contact person): compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail Contact person: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

EUH210 Safety data sheet available on request.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 2 of 12

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
78-40-0	triethyl phosphate			1 - < 5 %
	201-114-5	015-013-00-7		
	Acute Tox. 4, Eye Irrit. 2; H302 H319			
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate			1 - < 5 %
	945-730-9		01-2119511174-52	
	Aquatic Acute 1, Aquatic Chronic 3; H400 H412			
25791-96-2	Glycerine, propoxylated			1 - < 5 %
	Acute Tox. 4; H302			
115-86-6	Triphenylphosphate			0.1 - < 1 %
	204-112-2			
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
78-40-0	201-114-5	triethyl phosphate	1 - < 5 %
		oral: LD50 = 1170 mg/kg	
26444-49-5	945-730-9	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg Aquatic Acute 1; H400: M=1	
25791-96-2		Glycerine, propoxylated	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 1000 mg/kg	
115-86-6	204-112-2	Triphenylphosphate	0.1 - < 1 %
		dermal: LD50 = > 10000 mg/kg; oral: LD50 = > 20000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary.

After inhalation

Provide fresh air.

After contact with skin

Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. IF SWALLOWED: Immediately call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision: 28.11.2025

8519-30N PU Resin

Product code: 8519-30N

Page 3 of 12

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products, Flammable vapours can accumulate in steam space of closed systems.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. Evacuate area.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.

Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Hints on joint storage

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 4 of 12

No special measures are necessary.

Further information on storage conditions

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
78-40-0	triethyl phosphate			
Worker DNEL, long-term		inhalation	systemic	9.9 mg/m ³
Worker DNEL, long-term		dermal	systemic	2 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1.74 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1 mg/kg bw/day
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate			
Worker DNEL, long-term		inhalation	systemic	3,5 mg/m ³
Worker DNEL, acute		inhalation	systemic	28 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	4 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,875 mg/m ³
Consumer DNEL, acute		inhalation	systemic	7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	2 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
25791-96-2	Glycerine, propoxylated			
Worker DNEL, long-term		inhalation	systemic	98 mg/m ³
Worker DNEL, long-term		dermal	systemic	13,9 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	29 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8,3 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,3 mg/kg bw/day
115-86-6	Triphenylphosphate			
Worker DNEL, long-term		dermal	systemic	1.05 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	3.7 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0.91 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0.525 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0.525 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
78-40-0	triethyl phosphate	
Freshwater		0.632 mg/l
Freshwater (intermittent releases)		9 mg/l
Marine water		0.063 mg/l
Freshwater sediment		5 mg/kg
Marine sediment		0.5 mg/kg
Micro-organisms in sewage treatment plants (STP)		298.5 mg/l
Soil		0.64 mg/kg

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 5 of 12

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	
Freshwater		0,002 mg/l
Marine water		0,0002 mg/l
Freshwater sediment		3,43 mg/kg
Marine sediment		0,343 mg/kg
Secondary poisoning		267 mg/kg
Soil		0,68 mg/kg
25791-96-2	Glycerine, propoxylated	
Freshwater		0,2 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,02 mg/l
Freshwater sediment		0,52 mg/kg
Marine sediment		0,052 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		0,067 mg/kg
115-86-6	Triphenylphosphate	
Freshwater		0.00048 mg/l
Freshwater (intermittent releases)		0.003 mg/l
Marine water		0.000048 mg/l
Freshwater sediment		0.143 mg/kg
Marine sediment		0.014 mg/kg
Secondary poisoning		16.667 mg/kg
Micro-organisms in sewage treatment plants (STP)		5 mg/l
Soil		0.028 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NR (natural rubber, Natural latex) 0,5 mm, Breakthrough time: 480 min

EN ISO 374

Skin protection

Avoid contact with skin, eyes and clothes.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	beige
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	>200 °C
Flammability:	not determined
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>100 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents
not determined

Partition coefficient n-octanol/water:	not determined
Vapour pressure (at 20 °C):	1 hPa
Density (at 22 °C):	2,0 - 2,2 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not determined

DIN EN ISO 2811

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic (at 22 °C):	100.000 - 140.000 mPa·s

DIN 53019

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.
Vapours can form explosive mixtures with air.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 7 of 12

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-40-0	triethyl phosphate				
	oral	LD50 1170 mg/kg	Rat	GESTIS	
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate				
	oral	LD50 >5000 mg/kg	Rat	Pre-supplier/manufacturer	
	dermal	LD50 >2000 mg/kg	Rat	Pre-supplier/manufacturer	OECD 402
25791-96-2	Glycerine, propoxylated				
	oral	LD50 > 1000 mg/kg	Rat	Pre-supplier/manufacturer	OECD 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1992)	OECD Guideline 402
115-86-6	Triphenylphosphate				
	oral	LD50 > 20000 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	dermal	LD50 > 10000 mg/kg	Rabbit	Study report (1976)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 8 of 12

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Other information

No data available

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate					
	Acute fish toxicity	LC50 1,3 mg/l	96 h	Oryzias latipes (Ricefish)	Pre-supplier/manufacturer	
	Acute algae toxicity	ErC50 0,55 mg/l	72 h	Desmodesmus subspicatus	Pre-supplier/manufacturer	Regulation (EC) No. 440/2008, Annex C.3
	Algae toxicity	NOEC 0,11 mg/l	3 d	Desmodesmus subspicatus	Pre-supplier/manufacturer	Regulation (EC) No. 440/2008, Annex C.3
	Crustacea toxicity	NOEC 0,21 mg/l	21 d	Daphnia magna (Big water flea)	Pre-supplier/manufacturer	
	Acute bacteria toxicity	EC50 >10000 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	OECD 209
25791-96-2	Glycerine, propoxylated					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Leuciscus idus	Study report (1992)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2003)	EU Method C.3
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (1992)	OECD Guideline 202
	Crustacea toxicity	NOEC >= 10 mg/l	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	EC50 >10000 mg/l ()	3 h	Activated sludge	Pre-supplier/manufacturer	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 9 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
115-86-6	Triphenylphosphate					
	Acute fish toxicity	LC50 0.4 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	other: see below
	Acute algae toxicity	ErC50 2.45 mg/l	72 h	Raphidocelis subcapitata	Study report (2000)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1 mg/l	48 h	Daphnia magna	Aquatic Toxicology and Hazard Assessment	other: see below
	Fish toxicity	NOEC >= 0.001 mg/l	90 d	Oncorhynchus mykiss	Aquatic Toxicology and Hazard Assessment	Flow through system with 90d exposure pe
	Crustacea toxicity	NOEC 0.254 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

No data available

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate			
	OECD 301C	75 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-40-0	triethyl phosphate	0,8
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	4,5
25791-96-2	Glycerine, propoxylated	>= -1,82 - 12
115-86-6	Triphenylphosphate	4.63

BCF

CAS No	Chemical name	BCF	Species	Source
26444-49-5	Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	220		
115-86-6	Triphenylphosphate	144	Oryzias latipes	REACH Registration D

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision: 28.11.2025

8519-30N PU Resin

Product code: 8519-30N

Page 10 of 12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 11 of 12

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

Other applicable information

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
Triphenylphosphate

Restrictions on use (REACH, annex XVII):

Entry 75

Directive 2010/75/EU on industrial emissions: 3.597 % (71.94 g/l)

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

(EU) EINECS/ELINCS/NLP: yes

(RC) TCSI: yes

(NZ) NZIoC: yes

(USA) TSCA: yes

(CDN) DSL: no

(ROK) KECI/ECL: unknown

(RP) PICCS: no

(JP) MITI: no

(CHN) IECSC: yes

(AUS) AIIC: no

(CDN) NDSL: no

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,9,11,15.

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4

Eye Irrit. 2: Eye irritation, hazard category 2

Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

8519-30N PU Resin

Revision: 28.11.2025

Product code: 8519-30N

Page 12 of 12

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH210	Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)