

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 1 of 14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 9190 Liquid

UFI:

C6K0-N00N-S00U-9NRA

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Maintainer, irritant, containing solvents with skin absorptive substances

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Company name: Kisling AG  
Street: Motorenstrasse 102  
Place: CH-8620 Wetzikon  
Telephone: +41 58 272 0 272  
E-mail: customerservice@kisling.com  
Internet: www.kisling.com

#### Supplier

Company name: Kisling (Deutschland) GmbH  
Street: Salzstraße 15  
Place: D-74676 Niedernhall  
Telephone: +49 7940 50961 61  
E-mail: customerservice@kisling.com  
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143  
E-mail: compliance@kisling.com  
Internet: www.kisling.com

### 1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Asp. Tox. 1; H304  
Eye Irrit. 2; H319  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

propan-2-ol  
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  
acetone

Signal word: Danger

#### Pictograms:



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 2 of 14

#### Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.


#### Precautionary statements

P210	Keep away from heat. No Smoking.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



#### Hazard statements

H304

#### Precautionary statements

P301+P310-P331

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Stripper, irritant, containing solvents with skin absorptive substances

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol			50 - < 100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			50 - < 100 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
67-64-1	acetone			30 - < 50 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
110-82-7	cyclohexane			0.1 - < 1 %
	203-806-2	601-017-00-1		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 3 of 14

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol	50 - < 100 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13900 mg/kg; oral: LD50 = 4570-5840 mg/kg	
	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	50 - < 100 %
		inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg	
67-64-1	200-662-2	acetone	30 - < 50 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg	
110-82-7	203-806-2	cyclohexane	0.1 - < 1 %
		inhalation: LC50 = > 5540 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	

#### Labelling for contents according to Regulation (EC) No 648/2004

< 5 % aliphatic hydrocarbons.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

##### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

##### After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

##### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

##### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation. Causes eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder, Foam.

##### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 4 of 14

with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Provide adequate ventilation.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

See protective measures under point 7 and 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. When using do not eat or drink.

#### Further information on handling

When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

#### Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

#### Further information on storage conditions

Keep away from heat.

### 7.3. Specific end use(s)

Stripper, irritant, containing solvents with skin absorptive substances

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
110-82-7	Cyclohexane	200	700		TWA (8 h)	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 5 of 14

#### DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
67-64-1	acetone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
110-82-7	cyclohexane			
Worker DNEL, long-term		inhalation	systemic	700 mg/m³
Worker DNEL, acute		inhalation	systemic	1400 mg/m³
Worker DNEL, long-term		inhalation	local	700 mg/m³
Worker DNEL, acute		inhalation	local	1400 mg/m³
Worker DNEL, long-term		dermal	systemic	2016 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	206 mg/m³
Consumer DNEL, acute		inhalation	systemic	412 mg/m³
Consumer DNEL, long-term		inhalation	local	206 mg/m³
Consumer DNEL, acute		inhalation	local	412 mg/m³
Consumer DNEL, long-term		dermal	systemic	1186 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	59,4 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 6 of 14

#### PNEC values

CAS No	Name of agent	
Environmental compartment		Value
67-63-0	propan-2-ol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
67-64-1	acetone	
Freshwater		10,6 mg/l
Freshwater (intermittent releases)		21 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
110-82-7	cyclohexane	
Freshwater		0,0447 mg/l
Freshwater (intermittent releases)		0,009 mg/l
Marine water		0,00447 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		0,36 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,24 mg/l
Soil		0,694 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles

EN 166

##### Hand protection

Tested protective gloves must be worn.

Suitable material:

Thickness of the glove material > 0,4mm

> 480 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 7 of 14

#### Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: A (EN 14387)

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	55 °C
Flammability:	Highly flammable
Lower explosion limits:	2 vol. %
Upper explosion limits:	14,3 vol. %
Flash point:	-19 °C
Auto-ignition temperature:	425 °C
Decomposition temperature:	not applicable
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	233 hPa
Density:	0,75 g/cm <sup>3</sup>
Relative vapour density:	not determined
Particle characteristics:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Oxidizing properties

not determined

##### Other safety characteristics

Solvent content: 99,5%

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Oxidising agent, strong

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Oxidising agent, strong

#### 10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 8 of 14

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.5. Incompatible materials

Oxidising agent, strong

#### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

No data available

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol				
	oral	LD50 4570-5840 mg/kg	Rat	Pre-supplier/manufacturer	OECD 401
	dermal	LD50 13900 mg/kg	Rabbit	Pre-supplier/manufacturer	OECD 402
	inhalation (4 h) vapour	LC50 30 mg/l	Rat	Pre-supplier/manufacturer	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
67-64-1	acetone				
	oral	LD50 5800 mg/kg	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 > 7426 mg/kg	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
110-82-7	cyclohexane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 5540 mg/l	Rat	Study report (1981)	OECD Guideline 403

##### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 9 of 14

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (propan-2-ol; Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; acetone)

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### **Specific effects in experiment on an animal**

No data available

#### **Additional information on tests**

No data available

#### **Practical experience**

May be harmful if swallowed, in contact with skin or if inhaled.

### **11.2. Information on other hazards**

#### **Other information**

No data available

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-63-0	propan-2-ol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LL50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	Study report (1995) OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Raphidocelis subcapitata	SIDS Initial Assessment Report For SIAM OECD Guideline 201
	Acute crustacea toxicity	EL50	7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 211
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978) The toxicity of acetone towards daphnids
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310 Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	(EC50 mg/l)	61150	0.5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992) ISO 8192
110-82-7	cyclohexane					
	Acute fish toxicity	LC50 mg/l	4,53	96 h	Pimephales promelas	Vol. 5, Centre for Lake Superior Studies OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9,317	72 h	Raphidocelis subcapitata	Study report (1998) OECD Guideline 201
	Acute crustacea toxicity	EC50	0,9 mg/l	48 h	Daphnia magna	Publication (1987) OECD Guideline 202

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05
67-64-1	acetone	-0,23
110-82-7	cyclohexane	3,44

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 11 of 14

#### BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone	3		Unpublished calculat
110-82-7	cyclohexane	167	Pimephales promelas	J. Fish. Board Can.

#### 12.4. Mobility in soil

Product is easily volatile.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### 14.1. UN number or ID number:

UN 1993

##### 14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S.

##### 14.3. Transport hazard class(es):

3

##### 14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640C

Limited quantity:

1 L

Excepted quantity:

E2

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 12 of 14

Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993  
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
Hazard label: 3



Classification code: F1  
Special Provisions: 274 601 640C  
Limited quantity: 1 L  
Excepted quantity: E2

#### Marine transport (IMDG)

14.1. UN number or ID number: UN 1993  
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
Hazard label: 3



Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993  
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.  
14.3. Transport hazard class(es): 3  
14.4. Packing group: II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 13 of 14

Danger releasing substance: Hydrocarbons, C7-C9, n-al

#### 14.6. Special precautions for user

No data available

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 57, Entry 75

2010/75/EU (VOC): 99,5 %

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kisling - 9190 Liquid

Revision date: 14.11.2023

Product code: 9190F

Page 14 of 14

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)