

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2250 Paint primer red brown 400 ml

UFI: F235-Y83H-Q00S-W8Q7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Primers

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	technical.support@kisling.com	
Contact person:	Dr. Hans Götz	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335
STOT SE 3; H336
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

n-butyl acetate
xylene
butan-1-ol

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 2 of 15

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

Tactile warning according to EN/ISO 11683.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H318-H335-H336-H373

Precautionary statements

P102-P210-P211-P251-P410+P412

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Paints and varnishes

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
115-10-6	dimethyl ether			40 - 60 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
1330-20-7	xylene			15 - < 30 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
71-36-3	butan-1-ol			5 - < 15 %
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
123-86-4	n-butyl acetate			5 - < 15 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
25068-38-6	epoxy resin (Mn <= 700), reaction product: bisphenol-A-(epichlorhydrin)			5 - < 15 %
	500-033-5	603-074-00-8		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
115-10-6	204-065-8	dimethyl ether	40 - 60 %
		inhalation: LC50 = 164000 ppm (gases)	
1330-20-7	215-535-7	xylene	15 - < 30 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1.5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 4300 mg/kg	
71-36-3	200-751-6	butan-1-ol	5 - < 15 %
		dermal: LD50 = 3400 mg/kg; oral: LD50 = 790 mg/kg	
123-86-4	204-658-1	n-butyl acetate	5 - < 15 %
		oral: LD50 = 14130 mg/kg	
25068-38-6	500-033-5	epoxy resin (Mn <= 700), reaction product: bisphenol-A-(epichlorhydrin)	5 - < 15 %
		dermal: LD50 = >22800 mg/kg; oral: LD50 = 11400 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water. In case of skin irritation, consult a physician.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 4 of 15

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

The following symptoms may occur: Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 5 of 15

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
115-10-6	Dimethylether	1000	1920		TWA (8 h)	
123-86-4	n-Butylacetate	50	241		TWA (8 h)	EU
		150	723		STEL (15 min)	EU
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 6 of 15

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
115-10-6	dimethyl ether		
Worker DNEL, long-term	inhalation	systemic	1894 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	471 mg/m ³
1330-20-7	xylene		
Worker DNEL, long-term	inhalation	systemic	221 mg/m ³
Worker DNEL, acute	inhalation	systemic	442 mg/m ³
Worker DNEL, long-term	inhalation	local	221 mg/m ³
Worker DNEL, acute	inhalation	local	442 mg/m ³
Worker DNEL, long-term	dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	65,3 mg/m ³
Consumer DNEL, acute	inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term	inhalation	local	65,3 mg/m ³
Consumer DNEL, acute	inhalation	local	260 mg/m ³
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	12,5 mg/kg bw/day
71-36-3	butan-1-ol		
Worker DNEL, long-term	inhalation	local	310 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	55,357 mg/m ³
Consumer DNEL, long-term	inhalation	local	155 mg/m ³
Consumer DNEL, long-term	dermal	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1,562 mg/kg bw/day
123-86-4	n-butyl acetate		
Worker DNEL, long-term	inhalation	systemic	300 mg/m ³
Worker DNEL, acute	inhalation	systemic	600 mg/m ³
Worker DNEL, long-term	inhalation	local	300 mg/m ³
Worker DNEL, acute	inhalation	local	600 mg/m ³
Worker DNEL, long-term	dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	35,7 mg/m ³
Consumer DNEL, acute	inhalation	systemic	300 mg/m ³
Consumer DNEL, long-term	inhalation	local	35,7 mg/m ³
Consumer DNEL, acute	inhalation	local	300 mg/m ³
Consumer DNEL, long-term	dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	2 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 7 of 15

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
115-10-6	dimethyl ether	
Freshwater		0,155 mg/l
Freshwater (intermittent releases)		1,549 mg/l
Marine water		0,016 mg/l
Freshwater sediment		0,681 mg/kg
Marine sediment		0,069 mg/kg
Micro-organisms in sewage treatment plants (STP)		160 mg/l
Soil		0,045 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg
71-36-3	butan-1-ol	
Freshwater		0,082 mg/l
Freshwater (intermittent releases)		2,25 mg/l
Marine water		0,008 mg/l
Freshwater sediment		0,324 mg/kg
Marine sediment		0,032 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,017 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater (intermittent releases)		0,36 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,098 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,09 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles

Hand protection

Tested protective gloves must be worn.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 8 of 15

Suitable material:
Thickness of the glove material > 0,4mm
> 30 min.
EN ISO 374

Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: AP2 (EN 140/143).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	light grey, red brown
Odour:	characteristic

Test method

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	not applicable
Lower explosion limits:	0,9 vol. %
Upper explosion limits:	14 vol. %
Flash point:	< 21 °C
Auto-ignition temperature:	not determined
pH-Value:	not applicable
Water solubility:	practically insoluble
Vapour pressure: (at 50 °C)	> 5000 hPa
Density:	0,6-0,8 g/cm ³

9.2. Other information

Information with regard to physical hazard classes

Self-ignition temperature >300°C

Other safety characteristics

Flow time: < 40s 6 DIN EN ISO 2431

Further Information

none

SECTION 10: Stability and reactivity

10.1. Reactivity

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

alkali.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 9 of 15

10.6. Hazardous decomposition products

none

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 0.0000 mg/kg; ATE (dermal) 0.0000 mg/kg; ATE (inhalation vapour) 0.0000 mg/l; ATE (inhalation dust/mist) 0.0000 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
115-10-6	dimethyl ether					
	inhalation (4 h) gas	LC50 ppm	164000	Rat	Study report (1979)	Ten male rats were administered the test
1330-20-7	xylene					
	oral	LD50 mg/kg	4300	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1.5 mg/l			
71-36-3	butan-1-ol					
	oral	LD50 mg/kg	790	Rat		
	dermal	LD50 mg/kg	3400	Rabbit		
123-86-4	n-butyl acetate					
	oral	LD50 mg/kg	14130	Rat	Publication (1954)	acute oral toxicity test
25068-38-6	epoxy resin (Mn <= 700), reaction product: bisphenol-A-(epichlorhydrin)					
	oral	LD50 mg/kg	11400	Rat	GESTIS	
	dermal	LD50 mg/kg	>22800	Rabbit	GESTIS	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene; butan-1-ol)

May cause drowsiness or dizziness. (butan-1-ol)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 10 of 15

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
115-10-6	dimethyl ether					
	Acute fish toxicity	LC50 mg/l	> 4100	96 h	Poecilia reticulata	Study report (1988) other: NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 mg/l	154,917	96 h	green algae	Other company data (2009) other: Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 mg/l	> 4400	48 h	Daphnia magna	Study report (1988) other: NEN6501: Water -Determination of
1330-20-7	xylene					
	Fish toxicity	NOEC mg/l	> 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l	1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 other: US EPA 600/4-91-003
	Acute bacteria toxicity	(EC50 mg/l)	> 175	0 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (
71-36-3	butan-1-ol					
	Acute fish toxicity	LC50 mg/l	1376	96 h	Pimephales promelas	Study report (1998) OECD Guideline 203
	Acute algae toxicity	ErC50	225 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1998) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	1328	48 h	Daphnia magna	Study report (1998) OECD Guideline 202
	Crustacea toxicity	NOEC	4,1 mg/l	21 d	Daphnia magna	Study report (1996) OECD Guideline 211
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas	Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia sp.	Publication (1959) OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	23,2	21 d	Daphnia magna	Study report (2000) OECD Guideline 211

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,07
1330-20-7	xylene	3,2
71-36-3	butan-1-ol	10
123-86-4	n-butyl acetate	200

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 12 of 15

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
71-36-3	butan-1-ol	3,16		QSAR (2017)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 13 of 15

Special Provisions: 190 327 344 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

: Y203

14.5. Environmental hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 14 of 15

ENVIRONMENTALLY HAZARDOUS: Yes



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 80,8%; 678 g/l

2004/42/EC (VOC): 678 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

National regulatory information

Employment restrictions: Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
STOT SE 3; H335	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
STOT RE 2; H373	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H226 Flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2250 Paint primer red brown 400 ml

Revision date: 06.02.2024

Product code: 91388

Page 15 of 15

H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Coatings and paints, thinners, paint removers	-	-	9a	7, 11	11a	7, 7a	91	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)