

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision: 25.02.2026

2260 Rust protection primer red-brown

Product code: 92085

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2260 Rust protection primer red-brown

UFI: 7898-SNW9-G20K-M1MS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive paints, containing solvents, high in aromatics, harmful

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: customerservice@kisling.com
Contact person: Product Compliance Telephone: +49 7940 5096 143
E-mail (Contact person): compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

n-butyl acetate
xylene
2-methoxy-1-methylethyl acetate

Signal word: Warning**Pictograms:****Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 2 of 14

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe aerosol dispensers and lighters.
P271	Use only outdoors or in a well-ventilated area.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

Tactile warning according to EN/ISO 11683.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



Hazard statements

H336-H373

Precautionary statements

P102-P260-P271-P501

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
123-86-4	n-butyl acetate			15 - < 30 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
1330-20-7	xylene			5 - < 15 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
100-41-4	ethylbenzene			5 - < 15 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 15 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
123-86-4	204-658-1	n-butyl acetate	15 - < 30 %
		oral: LD50 = 14130 mg/kg	
1330-20-7	215-535-7	xylene	5 - < 15 %
		inhalation: LC50 = 19,8 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 5000 mg/kg	
100-41-4	202-849-4	ethylbenzene	5 - < 15 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 15 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Powder.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Danger of serious damage to health by prolonged exposure.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 4 of 14

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid release to the environment. In use, may form flammable/explosive vapour-air mixture.
Only use the material in places where open light, fire and other flammable sources can be kept away.
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools.

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. When using do not eat, drink or smoke.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Keep only in the original container in a cool, well-ventilated place.
Never use pressure to empty container. Do not allow to enter into surface water or drains.

7.2. Conditions for safe storage, including any incompatibilities

Hints on joint storage

Do not store together with: ,

Further information on storage conditions

Follow the instructions for use on the label.
Keep container dry.
Keep away from sources of ignition - No smoking. Protect from direct sunlight.

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
--------	---------------	-----	-------------------	---------------------	----------	--------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 5 of 14

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
108-65-6	2-Methoxy-1-methylethylacetate	50	275		TWA (8 h)	
		100	550		STEL (15 min)	
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
123-86-4	n-Butyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	300 mg/m ³
Worker DNEL, acute		inhalation	systemic	600 mg/m ³
Worker DNEL, long-term		inhalation	local	300 mg/m ³
Worker DNEL, acute		inhalation	local	600 mg/m ³
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35.7 mg/m ³
Consumer DNEL, acute		inhalation	systemic	300 mg/m ³
Consumer DNEL, long-term		inhalation	local	35.7 mg/m ³
Consumer DNEL, acute		inhalation	local	300 mg/m ³
Consumer DNEL, long-term		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
1330-20-7	xylene			
Worker DNEL, long-term		inhalation	systemic	221 mg/m ³
Worker DNEL, acute		inhalation	systemic	442 mg/m ³
Worker DNEL, long-term		inhalation	local	221 mg/m ³
Worker DNEL, acute		inhalation	local	442 mg/m ³
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m ³
Consumer DNEL, acute		inhalation	systemic	260 mg/m ³
Consumer DNEL, long-term		inhalation	local	65,3 mg/m ³
Consumer DNEL, acute		inhalation	local	260 mg/m ³
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day
100-41-4	ethylbenzene			
Worker DNEL, long-term		inhalation	systemic	77 mg/m ³
Worker DNEL, acute		inhalation	local	293 mg/m ³
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	15 mg/m ³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term		inhalation	systemic	275 mg/m ³
Worker DNEL, acute		inhalation	local	550 mg/m ³
Worker DNEL, long-term		dermal	systemic	796 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	33 mg/m ³
Consumer DNEL, long-term		inhalation	local	33 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 6 of 14

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
	DNEL type			
	Consumer DNEL, long-term	dermal	systemic	320 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	36 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
	Environmental compartment	
123-86-4	n-butyl acetate	
	Freshwater	0.18 mg/l
	Freshwater (intermittent releases)	0.36 mg/l
	Marine water	0.018 mg/l
	Freshwater sediment	0.981 mg/kg
	Marine sediment	0.098 mg/kg
	Micro-organisms in sewage treatment plants (STP)	35.6 mg/l
	Soil	0.09 mg/kg
1330-20-7	xylene	
	Freshwater	0,327 mg/l
	Freshwater (intermittent releases)	0,327 mg/l
	Marine water	0,327 mg/l
	Freshwater sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Micro-organisms in sewage treatment plants (STP)	6,58 mg/l
	Soil	2,31 mg/kg
100-41-4	ethylbenzene	
	Freshwater	0,1 mg/l
	Freshwater (intermittent releases)	0,1 mg/l
	Marine water	0,01 mg/l
	Freshwater sediment	13,7 mg/kg
	Marine sediment	1,37 mg/kg
	Secondary poisoning	20 mg/kg
	Micro-organisms in sewage treatment plants (STP)	9,6 mg/l
	Soil	2,68 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
	Freshwater	0.635 mg/l
	Freshwater (intermittent releases)	6.35 mg/l
	Marine water	0.064 mg/l
	Freshwater sediment	3.29 mg/kg
	Marine sediment	0.329 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	0.29 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 7 of 14

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material: Butyl caoutchouc (butyl rubber)
Thickness of the glove material 0,7 mm
> 480 min

See information supplied by the manufacturer.

Skin protection

(Natural fibres (e.g. cotton)/ heat-resistant synthetic fibres)

Respiratory protection

In case of inadequate ventilation wear respiratory protection. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	red brown
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	124 °C
Flammability:	not determined
Lower explosion limits:	1,1 vol. %
Upper explosion limits:	7,5 vol. %
Flash point:	23 °C
Auto-ignition temperature:	315 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.

Solubility in other solvents
not determined

Partition coefficient n-octanol/water:	not determined
Vapour pressure (at 20 °C):	10,7 hPa
Density (at 20 °C):	1,28 g/cm ³
Relative density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
not determined

Other safety characteristics

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 8 of 14

Evaporation rate:	not determined
Solvent content:	41%
Solid content:	59%
Viscosity / dynamic:	not determined
Flow time:	62 s 4 DIN 53211

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

In case of warming: Thermal decomposition.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 14130 mg/kg	Rat	publication (1954)	acute oral toxicity test
1330-20-7	xylene				
	oral	LD50 5000 mg/kg	Rat	GESTIS	
	dermal	ATE 1100 mg/kg			
	inhalation (4 h) vapour	LC50 19,8 mg/l	Rat	GESTIS	
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-butyl acetate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May cause respiratory irritation. Potential hazards:

The product is skin resorptive.

Irritating to eyes. (reversible.)

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas	publication (1984)	OECD Guideline 203
	Acute algae toxicity	ErC50 397 mg/l	72 h	Raphidocelis subcapitata (previous names: Pseudoki)	study report (2000)	OECD Guideline 201
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia sp.	publication (1959)	OECD Guideline 202
	Crustacea toxicity	NOEC 23.2 mg/l	21 d	Daphnia magna	study report (2000)	OECD Guideline 211
1330-20-7	xylene					
	Acute algae toxicity	ErC50 3,2 mg/l	72 h	Selenastrum capricornutum	Galassi et al. 1988	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown	
Revision: 25.02.2026	Product code: 92085 Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50 3,6 mg/l	96 h	Pseudokirchneriella subcapitata	ECHA	
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	200
1330-20-7	xylene	3,15
100-41-4	ethylbenzene	3,15
108-65-6	2-methoxy-1-methylethyl acetate	0,43

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 11 of 14

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Other applicable information (land transport)

No dangerous good in sense of this transport regulation. < 450 Liter ADR 2.2.3.1.5.

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: 163 223 367 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 12 of 14



Special Provisions:	A3 A72 A192
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 49.89 % (638.592 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 38 % (486.4 g/l)

Subcategory according to Directive 2004/42/EC: Primer - Surfacer/filler and general (metal) primer, VOC limit value: 540 g/l

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

(EU) EINECS/ELINCS/NLP: yes

(RC) TCSI: yes

(NZ) NZIoC: yes

(USA) TSCA: yes

(CDN) DSL: yes

(ROK) KECI/ECL: yes

(RP) PICCS: yes

(JP) MITI: yes

(CHN) IECSC: yes

(AUS) AIIC: yes

(CDN) NDSL: no

15.2. Chemical safety assessment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 13 of 14

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
 Flam. Liq. 3: Flammable liquids, hazard category 3
 Acute Tox. 4: Acute toxicity, hazard category 4
 Asp. Tox. 1: Aspiration hazard, hazard category 1
 Skin Irrit. 2: Skin irritation, hazard category 2
 Eye Irrit. 2: Eye irritation, hazard category 2
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2260 Rust protection primer red-brown

Revision: 25.02.2026

Product code: 92085

Page 14 of 14

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)