



according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

3040 Nano rain repellent Eco

UFI: 0FRD-E8K5-M004-X5XM

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Acid-hardened sealants, high in solvents

#### 1.3. Details of the supplier of the safety data sheet

Company name: Kisling (Deutschland) GmbH

Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61

E-mail: technical.support@kisling.com

Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143

E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone 24 hr. emergency phone number +1 872 5888271 (KAR)

number: Medicines & Poisons Info Office +356 2545 6508

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:





### **Hazard statements**

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

# **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P403+P235 Store in a well-ventilated place. Keep cool.

#### Additional advice on labelling

Tactile warning according to EN/ISO 11683.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger



according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 2 of 10

#### Pictograms:





## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

# **Chemical characterization**

Acid-hardened sealants, high in solvents

#### **Hazardous components**

CAS No	Chemical name	Chemical name						
	EC No Index No REACH No							
	Classification (Regulation (EC) No 1272/2008)							
64-17-5	7-5 Ethanol							
	200-578-6 603-002-00-5 01-2119457610-43							
	Flam. Liq. 2, Eye Irrit. 2; H225 H319							

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
64-17-5	200-578-6	Ethanol	50 - < 100 %		
	inhalation: LC50 = 124,7 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100				

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

If unconscious but breathing normally, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2), Dry extinguishing powder,, alcohol resistant foam, Water spray.

# Unsuitable extinguishing media

Strong water jet

# 5.3. Advice for firefighters





according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 3 of 10

In case of fire: Wear self-contained breathing apparatus. Use water spray jet to protect personnel and to cool endangered containers.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

# Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

After contact with skin, wash immediately with plenty of water and soap.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

## Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

## Further information on storage conditions

Keep away from heat.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

#### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters



according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 4 of 10

#### **DNEL/DMEL values**

CAS No	Name of agent								
DNEL type	DNEL type		Effect	Value					
64-17-5	Ethanol								
Worker DNEL,	Worker DNEL, long-term		systemic	950 mg/m³					
Worker DNEL,	Worker DNEL, long-term		systemic	343 mg/kg bw/day					
Consumer DN	Consumer DNEL, long-term		systemic	114 mg/m³					
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day					
Consumer DN	EL, long-term	oral	systemic	87 mg/kg bw/day					

#### **PNEC** values

CAS No	Name of agent					
Environment	Environmental compartment					
64-17-5	Ethanol					
Freshwater	Freshwater					
Freshwater (	2,75 mg/l					
Marine wate		0,79 mg/l				
Freshwater	3,6 mg/kg					
Marine sedir	Marine sediment					
Secondary p	Secondary poisoning					
Micro-organi	Micro-organisms in sewage treatment plants (STP)					
Soil	Soil					

#### 8.2. Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

# Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear eye/face protection.

EN 166

#### **Hand protection**

Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm

480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

**EN ISO 374** 

## Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Filtering device with filter or ventilator filtering device of type: ABEK

### **Environmental exposure controls**

Do not allow to enter into surface water or drains. No special environmental measures are necessary.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear



according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 5 of 10

Odour: Alcohol

Test method

Melting point/freezing point: -117 °C

Melting point/freezing point:

-117 °C

Boiling point or initial boiling point and

78 °C

boiling range:

Lower explosion limits: 3,5 vol. %
Upper explosion limits: 15 vol. %
Flash point: 18 °C
Auto-ignition temperature: 400 °C
pH-Value: 2

Water solubility: completely miscible Vapour pressure: 57 hPa

(at 20 °C)

Density (at 20 °C): 0,82 g/cm³ DIN 51757

#### 9.2. Other information

## Other safety characteristics

Solvent content: 90%

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

Keep away from heat.

# 10.3. Possibility of hazardous reactions

Keep away from: alkali. Alkali metals. Alkaline earth metal

## 10.4. Conditions to avoid

Thermal decomposition can lead to the escape of irritating gases and vapours.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

## 10.5. Incompatible materials

alkali. Alkali metals. Alkaline earth metal

## 10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

Carbon monoxide Hydrogen chloride (HCI)

#### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

# ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to Regulation (EC) No 1907/2006

## 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 6 of 10

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64-17-5	Ethanol							
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401		
	dermal	dermal LD50 mg/kg		Rabbit	Pre-supplier/manufa	ot OECD 402		
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403		

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### **Practical experience**

May be harmful if swallowed, in contact with skin or if inhaled.

# 11.2. Information on other hazards

#### Other information

Has degreasing effect on the skin.

## **Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## **SECTION 12: Ecological information**

# 12.1. Toxicity

No data available



according to Regulation (EC) No 1907/2006

## 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 7 of 10

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64-17-5	Ethanol							
	Acute fish toxicity	LC50 15400 mg/l		96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975	
	Acute algae toxicity	ErC50 22000 mg/l	ca.		Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201	
	Acute crustacea toxicity		48 h Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11			
			100 d Oryzias latipes		Environmental Toxicology and Chemistry,	Chronic effects of substance on reproduc		
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a	
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th	

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	-0,77

# BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	Ethanol	1	Cyprinus carpio	Comparative Biochemi

# 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

The evaluation was carried out according to the calculation method.

According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains.



according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 8 of 10

#### List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation,

supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and

mother liquors; hazardous waste

#### List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation,

supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and

mother liquors; hazardous waste

#### Contaminated packaging

Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:

3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

# Marine transport (IMDG)

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3





according to Regulation (EC) No 1907/2006

3040 Nano rain repellent Eco							
Revision date: 06.02.2024	Product code: 94153	Page 9 of 10					
Special Provisions:	144						
Limited quantity:	1 L						
Excepted quantity:	E2						

Air transport (ICAO-TI/IATA-DGR)

EmS:

14.1. UN number or ID number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

F-E, S-D

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 90 % (738 g/l)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

## **SECTION 16: Other information**

# Abbreviations and acronyms

Flam. Liq: Flammable liquid Eye Irrit: Eye irritation

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.





according to Regulation (EC) No 1907/2006

# 3040 Nano rain repellent Eco

Revision date: 06.02.2024 Product code: 94153 Page 10 of 10

## **Identified uses**

TF: Technical functions

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Acid-hardened sealants, high in solvents	IS, PW, C	-	9a, 15, 32	11, 19	8e, 10a	1, 1a, 1b, 4	7, 13, 14, 119	

 LCS: Life cycle stages
 SU: Sectors of use

 PC: Product categories
 PROC: Process categories

 ERC: Environmental release categories
 AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)