

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4615 Adhesive lubricant spray 400 ml

UFI: MM0D-S8YK-400G-YCXF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	technical.support@kisling.com	
Contact person:	Dr. Hans Götz	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229
Asp. Tox. 1; H304
Skin Irrit. 2; H315
STOT SE 3; H336
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 2 of 9

P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229-H336

Precautionary statements

P102-P210-P211-P251-P410+P412

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Lubricants, greases, release products

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics			25-50 %
	927-510-4			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-49-0	927-510-4	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics	25-50 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >5840 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 3 of 9

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately.
When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 4 of 9

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics		
Worker DNEL, long-term	inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term	dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term	dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	149 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

No data available

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NR (natural rubber, Natural latex) > 0,4 mm, Breakthrough time: > 480 min EN ISO 374

Skin protection

Wear suitable protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Use suitable breathing apparatus. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	light yellow	
Odour:	characteristic	
Melting point/freezing point:		No data available
Lower explosion limits:		1,4 vol. %
Upper explosion limits:		13,00 vol. %
Flash point:		-104 °C
Water solubility:		0 g/L
Density (at 20 °C):		0,768 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 5 of 9

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermic reaction with: Alkali (lye); Strong acid; Oxidising agent, strong

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5. Incompatible materials

Oxidising agent, strong. . Alkali (lye)

10.6. Hazardous decomposition products

Hazardous decomposition products: Carbon dioxide (CO₂) Carbon monoxide Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics				
	oral	LD50 >5840 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

11.2. Information on other hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 6 of 9

Other information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	Hydrocarbons C7 - n-alkanes - isoalkanes - cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 7 of 9

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 8 of 9

Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 29, Entry 40
 2010/75/EU (VOC): 548 g/L (88%)

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Aerosol: Aerosols
 Flam. Liq: Flammable liquid
 Asp. Tox: Aspiration hazard
 Skin Irrit: Skin irritation
 STOT SE: Specific target organ toxicity - single exposure
 Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

4615 Adhesive lubricant spray 400 ml

Revision date: 06.02.2024

Product code: 93887

Page 9 of 9

H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Lubricating agent	PW, C	-	24	11	-	-	7, 80	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)