

according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4740 Rust dissolver MoS2 Spray 400 ml

UFI: W7SE-P8Y1-X007-PGJG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Kisling (Deutschland) GmbH

Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61

E-mail: customerservice@kisling.com

Contact person: Product Compliance Telephone: +49 7940 5096 143

E-mail: compliance@kisling.com

Internet: www.kisling.com

1.4. Emergency telephone 24 hr. emergency phone number +1 872 5888271 (KAR)

<u>number:</u> Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Signal word: Danger

Pictograms:







Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 2 of 13

P210 Keep away from heat. No Smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:







Hazard statements

H222-H229-H336

Precautionary statements

P102-P210-P211-P251-P410+P412

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	1272/2008)				
	Hydrocarbons, C7-C9, n-alkanes, is	soalkanes, cyclics		30 - < 50 %		
	920-750-0		01-2119473851-33			
	Flam. Liq. 2, STOT SE 3, Asp. Tox.	1, Aquatic Chronic 2; H225 H336 H	304 H411			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified					
	265-159-2		01-2119480132-48			
	Asp. Tox. 1; H304					
	Hydrocarbons C11-C14 - n-alkanes - isoalkanes - cyclics - 2-25% aromatics					
	925-653-7		01-2119458869-15			
	Asp. Tox. 1, Aquatic Chronic 3; H30)4 H412				
1174921-73- 3	Hydrocarbons, C9-C10, n-alkanes,	isoalkanes, cyclics, < 2% aromatics		1 - < 5 %		
	927-344-2		01-2119471843-32			
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

opositio cono. Elittico, il factoro ana ATE			
CAS No	EC No	o Chemical name	
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE	
	920-750-0	750-0 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg		
64742-56-9	265-159-2	265-159-2 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % aromatic hydrocarbons.





according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 3 of 13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Powder.

5.2. Special hazards arising from the substance or mixture

Reignition possible over considerable distance. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Wear a self-contained breathing apparatus and chemical protective clothing. Move undamaged containers from immediate hazard area if it can be done safely. Evacuate area.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area. Avoid breathing spray. See protective measures under point 7 and 8.

6.2. Environmental precautions

Avoid release to the environment. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up





according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 4 of 13

For containment

Use non-sparking tools. Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Only use the material in places where open light, fire and other flammable sources can be kept away. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Advice on general occupational hygiene

Draw up and observe skin protection programme. Avoid contact with skin, eyes and clothes. Avoid breathing spray. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect from sunlight.

Hints on joint storage

Do not store together with:

Pyrophoric or self-heating substances, Organic peroxides and self-reactive substances, Flammable solids, gas, Blasting agent

Further information on storage conditions

5 - 30°C

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Consumer DNI	EL, long-term	inhalation	systemic	608 mg/m³
Consumer DNI	EL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	699 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Ba	aseoil - unspecified		
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³
Consumer DNI	EL, long-term	oral	systemic	0,74 mg/kg bw/day
1174921-73- 3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2	2% aromatics		
Worker DNEL,	long-term	dermal	systemic	300 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	1500 mg/m³

PNEC values

CAS No	Name of agent			
Environmental	Environmental compartment Value			
64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
Secondary pois	Secondary poisoning 9,33 mg/kg			

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material:

Thickness of the glove material 0,45 mm

> 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 6 of 13

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Self-contained respirator (breathing apparatus)

Thermal hazards

Heating causes rise in pressure with risk of bursting.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light brown
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not applicable

boiling range:

not determined Flammability: Lower explosion limits: 0.6 vol. % Upper explosion limits: 15,0 vol. % not applicable Flash point: not determined Auto-ignition temperature: not determined Decomposition temperature: not applicable pH-Value: not determined Viscosity / kinematic: **Immiscible** Water solubility:

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative density:

Relative vapour density:

not determined
not determined
not determined
not determined
not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Heating may cause an explosion. Vapours can form explosive mixtures with air.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined Viscosity / dynamic: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 7 of 13

Materials to avoid:

10.4. Conditions to avoid

Avoid high temperatures or direct sunlight.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name	Chemical name					
	Exposure route	Dose	Species	Source	Method		
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de		
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403		
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified						
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 8 of 13

Additional information on tests

No data available

Practical experience

No data available

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
	Acute fish toxicity	LL50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Raphidocelis subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EL50	7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
64742-56-9	-9 Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 9 of 13

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; gases in pressure containers (including halons) containing hazardous substances;

hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; gases in pressure containers (including halons) containing hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances;

hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 10 of 13

Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1

2

Special Provisions: 63 190 277 327 344 381 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C7-C9Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

14.6. Special precautions for user
Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial 100 % (680 g/l)

emissions:





according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 11 of 13

Directive 2004/42/EC on VOC in paints

and varnishes:

100 % (680 g/l)

Information according to Directive

2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information: E2

Additional information

Regulation (EC) No. 648/2004 [Detergents regulation].

Aerosol Directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml

Revision date: 09.09.2024 Product code: 94523 Page 12 of 13

Abbreviations and acronyms

Aerosol: Aerosol

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.



according to Regulation (EC) No 1907/2006

4740 Rust dissolver MoS2 Spray 400 ml				
Revision date: 09.09.2024	Product code: 94523	Page 13 of 13		
H229	Pressurised container: May burst if heated.			
H304	May be fatal if swallowed and enters airways.			
H336	May cause drowsiness or dizziness.			
H411	Toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)