

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

5235 Cockpit care Spray 400 ml

UFI: VQND-78GF-T009-S89J

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Automotive care products

### 1.3. Details of the supplier of the safety data sheet

Company name:	Kisling (Deutschland) GmbH	
Street:	Salzstraße 15	
Place:	D-74676 Niedernhall	
Telephone:	+49 7940 50961 61	
E-mail:	technical.support@kisling.com	
Contact person:	Dr. Hans Götz	Telephone: +49 7940 5096 143
E-mail:	compliance@kisling.com	
Internet:	www.kisling.com	

### 1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Aerosol 1; H222-H229  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

propan-2-ol  
Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane

Signal word: Danger

#### Pictograms:



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 2 of 11

#### Precautionary statements

- P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P273 Avoid release to the environment.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Special labelling of certain mixtures

- EUH208 Contains DL-Limonene. May produce an allergic reaction.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Pictograms:



#### Hazard statements

H222-H229-H336

#### Precautionary statements

P102-P210-P211-P251-P410+P412

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	Classification (Regulation (EC) No 1272/2008)	
67-63-0	propan-2-ol	30 - < 50 %
	200-661-7 603-117-00-0	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane	15 - < 30 %
	921-024-6 01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
8042-47-5	White mineral oil (petroleum)	5 - < 15 %
	232-455-8 01-2119487078-27	
	Asp. Tox. 1; H304	
138-86-3	DL-Limonene	0.1 - < 1 %
	205-341-0 601-029-00-7	
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H226 H315 H317 H304 H400 H410	

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 3 of 11

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-63-0	200-661-7	propan-2-ol	30 - < 50 %
		inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13900 mg/kg; oral: LD50 = 4570-5840 mg/kg	
64742-49-0	921-024-6	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane	15 - < 30 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
8042-47-5	232-455-8	White mineral oil (petroleum)	5 - < 15 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

#### Labelling for contents according to Regulation (EC) No 648/2004

15 % - &lt; 30 % aliphatic hydrocarbons, perfumes.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention.

##### After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder,, alcohol resistant foam, Water spray.

##### Unsuitable extinguishing media

Strong water jet

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 4 of 11

accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

#### Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately.  
When using do not eat or drink.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

##### Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

##### Further information on storage conditions

Keep away from heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
67-63-0	propan-2-ol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
8042-47-5	White mineral oil (petroleum)			
Worker DNEL, long-term		inhalation	systemic	164,56 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	217,05 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	34,78 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 5 of 11

#### PNEC values

CAS No	Name of agent	
Environmental compartment		Value
67-63-0	propan-2-ol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

#### 8.2. Exposure controls

##### Appropriate engineering controls

No data available

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Wear protective gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

NR (natural rubber, Natural latex) > 0,4 mm, Breakthrough time: > 480 min EN ISO 374

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

Use suitable breathing apparatus. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	colourless	
Odour:	Lemon	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		-42 °C
Lower explosion limits:		0,6 vol. %
Upper explosion limits:		15 vol. %
Auto-ignition temperature:		>200 °C
pH-Value:		7-9
Water solubility:		practically insoluble
Vapour pressure:		3800 hPa
(at 20 °C)		
Vapour pressure:		6800 hPa
(at 50 °C)		

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 6 of 11

Density (at 20 °C):

0,66 g/cm<sup>3</sup>

#### SECTION 10: Stability and reactivity

##### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

##### 10.3. Possibility of hazardous reactions

Thermal decomposition can lead to the escape of irritating gases and vapours.

##### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

##### 10.5. Incompatible materials

Oxidising agent, strong. . Alkali (lye)

##### 10.6. Hazardous decomposition products

Hazardous decomposition products: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide Nitrogen oxides (NO<sub>x</sub>)

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

###### Toxicokinetics, metabolism and distribution

No data available

###### Acute toxicity

Based on available data, the classification criteria are not met.

###### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol				
	oral	LD50 4570-5840 mg/kg	Rat	Pre-supplier/manufacturer	OECD 401
	dermal	LD50 13900 mg/kg	Rabbit	Pre-supplier/manufacturer	OECD 402
	inhalation (4 h) vapour	LC50 30 mg/l	Rat	Pre-supplier/manufacturer	
64742-49-0	Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat		OECD 401
	dermal	LD50 >2000 mg/kg	Rat		OECD 402
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		OECD 403
8042-47-5	White mineral oil (petroleum)				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

###### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 7 of 11

#### Sensitising effects

Contains DL-Limonene. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; Hydrocarbons C6-C7 n-alkanes - isoalkanes - cyclics - <5% n-hexane)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

#### 11.2. Information on other hazards

##### Other information

No data available

### SECTION 12: Ecological information

#### 12.1. Toxicity

No data available

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method	
67-63-0	propan-2-ol						
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
8042-47-5	White mineral oil (petroleum)						
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Leuciscus idus melanotus	Study report (1992)	OECD Guideline 203
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 8 of 11

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### **Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - used product**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

##### **List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

##### **Contaminated packaging**

Completely emptied packages can be recycled. Dispose of waste according to applicable legislation.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

#### **Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 9 of 11



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L  
Excepted quantity: E0

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 29, Entry 40, Entry 75

2010/75/EU (VOC): 96,4%

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 10 of 11

#### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Abbreviations and acronyms

Aerosol: Aerosols  
Flam. Liq: Flammable liquid  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Eye Irrit: Eye irritation  
Skin Sens: Skin sensitisation  
STOT SE: Specific target organ toxicity - single exposure  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

#### Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH208 Contains DL-Limonene. May produce an allergic reaction.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### 5235 Cockpit care Spray 400 ml

Revision date: 06.02.2024

Product code: 94121

Page 11 of 11

#### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Surface modifier	-	-	14	-	-	-	-	3
2	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*