

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

UFI: JX29-F617-U00X-QF30

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Kisling (Deutschland) GmbH
Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61
E-mail: technical.support@kisling.com
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143
E-mail: compliance@kisling.com
Internet: www.kisling.com

1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)
Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

ethyl acetate

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 2 of 9

Additional advice on labelling

Tactile warning according to EN/ISO 11683.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H336

Precautionary statements

P102-P271-P405

2.3. Other hazards

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification (Regulation (EC) No 1272/2008)	
141-78-6	ethyl acetate	> 80 %
	205-500-4	607-022-00-5
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
141-78-6	205-500-4	ethyl acetate	> 80 %
	dermal: LD50 = > 20000 mg/kg; oral: LD50 = 4934 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with:

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 3 of 9

Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 4 of 9

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
141-78-6	ethyl acetate			
	Worker DNEL, long-term	inhalation	systemic	734 mg/m ³
	Worker DNEL, acute	inhalation	systemic	1468 mg/m ³
	Worker DNEL, long-term	inhalation	local	734 mg/m ³
	Worker DNEL, acute	inhalation	local	1468 mg/m ³
	Worker DNEL, long-term	dermal	systemic	63 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	367 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	734 mg/m ³
	Consumer DNEL, long-term	inhalation	local	367 mg/m ³
	Consumer DNEL, acute	inhalation	local	734 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	37 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	4,5 mg/kg bw/day

PNEC values

CAS No	Name of agent	Value
141-78-6	ethyl acetate	
	Freshwater	0,24 mg/l
	Freshwater (intermittent releases)	1,65 mg/l
	Marine water	0,024 mg/l
	Freshwater sediment	1,15 mg/kg
	Marine sediment	0,115 mg/kg
	Secondary poisoning	200 mg/kg
	Micro-organisms in sewage treatment plants (STP)	650 mg/l
	Soil	0,148 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material:

Butyl caoutchouc (butyl rubber) 0,7mm

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 5 of 9

120min

See information supplied by the manufacturer.

Skin protection

(Natural fibres (e.g. cotton)/ heat-resistant synthetic fibres)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.
In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	whitish	
Odour:	fruity	
Boiling point or initial boiling point and boiling range:		77 °C
Lower explosion limits:		2,2 vol. %
Upper explosion limits:		11,5 vol. %
Flash point:		-2,99 °C
Auto-ignition temperature:		420 - 460 °C
Water solubility:		80 g/L
Partition coefficient n-octanol/water:		0,66 - 0,73
Vapour pressure:		98,4 hPa
(at 20 °C)		
Vapour pressure:		379 hPa
(at 50 °C)		
Density (at 20 °C):		0,9 g/cm ³

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Other safety characteristics

Viscosity / dynamic:
(at 20 °C) 12 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

,

10.4. Conditions to avoid

In case of warming: Thermal decomposition.

10.5. Incompatible materials

Oxidising agent. Acid. Strong acid. Alkali (lye). Peroxides. Amines.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 6 of 9

10.6. Hazardous decomposition products

Carbon monoxide Acetic acid. Ethanol.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
141-78-6	ethyl acetate					
	oral	LD50 mg/kg	4934	Rabbit	Ind. Med. Vol. 41, No.4, 31 - 33 (1972)	OECD Guideline 401
	dermal	LD50 mg/kg	> 20000	Rabbit	Am Ind Hyg Ass J, 23, 95 (1962)	Similar to one day cuff method of Draize

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

May cause respiratory irritation. Potential hazards:

The product is skin resorptive.

Irritating to eyes. (reversible.)

11.2. Information on other hazards

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 7 of 9

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	Publication (1984) other: US EPA method E03-05
	Fish toxicity	NOEC	< 9,65 mg/l	32 d	Pimephales promelas	http://www.epa.gov/ecotox (1992) OECD Guideline 210
	Crustacea toxicity	NOEC	2,4 mg/l	21 d	Daphnia magna	Water Research 23: 501-510. (1989) other: see principles of method below

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,68

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus melanotus	Chemosphere 14, 1589

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); Solvents; hazardous waste

List of Wastes Code - used product

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); Solvents; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 8 of 9

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1173
14.2. UN proper shipping name: ETHYL ACETATE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

5450 Oil Stain Remover 1000 ml; 5450 Oil Stain Remover 1000 ml

Revision date: 06.02.2024

Product code: 70444

Page 9 of 9

IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 93,88 %, 844,92 g/l

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Solvent	IS, PW	-	9a, 35	7, 8a, 10, 19, 28	4, 8d	-	38, 105	
2	Washing and cleaning products	IS, PW, C	-	35	7, 11, 19, 28	4, 8d	-	105	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)