

18.08.2020

Kit Components

Product code	Description
--------------	-------------

1680-200816	ergo 1680
--------------------	------------------

Components:

1678-200807	ergo 1678 - Component A ergo 1680
1664-200407	ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 1678 - Component A ergo 1680

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41- 58-272 0 272

- Further information obtainable from: ergo@kisling.com

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS05 GHS07 GHS08 GHS09

- Signal word Danger

- Hazard-determining components of labelling:

Glycerin formal methacrylate

methacrylic acid

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 1)

- Precautionary statements

- P261 Avoid breathing vapours.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

- Labelling of packages where the contents do not exceed 125 ml**- Hazard pictograms**

GHS05 GHS07 GHS08 GHS09

- Signal word Danger**- Hazard-determining components of labelling:**

Glycerin formal methacrylate
 methacrylic acid
 Propylidynetrimethanol, ethoxylated, esters with acrylic acid
 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate

- Hazard statements

H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.
 H361 Suspected of damaging fertility or the unborn child.

- Precautionary statements

- P261 Avoid breathing vapours.
 P280 Wear protective gloves / eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

- 2.3 Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

EC number: 945-527-5	Glycerin formal methacrylate Repr. 2, H361; Aquatic Chronic 3, H412	> 30 - ≤ 50%
CAS: 79-41-4 EINECS: 201-204-4 Index number: 607-088-00-5 Reg.nr.: 01-2119463884-26-xxxx	methacrylic acid Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Flam. Liq. 4, H227	≥ 3 - < 5%
CAS: 28961-43-5 NLP: 500-066-5 Reg.nr.: 01-2119489900-30-xxxx	Propylidynetrimethanol, ethoxylated, esters with acrylic acid Eye Irrit. 2, H319; Skin Sens. 1, H317	> 1 - ≤ 5%
CAS: 52628-03-2 EINECS: 258-053-2	2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate Eye Dam. 1, H318; Skin Irrit. 2, H315	> 1 - < 3%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 2)		
CAS: 103671-44-9 Reg.nr.: 01-2119979579-10-xxxx	N,N-Bis-(2-hydroxyethyl)-para-toluidine, ethoxylated Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥ 0.1 - < 1%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥ 0.1 - < 1%
CAS: 91-66-7 EINECS: 202-088-8 Index number: 612-054-00-8	N,N-diethylaniline Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 2, H411	≥ 0.25 - ≤ 1%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥ 0.25 - ≤ 1%
CAS: 112-55-0 EINECS: 203-984-1	dodecane-1-thiol Skin Corr. 1C, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥ 0.1 - < 0.25%
CAS: 102-82-9 EINECS: 203-058-7	tributylamine Acute Tox. 3, H311; Acute Tox. 1, H330; Acute Tox. 4, H302; Skin Irrit. 2, H315	≤ 1%
CAS: 26741-53-7	3,9-Bis(2,4-di-tert.-butyl phenoxy)-2,4,8,10.tetroxa- 3,9-diphosphaspiro[5.5]undecane Aquatic Chronic 1, H410	≥ 0.025 - < 0.25%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting; seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 3)

- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire - and explosion protection: No special measures required.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep receptacle tightly sealed.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13

- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

79-41-4 methacrylic acid

MAK (Switzerland) Short-term value: 360 mg/m³, 100 ppm

Long-term value: 180 mg/m³, 50 ppm

SSc;

80-62-6 methyl methacrylate

MAK (Switzerland) Short-term value: 420 mg/m³, 100 ppm

Long-term value: 210 mg/m³, 50 ppm

S SSc;

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter ABEK

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid

Colour: White

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

- Flash point: >60 °C

- Flammability (solid, gas): Not applicable.

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not self-igniting.

- Explosive properties: Product does not present an explosion hazard.

- Explosion limits:

Lower: Not determined.

Upper: Not determined.

- Oxidising properties Not determined.

- Vapour pressure: Not determined.

- Density: Not determined.

- Relative density Not determined.

- Vapour density Not determined.

- Evaporation rate Not determined.

(Contd. on page 6)

-CHGEN-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 5)

- Solubility in / Miscibility with water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions
No dangerous reactions if used and stored according to specifications.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

79-41-4 methacrylic acid		
Oral	LD50	1,320 - 2,260 mg/kg (Rat, male/female)
Dermal	LD50	500 - 1,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	7,100 mg/l (Rat, male/female)
103671-44-9 N,N-Bis-(2-hydroxyethyl)-para-toluidine, ethoxylated		
Oral	LD50	619 mg/kg
Dermal	LD50	> 2,000 mg/kg
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (Rat, male/female)
Dermal	LD50	> 5,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	78,000 mg/l (Rat, male/female)
91-66-7 N,N-diethylaniline		
Oral	LD50	606 mg/kg (Rat, male/female)
Dermal	LD50	> 5,000 mg/kg (Rat, male/female)
Inhalative	LC50/4 h => LC50/4	1.92 mg/l (Rat, male/female)
102-82-9 tributylamine		
Inhalative	LC50/4 h	0.5 mg/l (Rat, male/female)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye damage.

(Contd. on page 7)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 6)

- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
No experimentally found toxicological data are available for this preparation.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Repr. 2
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging fertility or the unborn child.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.
Do not allow product to reach ground water, water course or undiluted sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|--|
| - 14.1 UN-Number | |
| - ADR, IMDG, IATA | UN3082 |
| - 14.2 UN proper shipping name | |
| - ADR | 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (N,N-
DIETHYLANILINE, dodecane-1-thiol) |

(Contd. on page 8)

-CHGEN-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020


Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 7)

- IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N,N-DIETHYLANILINE, dodecane-1-thiol), MARINE POLLUTANT
- IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N,N-DIETHYLANILINE, dodecane-1-thiol)

- 14.3 Transport hazard class(es)**- ADR**

- Class	9 (M6) Miscellaneous dangerous substances and articles.
- Label	9

- IMDG, IATA

- Class	9 Miscellaneous dangerous substances and articles.
- Label	9

- 14.4 Packing group

- ADR, IMDG, IATA	III
-------------------	-----

- 14.5 Environmental hazards:

- Marine pollutant:	Product contains environmentally hazardous substances: dodecane-1-thiol
- Special marking (ADR):	Symbol (fish and tree)
- Special marking (IATA):	Symbol (fish and tree)

- 14.6 Special precautions for user

- Warning:	Miscellaneous dangerous substances and articles.
- Hazard identification number (Kemler code):	90
- EMS Number:	F-A,S-F
- Stowage Category	A

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

- Transport/Additional information:

ADR: SV375
 IMDG-Code: 2.10.2.7
 IATA-DGR: A197 (375)

- ADR

- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

- Transport category

3

- Tunnel restriction code

-

- Remarks:

SV375:
 Diese Stoffe unterliegen, wenn sie in Einzelverpackungen oder zusammengesetzten Verpackungen mit einer Nettomenge von höchstens 5 l flüssiger Stoffe oder einer Nettomasse von höchstens 5 kg fester Stoffe je Einzel- oder Innenverpackung befördert werden, nicht den

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 8)

- übrigen Vorschriften des ADR/RID, vorausgesetzt, die Verpackungen entsprechen den allgemeinen Vorschriften der Unterabschnitte 4.1.1.1, 4.1.1.2 und 4.1.1.4 bis 4.1.1.8.

- **IMDG**
 - **Limited quantities (LQ)** 5L
 - **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

- **Remarks:**
 2.10.2.7:
 Meeresschadstoffe in Einzelverpackungen oder zusammengesetzten Verpackungen mit einer Nettomenge je Einzel- oder Innenverpackung von höchstens 5 L bei Flüssigkeiten oder einer Nettomasse je Einzel- oder Innenverpackung von höchstens 5 kg bei festen Stoffen unterliegen keinen anderen auf Meeresschadstoffe anwendbaren Vorschriften dieses Codes, sofern die Verpackungen die allgemeinen Vorschriften in 4.1.1.1, 4.1.1.2 und 4.1.1.4 bis 4.1.1.8 erfüllen. Im Falle von Meeresschadstoffen, die auch die Kriterien für die Aufnahme in eine andere Klasse erfüllen, finden alle Vorschriften dieses Codes, die für etwaige weitere Gefahren gelten, weiterhin Anwendung.

- **IATA**
 - **Remarks:** A 197 (375):
 These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

- **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N,N-DIETHYLANILINE, DODECANE-1-THIOL), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **National regulations:**

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 1

Revision: 18.08.2020

Trade name: ergo 1678 - Component A ergo 1680

(Contd. of page 9)

- Relevant phrases

H225 Highly flammable liquid and vapour.
 H227 Combustible liquid.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H311 Toxic in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 4: Flammable liquids – Category 4
 Acute Tox. 4: Acute toxicity - oral – Category 4
 Acute Tox. 3: Acute toxicity - dermal – Category 3
 Acute Tox. 1: Acute toxicity - inhalation – Category 1
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- * Data compared to the previous version altered.

- CHGEN

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41- 58-272 0 272

- Further information obtainable from: ergo@kisling.com

- Department issuing MSDS: ergo@kisling.com

- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Org. Perox. E H242 Heating may cause a fire.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02



GHS07



GHS09

- Signal word Warning

- Hazard-determining components of labelling:

dibenzoyl peroxide

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

- Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

(Contd. on page 2)

CHGEN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 1)

- P280 Wear protective gloves / eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410 Protect from sunlight.
 P411+P235 Store at temperatures not exceeding 30°C. Keep cool.
- Additional information:**
 EUH205 Contains epoxy constituents. May produce an allergic reaction.

- Labelling of packages where the contents do not exceed 125 ml
 - Hazard pictograms



GHS02 GHS07 GHS09

- Signal word Warning
- Hazard-determining components of labelling:
 dibenzoyl peroxide
 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
- Hazard statements
 H317 May cause an allergic skin reaction.
- Precautionary statements
 P261 Avoid breathing vapours.
 P280 Wear protective gloves / eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
 - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
 - Description: Adhesive

- Dangerous components:

CAS: 94-36-0 EINECS: 202-327-6 Index number: 617-008-00-0 Reg.nr.: 01-2119511472-50-xxxx	dibenzoyl peroxide ----- Org. Perox. B, H241; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Eye Irrit. 2, H319; Skin Sens. 1, H317	> 30 - \leq 50%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-xxxx	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ----- Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	\geq 2.5 - < 5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
 Immediately remove any clothing soiled by the product.
 Put contaminated clothing in water to prevent fire.
- After inhalation:
 Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
After contact with skin, wash immediately with plenty of soap and water.
If skin irritation continues, consult a doctor.
 - **After eye contact:**
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
 - **After swallowing:**
Rinse out mouth and then drink plenty of water.
If swallowed, do not induce vomiting: seek medical advice and show this container or label.
 - **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
May cause fire. May re-ignite itself after fire is extinguished. This material increases the risk of fire and may aid combustion. In a fire or if heated, a pressure increase will occur and the container may burst. Runoff to sewer may create fire or explosion hazard.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**
Pick up mechanically.
Flush away residues with plenty of water.
Never use saw-dust or other flammable substances.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Never replace spilled product into original containers (danger of decomposition).
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 10 for information on "stability and reactivity".
See Section 13 for disposal information.

-CHGEN-

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
- **Information about fire - and explosion protection:**
Keep away from heat and direct sunlight.
The product may cause fire due to release of oxygen. May be explosive, when combined with flammable substances.
Violent release of gases on decomposition.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Store away from flammable substances.
Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
Store away from foodstuffs.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
Store in a cool place.
- **Maximum storage temperature:** 30 °C
- **Minimum storage temperature:** 5 °C
- **Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers):** 5.2
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

MAK (Switzerland)	Short-term value: 5 e mg/m ³ Long-term value: 5 e mg/m ³
-------------------	---

- DNELs

94-36-0 dibenzoyl peroxide

Dermal	Longterm System	6.6 mg/kg bw/day (General population)
Inhalative	Acute, System	6.6 mg/m ³ (General population)
	Longterm System	11.75 mg/m ³ (General population)

- PNECs

94-36-0 dibenzoyl peroxide

Oral	PNEC oral	6.67 mg/kg Food (General population)
	PNEC Freshwater	0.000602 mg/l (General population)
	PNEC Freshwater sed	0.338 mg/kg (General population)
	PNEC Marinewater	0.000602 mg/l (General population)
	PNEC Soil	0.0758 mg/kg (General population)
	PNEC STP	0.35 mg/l (General population)
	PNEC Marinewater sed	0.0338 mg/kg (General population) No burden expected.

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

-CHGEN-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 4)

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Protection of hands:

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Tightly sealed goggles

- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Pasty

Colour: Blue

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not applicable.

- Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

- Flash point: Not applicable.

- Flammability (solid, gas): May cause fire.

- Decomposition temperature: ≥ 50 °C (SADT)

- Auto-ignition temperature: Product is not self-igniting.

- Explosive properties: Product does not present an explosion hazard.

- Explosion limits:

Lower: Not determined.

Upper: Not determined.

- Oxidising properties: Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 5)

- Density at 20 °C:	1.15 g/cm ³
- Relative density	Not determined.
- Vapour density	Not applicable.
- Evaporation rate	Not applicable.
- Solubility in / Miscibility with water:	Insoluble.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
- 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
SADT (Self-Accelerating Decomposition Temperature): is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport.
A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the given temperature. Contact with incompatible substances can cause decomposition at or below the SADT.
Protect from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions** Reacts with heavy metals.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Metal-salts, amines
- **10.6 Hazardous decomposition products:**
No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	11,400 mg/kg (Rat, male/female)
------	------	---------------------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
No experimentally found toxicological data are available for this preparation.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)

- CHGEN -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. of page 6)

SECTION 12: Ecological information

- 12.1 Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- Ecotoxicological effects:

- **Remark:** Very toxic for fish

- Additional ecological information:

- General notes:

Also very poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods

- **Recommendation** Disposal must be made according to official regulations.

- Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number

- **ADR, IMDG, IATA**

UN3108

- 14.2 UN proper shipping name

- **ADR**

3108 ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide), ENVIRONMENTALLY HAZARDOUS

- **IMDG**


ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide), MARINE POLLUTANT

- **IATA**

ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)

- 14.3 Transport hazard class(es)

- **ADR**



- **Class**

5.2 (P1) Organic peroxides.

(Contd. on page 8)

-CHGEN-

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 7)

- Label 5.2

- IMDG



- Class 5.2 Organic peroxides.

- Label 5.2

- IATA



- Class 5.2 Organic peroxides.

- Label 5.2

- 14.4 Packing group

- ADR, IMDG, IATA Void

- 14.5 Environmental hazards:

- Marine pollutant: Symbol (fish and tree)

- Special marking (ADR): Symbol (fish and tree)

- 14.6 Special precautions for user Warning: Organic peroxides.

- Hazard identification number (Kemler code): -

- EMS Number: F-J,S-R

- Segregation groups Peroxides

- Stowage Category D

- Stowage Code SW1 Protected from sources of heat.

- Segregation Code SG35 Stow "separated from" SGG1-acids

SG36 Stow "separated from" SGG18-alkalis.

- 14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ) 500 g

- Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

- Transport category 2

- Tunnel restriction code D

- IMDG

- Limited quantities (LQ) 500 g

- Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

- UN "Model Regulation":

UN 3108 ORGANIC PEROXIDE TYPE E, SOLID
(D I B E N Z O Y L P E R O X I D E), 5 . 2 ,
ENVIRONMENTALLY HAZARDOUS

CHGEN

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2020

Version number 5

Revision: 18.08.2020

Trade name: ergo 1664 - Component B ergo 1665, ergo 1675, ergo 1680

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- National regulations:

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H241 Heating may cause a fire or explosion.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B

Org. Perox. E: Organic peroxides – Type E/F

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- * **Data compared to the previous version altered.**

CHGEN